according to 1907/2006/EC, Article 31

Printing date 29.11.2022 Version number 2 (replaces version 1)



Revision: 08.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Q 70-421 1K black matt
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Q-Company Int. GmbH

Lentföhrdener Strasse 12 – 14

D-24576 Weddelbrook, Germany

msds@grefinish.com

Tel +49 (0)4192 891420

www.qrefinish.com

· 1.4 Emergency telephone number: +49 (0)551-19240 (Giftinformationszentrum-Nord)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

n-Butvl acetate

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2-Methoxy-1-methylethyl acetate

cobalt bis(2-ethylhexanoate)

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 29.11.2022 Version number 2 (replaces version 1)



Trade name: Q 70-421 1K black matt

(Contd. of page 1)

Revision: 08.11.2022

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
L	n-Butyl acetate	<15%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♠ Flam. Liq. 3, H226; ♠ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics † Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	2.5-<10%
	2-Methoxy-1-methylethyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	2.5-<10%
EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-<2.5%

according to 1907/2006/EC, Article 31

Printing date 29.11.2022 Version number 2 (replaces version 1) Revision: 08.11.2022

Trade name: Q 70-421 1K black matt

		(Contd. of page 2)
CAS: 2457-01-4	barium bis(2-ethylhexanoate)	<1%
EINECS: 219-535-8	♠ Repr. 2, H361d; ♠ Eye Dam. 1, H318; ♠ Acute Tox. 4, H302; Acute Tox. 4, H332	
CAS: 136-52-7	cobalt bis(2-ethylhexanoate)	<i>≥</i> 0.1-<0.25%
EINECS: 205-250-6	& Repr. 1B, H360Fd; 🕸 Aquatic Acute 1, H400; 🕦 Eye Irrit.	
Reg.nr.: 01-2119524678-29	2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	
CAS: 22464-99-9	2-ethylhexanoic acid, zirconium salt	<1%
EINECS: 245-018-1	& Repr. 2, H361d	
Reg.nr.: 01-2119979088-21		
CAS: 85203-81-2	Hexanoic acid, 2-ethyl-, zinc salt, basic	<1%
EINECS: 286-272-3	Repr. 2, H361d; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	
CAS: 162627-17-0	Fatty acids, C18-unsatd., dimers, reaction products with N,N-	<0.1%
EC number: 605-296-0	dimethyl-1,3-propanediamine and1,3-propanediamine	
Reg.nr.: 01-2119970640-38	💠 Skin Sens. 1A, H317	
· Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:


Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

according to 1907/2006/EC, Article 31



Trade name: Q 70-421 1K black matt

Printing date 29.11.2022

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

	8.1 Control parameters Ingredients with limit values that require monitoring at the workplace:		
	6-4 n-Butyl acetate		
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm		
1330-	20-7 Xylene		
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV		
108-6	5-6 2-Methoxy-1-methylethyl acetate		
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk		
100-4	1-4 Ethylbenzene		
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk		
112-0	7-2 2-Butoxyethyl acetate		
WEL	Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk		
136-5	2-7 cobalt bis(2-ethylhexanoate)		
WEL	Long-term value: 0.1 mg/m³ as Co; Carc, Sen		

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Version number 2 (replaces version 1) Revision: 08.11.2022

Trade name: Q 70-421 1K black matt

(Contd. of page 4)

Ingredients with biological limit values:

1330-20-7 Xylene

Printing date 29.11.2022

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

REFINISH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.11.2022 Version number 2 (replaces version 1) Revision: 08.11.2022

Trade name: Q 70-421 1K black matt

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic
· Odour threshold: Not determined.

• Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling

range 124-128 °C (123-86-4 n-Butyl acetate)

· Flammability Flammable.

Lower and upper explosion limit

• Lower: 1.2 Vol % (123-86-4 n-Butyl acetate) • Upper: 7.5 Vol % (123-86-4 n-Butyl acetate)

• Flash point: 24 °C (DIN 53213)

• Ignition temperature: 315 °C (DIN 51794, 108-65-6 2-Methoxy-1-methylethyl

acetate)

Decomposition temperature:pHNot determined.Not determined.

· Viscosity:

• Kinematic viscosity at 20 °C 80 s (DIN 53211/4)
• Dynamic: Not determined.

Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 10.7 hPa (123-86-4 n-Butyl acetate)

· Density and/or relative density

Density at 20 °C: 1.281 g/cm³ (DIN 53217)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 37.05 % *· Solids content (weight-%):* 62.9 %

• Change in condition • Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void
· Self-reactive substances and mixtures Void

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Printing date 29.11.2022 Version number 2 (replaces version 1) Revision: 08.11.2022

Trade name: Q 70-421 1K black matt

(Contd. of page 6) · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:


Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 8)



Safety data sheet according to 1907/2006/EC, Article 31





Trade name: Q 70-421 1K black matt

(Contd. of page 7)

Revision: 08.11.2022

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name		
· ADR	UNI 263 PAINT	
· IMDG, IATA	PAINT	
· 14.3 Transport hazard class(es)		
· ADR		
· Class	3 (F1) Flammable liquids.	
· Label	3 (11) 1 tummaote tiquitus.	
· IMDG, IATA		
· Class	3 Flammable liquids.	
· Label	3	
· 14.4 Packing group		
· ADR, IMDĞ, İATA	III	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code):	30	
EMS Number:	F-E, <u>S-E</u>	
· Stowage Category	A	
· 14.7 Maritime transport in bulk according to IM		
instruments	Not applicable.	
· Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	5L	

REFINISH

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.11.2022 Version number 2 (replaces version 1) Revision: 08.11.2022

Trade name: Q 70-421 1K black matt

	(Contd. of page
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	≤ 450 l: -
·IMDG	
· Limited quantities (LQ)	5L
Remarks:	≤ 30 l: -
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2 (replaces version 1)



Trade name: Q 70-421 1K black matt

Printing date 29.11.2022

(Contd. of page 9)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Repr. 1B: Reproductive toxicity - Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.