
Product name	:	MoTip Vaseline Spray	
Article number	:	090302	
Supplier / Producer	:	MOTIP DUPLI B.V.	
		Wolframweg 2	
		NL-8471 XC WOLVEGA	
		Telephone number	+31 561 – 69 44 00
		Telefax number	+31 561 – 69 44 31

Product description

High quality transparent, universal lubricant and preservative.

Applications

Battery poles
Audio controls
Fasteners (screws, bolts, nuts and nails)
Antennas
Electrical Connections
Protection for ultra light material (ultra light planes, wind turbines)

Product characteristics

Water-repellent
Excellent adhesion
Prevents wear and sticking
Can be used in the food industry
Resistant to weather influences
Resistant to weak acids and bases
Excellent corrosion prevention
Misty spray pattern

Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	Vaseline
VOC-content	:	Approximately 85% w/w
Colour	:	White
Scent	:	Characteristic
Relative density at 20°C	:	0,89 g/ml
Yield	:	1,11 g/sec
Vapour pressure at 20°C	:	3 to 4 bar
4 Ball EP-test (ASTM D 2596)	:	3136 N
4 Ball Wear-test (ASTM D 2266)	:	< 0,4 mm
Drop point	:	42°C – 60°C
Temperature resistant	:	-30°C tot +160°C
pH-value	:	Neutral



Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Apply vaseline spray in a thin layer.
Optimum lubrication is obtained after evaporation of the solvent.