




## 00665 – HYDROCLEANER SLOW



Ready for use



Use clean industrial paper/cloth and wipe

### DESCRIPTION

Anti-silicone detergent, antistatic, water-borne dust-proof slow cleaner.

### USE

It removes silicones from the surface giving an antistatic effect. Suitable to clean substrates or pre-existent coatings. Can be used to degrease small, bare metal surfaces. To degrease large metal surfaces use 00695 SILICONE REMOVER SLOW.

Suggested before HYDROFAN BASECOAT.

### CHARACTERISTICS

- Solvent free water-borne product (Volatile organic compounds = 0)
- Fast evaporation suitable for use at temperature above 25°C.
- Good detergent power
- Good anti-static power
- Non-aggressive even on single-pack nitrocombi and synthetic coatings
- To remove tar spots use 00695 SILICONE REMOVER SLOW

### SUBSTRATE PREPARATION

The surface must be ready to be coated.

### APPLICATION

By using clean rags or industrial paper, work as follows:

- Wipe the surface with a rag or paper soaked in detergent.
- Before the product has evaporated, dry with clean rag or paper. Never allow the product to evaporate on the substrate.

**DIR 2004/42/CE: Preparatory and cleaning IIB/a – VOC ready for use 200 g/l**

**This product ready for use contains at most 0 g/l VOC**

### OVERCOAT WITH

Any product within the Lechler Car Refinish range.

### NOTE

Keep warm, do not store at temperatures below +5 °C.

**TECHNICAL DATA SHEET N° 0618-GB**

**UPDATED 02/2008**

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.