




Technical Data Sheet n° 0642-GB


ENERGY SPRAY LINE



EL085 – ESL UHS FADE-OUT BLENDER



Ready for use



Air drying at 20° C:
1-5 min.

DESCRIPTION

Aerosol fade-out blender, especially for UHS finishes.

USE

Special product used in car refinish to fade out UHS solvent-based topcoats and clearcoats.

CHARACTERISTICS

- Easy to use - ready for use (Aerosol)
- Apply directly after fade-out
- Fast flash-off
- High solvent power making the fade-out uniform

SUBSTRATE PREPARATION

Application of HYDROFAN basecoat + MACROFAN UHS CLEARCOATS or topcoat MACROFAN MAC4.

APPLICATION

Spraying.

Ready for use. Shake well 1-2 minutes before use.

Apply immediately after the fade-out.

Spray temperature: 15-30° C

N° of coats: 1-2 on the fade-out and on the adjacent zone

Spray distance: 20-25 cm

DIR 2004/42/CE: Special finishes IIB/e – VOC ready for use 840 g/l

This product ready for use contains at most 840 g/l VOC

DRYING TIMES


Air drying at 20°C

1-5 minutes

Polishing: if necessary after topcoat through-drying.

NOTES

Do not apply directly on the matt basecoat HYDROFAN, but on MACROFAN UHS CLEARCOATS and on the topcoat MACROFAN MAC4.



ATTENTION: After use turn the aerosol upside down and spray the rest out of the supplying pipe in order to avoid blockage problems during the storage time before the following use.

SHELF LIFE AT 20°C: 24 months

TECHNICAL DATA SHEET N° 0642-GB
UPDATED 10/2008

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.