according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16

Revision Date 18.05.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	POLYFAN THINNER
Product code	:	L0000845

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	: Paints, varnishes and enamels
Chemical nature	: Thinner for coatings

#### 1.3 Details of the supplier of the safety data sheet

Company	: Lechler SpA
	Via Cecilio 17
	22100 Como- CO-
Telephone	: +39031586111
Telefax	: +39031586206
E-mail address	: safety@lechler.eu
Responsible/issuing person	

#### 1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299 This telephone number is available during office hours only.

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 Serious eye damage, Category 1 Specific target organ toxicity - single exposure, Category 3, Central nervous system H225: Highly flammable liquid and vapour.H318: Causes serious eye damage.H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16	Revision Date 1	8.05.2018	Print Date 05.02.2019
Signal word :	Danger		
Hazard statements :	H225 H318 H336	Highly flammable liquid ar Causes serious eye dama May cause drowsiness or	age.
Precautionary statements :	EUH066Repeate cracking. <b>Prevention:</b> P210	d exposure may cause skin Keep away from heat, hot	t surfaces, sparks,
	P233 P261	open flames and other igr smoking. Keep container tightly close Avoid breathing dust/ fum	sed.
	P280	vapours/ spray. Wear protective gloves/ e protection.	0
	<b>Response:</b> P305 + P351 + P	2338 + P310 IF IN EYES: with water for several min contact lenses, if present Continue rinsing. Immedia POISON CENTER/doctor	utes. Remove and easy to do. ately call a
	P370 + P378	In case of fire: Use dry sa or alcohol-resistant foam	

Hazardous components which must be listed on the label:

- 141-78-6 ethyl acetate
- 78-83-1 2-methylpropan-1-ol

### 2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Liquid

## Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No	[%]
	Registration number	1272/2008)	
ethyl acetate	141-78-6	Flam. Liq. 2; H225	>= 70 - < 90

according to Regulation (EC) No. 830/2015

# **POLYFAN THINNER**

Version 2.16

Revision Date 18.05.2018

Print Date 05.02.2019

	205-500-4 01-2119475103-46	Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	
2-methylpropan-1-ol	78-83-1 201-148-0 01-2119484609-23	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 5 - < 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice	<ul> <li>When symptoms persist or in all cases of doubt seek medical advice.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
If inhaled	<ul> <li>Remove to fresh air.</li> <li>Keep patient warm and at rest.</li> <li>If breathing is irregular or stopped, administer artificial respiration.</li> <li>If unconscious, place in recovery position and seek medical advice.</li> </ul>
In case of skin contact	<ul> <li>Take off all contaminated clothing immediately.</li> <li>Wash skin thoroughly with soap and water or use recognized skin cleanser.</li> <li>Do NOT use solvents or thinners.</li> <li>Put shower on working place</li> </ul>
In case of eye contact	<ul> <li>Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.</li> <li>Seek medical advice.</li> <li>Put eye-washer on working place</li> <li>Remove contact lenses.</li> </ul>
If swallowed	: If accidentally swallowed obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.
2 Most important symptoms and	l effects, both acute and delayed
Symptoms	· No information available

# 4.2

Symptoms	: No information available.
Risks	: No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: The first aid procedure should be established in consultation
	with the doctor responsible for industrial medicine.

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16

Revision Date 18.05.2018

Seek medical advice.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media	<ul> <li>Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.</li> <li>Keep containers and surroundings cool with water spray.</li> </ul>
Unsuitable extinguishing media	: Do NOT use water jet.

#### 5.2 Special hazards arising from the substance or mixture

	Specific hazards during firefighting	<ul> <li>As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).</li> <li>Exposure to decomposition products may be a hazard to health.</li> <li>Cool closed containers exposed to fire with water spray.</li> <li>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.</li> <li>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.</li> </ul>
5.3	Advice for firefighters	

# Special protective equipment : Wear self-contained breathing apparatus for firefighting if necessary.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

|--|

#### 6.2 Environmental precautions

Environmental precautions	<ul> <li>Try to prevent the material from entering drains or water courses.</li> </ul>
	If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and materials for containment and cleaning up

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16	Revision Date 18.05.2018	Print Date 05.02.2019
Methods for cleaning up	: Clean with detergents. Avoid solvent Contain and collect spillages with nor materials, e.g. sand, earth, vermiculi and place in a suitable container. Th should be cleaned up immediately wi decontaminant. One possible (flamm comprises water (45 parts by volume (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts) alternative is sodium carbonate (5 parts)	n-combustible absorbent te, diatomaceous earth le contaminated area ith a suitable nable) decontaminant e)/ethanol or isopropanol ). A non-flammable
	Pick up and transfer to properly label Clean contaminated surface thoroug Dam up. Soak up with inert absorbent materia hazardous waste.	hly.

### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling :	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Use only in area provided with appropriate exhaust ventilation.</li> <li>Avoid contact with skin, eyes and clothing.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Avoid inhalation of vapour or mist.</li> <li>For personal protection see section 8.</li> <li>Thoroughly mix before using</li> <li>After using, store in a well-sealed container</li> </ul>
Advice on protection against : fire and explosion	Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage	:	Observe label precautions.
areas and containers		Containers which are opened must be carefully resealed and
		kept upright to prevent leakage.

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16	Revision Date 18.05.2018	Print Date 05.02.2019	
	floors. Vapours may form explosive mixtu Electrical installations / working ma the technological safety standards. Keep away from sources of ignition Store between 5° an 35°C in a dry from source of heat, ignition and di	Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Electrical installations / working materials must comply with the technological safety standards. Keep away from sources of ignition - No smoking. Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight. Store in accordance with the particular national regulations.	
Advice on common storage	: Keep away from oxidizing agents a materials.	and strongly acid or alkaline	
7.3 Specific end use(s)			
: This information is not available.			

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
ethyl acetate	141-78-6	TWA	400 ppm		ACGIH
2- methylpropan- 1-ol	78-83-1	TWA	50 ppm	2007-01-01	ACGIH

### 8.2 Exposure controls

### Personal protective equipment

Respiratory protection	<ul> <li>Apply technical measures to comply with the occupational exposure limits.</li> <li>This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.</li> <li>Respirator with combination filter for vapour/particulate (EN 141)</li> </ul>
Hand protection	: Solvent-resistant gloves (butyl-rubber) recomended. For prolonged or repeated contact use protective gloves. Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16	Revision Date 18.05.2018	Print Date 05.02.2019
Eye protection	<ul> <li>conditions under which the product is danger of cuts, abrasion, and the cont If used in solution, or mixed with other conditions which differ from EN 374, or the CE approved gloves.</li> <li>Barrier creams may help to protect the they should however not be applied or occurred.</li> <li>Skin should be washed after contact. Wash your hands and put on barrier c</li> <li>Chemical resistant goggles must be weighted or occurred.</li> </ul>	act time. substances, and under ontact the supplier of e exposed areas of skin, nce exposure has
Skin and body protection	: Skin should be washed after contact. Personnel should wear protective cloth Flame retardant antistatic protective c Workers should wear antistatic footwe	lothing.
Environmental exposure control	S	
General advice	<ul> <li>Try to prevent the material from enteric courses.</li> <li>If the product contaminates rivers and respective authorities.</li> </ul>	•

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like
Flash point	: 0 - < 21 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: Not applicable
рН	: not determined
Freezing point	: Not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16	Revision Date 18.05.2018	Print Date 05.02.201
Density	: 0,9014 g/cm3	
Water solubility	: not determined	
Partition coefficient: n- octanol/water	: No data available	
Solubility in other solvents	: not determined	
Flow time	: 10 s 4 mm Method: ASTM D 1200 '82	
Relative vapour density	: Not applicable	
Evaporation rate	: not determined	
9.2 Other information		
Solids by weight	: 5,25 %	
Volatile organic compounds (VOC) content	: 94,74 %	
SECTION 10: Stability and re	activity	
10.1 Reactivity		
None reasonably foreseeable		
10.2 Chemical stability		
The product is chemically sta	ble.	
10.3 Possibility of hazardous rea	octions	
Hazardous reactions	: No dangerous reaction known unde	er conditions of normal use.
10.4 Conditions to avoid		
Conditions to avoid	<ul> <li>Our products were manufactured in standards to avoid decomposition a defined conditions.</li> <li>Taking the product type into accoun the product in its original packaging it.</li> </ul>	and degrading under the attraction in the attraction in the attraction is advisable to leave

### 10.5 Incompatible materials

 Materials to avoid
 : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

Hazardous decomposition	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of
-------------------------	---

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16	Revision Date 18.05.2018	Print Date 05.02.2019
products	nitrogen (NOx), dense black smoke.	
Thermal decomposition	: Not applicable	

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

<u>Product</u>
----------------

Tiouuce	
Acute inhalation toxicity :	Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects., Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness., Inhalation of airborne droplets may cause irritation of the respiratory tract.
Skin corrosion/irritation :	Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
Further information :	The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Toxicity to fish

Remarks: No data is available on the product itself.

#### 12.2 Persistence and degradability

Biodegradability	:	No data available
------------------	---	-------------------

:

### 12.3 Bioaccumulative potential

Bioaccumulation	: No data available

### 12.4 Mobility in soil

Mobility : No data available

#### 12.5 Results of PBT and vPvB assessment

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16

Revision Date 18.05.2018

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

Additional ecological	: There is no data available for this product.
information	

### **SECTION 13: Disposal considerations**

#### **13.1 Waste treatment methods**

Product	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Disposal together with normal waste is not allowed. Special disposal required according to local regulations.</li> </ul>
Contaminated packaging	<ul> <li>Empty containers should be taken to an approved waste handling site for recycling or disposal.</li> <li>According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.</li> <li>The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.</li> <li>The following Waste Codes are only suggestions:150110*</li> </ul>

### **SECTION 14: Transport information**

#### 14.1 UN number

ADR	: UN 1263
IMDG	: UN 1263
ΙΑΤΑ	: UN 1263

#### 14.2 Proper shipping name

ADR	PAINT RELATED MATERIAL
IMDG	PAINT RELATED MATERIAL
ΙΑΤΑ	PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

ADR	: 3
IMDG	: 3
ΙΑΤΑ	: 3

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16

Revision Date 18.05.2018

Print Date 05.02.2019

### 14.4 Packing group

ADR		
Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3
IMDG		
Packing group	:	II
Labels	:	3
EmS Code	:	F-E,S-E
ΙΑΤΑ		
Packing group	:	II
Labels	:	3
14.5 Environmental hazards		
ADR		
Environmentally hazardous	:	no
IMDG		
Marine pollutant	:	no
ΙΑΤΑ		
Environmentally hazardous	:	no
14.6 Special precautions for user		

# 14.6 Special precautions for user

Not applicable

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of : Not applicable Substances of Very High Concern for Authorisation (Article 59).

11 / 13

according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16

Revision Date 18.05.2018

REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	: Banned and/or restricted
78-83-1	2-methylpropan-1-ol
MAL-Code-Number	: 4-1 (1993) 1.605-m3 air/10 g
Risk classification according to VbF	: Flash point less than 21 °C, at 15 °C not miscible in water Specially dangerous flammable liquids
Water contaminating class (Germany)	: slightly water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

#### 15.2 Chemical safety assessment

No data is available on the product itself.

### **SECTION 16: Other information**

#### Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

### SAFETY DATA SHEET according to Regulation (EC) No. 830/2015

# POLYFAN THINNER

Version 2.16

Revision Date 18.05.2018

Print Date 05.02.2019

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.