Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : HYDROFAN COOL YELLOW

Product code : LNHF0110

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Paints, varnishes and enamels

Substance/Mixture

Telephone

Chemical nature : Mono compound enamel - finish coat

1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA

Via Cecilio 17 22100 Como- CO-

: +39031586111

Telefax : +39031586206 E-mail address : safety@lechler.eu

Responsible/issuing person

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during

office hours only. (8.00-18.00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

Precautionary statements : **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/

vapours/ spray.

P272 Contaminated work clothing should not be

allowed out of the workplace.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Disposal:

P501 Dispose of contents/ container to an

approved waste disposal plant.

Hazardous components which must be listed on the label:

• 2682-20-4 2-methylisothiazol-3(2H)-one

• 55965-84-9 reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-

isothiazol-3-one (3:1)

2.3 Other hazards

None known.

The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Water pigmented dispersion

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
2-butoxyethanol	111-76-2 203-905-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
N-methyl-2-pyrrolidone	872-50-4 212-828-1 01-2119472430-46	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 1B; H360D STOT SE 3; H335	>= 0,1 - < 0,3
2-methylisothiazol- 3(2H)-one	2682-20-4 220-239-6	Acute Tox. 3; H301 Acute Tox. 2; H330	>= 0,0015 - < 0,0025

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

		Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 (Acute M=10) (Chronic M=1)	
reaction mass of 5- chloro-2-methyl-2H- isothiazol-3-one and 2- methyl-2H-isothiazol-3- one (3:1)	55965-84-9	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 (Acute M=100) (Chronic M=100)	<= 0,0002

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : When symptoms persist or in all cases of doubt seek medical

advice.

Never give anything by mouth to an unconscious person.

If inhaled : Remove to fresh air.

Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial

respiration.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Take off all contaminated clothing immediately.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Do NOT use solvents or thinners. Put shower on working place

In case of eye contact : Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart.

Seek medical advice.

Put eye-washer on working place

Remove contact lenses.

If swallowed : If accidentally swallowed obtain immediate medical attention.

Do NOT induce vomiting.

Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation

with the doctor responsible for industrial medicine.

Seek medical advice.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Keep containers and surroundings cool with water spray.

Unsuitable extinguishing

media

: Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: As the product contains combustible organic components, fire

will produce dense black smoke containing hazardous

products of combustion (see section 10).

Exposure to decomposition products may be a hazard to

health.

Cool closed containers exposed to fire with water spray.
Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ventilate the area.

Refer to protective measures listed in sections 7 and 8.

Material can create slippery conditions.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

If the product contaminates rivers and lakes or drains inform

respective authorities.

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Use only in area provided with appropriate exhaust ventilation.

Avoid contact with skin, eyes and clothing.

Smoking, eating and drinking should be prohibited in the

application area.

Avoid inhalation of vapour or mist. For personal protection see section 8.

Thoroughly mix before using

After using, store in a well-sealed container

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Observe label precautions.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with the particular national regulations. Store between 5° an 35°C in a dry, well ventilated place away

from source of heat, ignition and direct sunlight.

No smoking.

Electrical installations / working materials must comply with

the technological safety standards.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline

materials.

German storage class : 10 Combustible liquids

7.3 Specific end use(s)

: This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

- 6						
	Components	CAS-No.	Value	Control	Update	Basis

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

				parameters		
2-	1	11-76-2	TWA	20 ppm	2000-06-16	2000/39/EC
butoxyethanol				98 mg/m3		
Further information	:	skin: Identi	skin: Identifies the possibility of significant uptake through the skinIndicative			
			STEL	50 ppm 246 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identi	skin: Identifies the possibility of significant uptake through the skinIndicative			
1-methyl-2- pyrrolidone	8'	72-50-4	TWA	10 ppm 40 mg/m3	2009-12-19	2009/161/EU
Further information	:	skin: Identi	dentifies the possibility of significant uptake through the skinIndicative			
			STEL	20 ppm 80 mg/m3	2009-12-19	2009/161/EU
Further information	:	skin: Identi	fies the poss	ibility of significant upta	ake through the skinIn	dicative

DNEL

N-methyl-2-pyrrolidone : End Use: Workers

Exposure routes: Dermal

Potential health effects: Long-term systemic effects

Value: 4,8 mg/kg

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 14,4 mg/m3

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 40 mg/m3

PNEC

N-methyl-2-pyrrolidone : Fresh water

Value: 0,25 mg/l

Marine water Value: 0,025 mg/l

Fresh water sediment Value: 1,42 mg/kg

Marine sediment Value: 0,142 mg/kg

Soil

Value: 0,138 mg/kg

Sewage treatment plant Value: 10 mg/kg

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

8.2 Exposure controls

Personal protective equipment

Respiratory protection : Apply technical measures to comply with the occupational

exposure limits.

This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in

exceptional cases suitable respiratory equipment should be

worn only for a short period of time.

Respirator with combination filter for vapour/particulate (EN

141)

Hand protection : Latex gloves

For prolonged or repeated contact use protective gloves.

Protective gloves complying with EN 374.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of

the CE approved gloves.

Barrier creams may help to protect the exposed areas of skin,

they should however not be applied once exposure has

occurred.

Skin should be washed after contact.

Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Skin should be washed after contact.

Wear suitable protective clothing.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water

courses.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Odour : solvent-like

Flash point : $> 63 - 100 \,^{\circ}\text{C}$

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Revision Date 28.04.2020 Version 2.26 Print Date 05.05.2020

: not determined Ignition temperature

Lower explosion limit : No data available

Upper explosion limit : No data available

Auto-ignition temperature : Not applicable

рΗ : not determined

Freezing point : Not applicable

Boiling point : not determined

Vapour pressure : 1,000 hPa

at 50 °C

Density : 1,0324 g/cm3

Water solubility : not determined

Partition coefficient: n-

octanol/water

: No data available

Solubility in other solvents : not determined

Flow time : 40 s

6 mm

Method: ISO/DIN 2431 '84

Relative vapour density : Not applicable

Evaporation rate : not determined

9.2 Other information

Solids by weight : 21,51 %

Volatile organic compounds : 6,26 %

(VOC) content

Water content : 72,21 %

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety

standards to avoid decomposition and degrading under the

defined conditions.

Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring

it.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of

nitrogen (NOx), dense black smoke.

Thermal decomposition : Not applicable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation

method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation

method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause

removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.

Further information : The concentration of each substance should be borne in mind

in assessing the toxicological effects deriving from the

preparation.

Components:

N-methyl-2-pyrrolidone:

Acute oral toxicity : LD50: 4.150 mg/kg, Rat(male and female), OECD Test

Guideline 401

Acute inhalation toxicity : LC50: > 5,1 mg/l, 4 h, Rat, OECD Test Guideline 403

Acute dermal toxicity : LD50: > 5.000 mg/kg, Rat, OECD Test Guideline 402

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

12.1 Toxicity

Toxicity to fish

Remarks:

No data is available on the product itself.

Toxicity to fish

N-methyl-2-pyrrolidone : LC50: > 500 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

2-methyl-2H-isothiazol-3-one : 10 5-Chloro-2-methyl- : 100

3(2H)isothiazolone mixt. with 2-Methyl-3(2H)isothiazolone

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

N-methyl-2-pyrrolidone : NOEC: 12,5 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

12.2 Persistence and degradability

Biodegradability : No data available

12.3 Bioaccumulative potential

Bioaccumulation : No data available

12.4 Mobility in soil

Mobility : No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological

information

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Disposal together with normal waste is not allowed. Special

disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

handling site for recycling or disposal.

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.

The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

The following Waste Codes are only suggestions: 150110*

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 Proper shipping name

ADR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

ADR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product contains substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

872-50-4 N-methyl-2-pyrrolidone

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

: Banned and/or restricted

872-50-4 N-methyl-2-pyrrolidone
108-01-0 2-dimethylaminoethanol
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

MAL-Code-Number : 1-3 (1993)

190-m3 air/10 g

Storage class (TRGS 510) : 10: Combustible liquids

Risk classification according

to VbF

: Flash Point > 55 °C up to 100 °C, at 15 °C not miscible with

water

Water contaminating class

(Germany)

: slightly hazardous to water

VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Version 2.26	Revision Date 28.04.2020	Print Date 05.05.2020
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H360D	May damage the unborn child.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	

List of references

Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended). Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Key or legend to abbreviations and acronyms used in the safety data sheet

according to Regulation (EC) No. 830/2015

HYDROFAN COOL YELLOW

Version 2.26 Revision Date 28.04.2020 Print Date 05.05.2020

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO -International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.