according to Regulation (EC) No. 830/2015

## MACROBASE OXIDE YELLOW

Version 2.19

Revision Date 25.09.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	MACROBASE OXIDE YELLOW
Product code	:	L0MC0013

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	: Paints, varnishes and enamels
Substance/Mixture	
Chemical nature	: Coloured concentrated base

#### 1.3 Details of the supplier of the safety data sheet

Company	: Lechler SpA
	Via Cecilio 17
	22100 Como- CO-
Telephone	: +39031586111
Telefax	: +39031586206
E-mail address	: safety@lechler.eu
Responsible/issuing person	

#### 1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299 This telephone number is available during office hours only.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Specific target organ toxicity - single exposure, Category 3, Central nervous system H226: Flammable liquid and vapour. H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017		Print Date 04.02.2019
Signal word	: Warning		
Hazard statements	: H226 H336	Flammable liquid and van May cause drowsiness of	
Precautionary statements	: <b>Prevention:</b> P210	Keep away from heat, ho open flames and other ig	
	P261	smoking. Avoid breathing dust/ fun vapours/ spray.	ne/ gas/ mist/
	<b>Response:</b> P303 + P361 + F	P353 IF ON SKIN (or hair) immediately all contamina Rinse skin with water/sho	ated clothing.
	P304 + P340 + F	P312 IF INHALED: Remov air and keep comfortable a POISON CENTER/doc unwell.	for breathing. Call
	P370 + P378	In case of fire: Use dry sa or alcohol-resistant foam	
	<b>Storage:</b> P403 + P233	Store in a well-ventilated container tightly closed.	place. Keep

Hazardous components which must be listed on the label:

• 123-86-4 n-butyl acetate

### Additional Labelling:

EUH208 Contains: triisotridecyl phosphite, 2-hydroxyethyl methacrylate. May produce an allergic reaction.

#### 2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Fluid pigmented dispersion

### Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No	[%]
	Registration number	1272/2008)	

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19

Revision Date 25.09.2017

Print Date 04.02.2019

		1	1	
heptan-2-one	110-43-0	Flam. Liq. 3; H226	>= 5 - < 10	
	203-767-1	Acute Tox. 4; H302		
	01-2119902391-49	Acute Tox. 4; H332		
Phosphoric acid		Eye Irrit. 2; H319	>= 1 - < 5	
polyester (72243-				
070628, Germany)				
Hexanoic acid, 2-ethyl-,	85203-81-2	Eye Irrit. 2; H319	>= 0,25 - < 1	
zinc salt, basic	286-272-3	Skin Irrit. 2; H315		
,		Repr. 2; H361d		
		Aquatic Chronic 3; H412		
triisotridecyl phosphite	77745-66-5	Skin Sens. 1; H317	>= 0,1 - < 1	
51 1	278-758-9	,	,	
	01-2119487302-40			
2-hydroxyethyl	868-77-9	Skin Irrit. 2; H315	>= 0,1 - < 1	
methacrylate	212-782-2	Eye Irrit. 2; H319	,	
, ,	01-2119490169-29	Skin Sens. 1; H317		
		Note D		
Substances with a workplace exposure limit :				
n-butyl acetate	123-86-4	EUH066	>= 17,5 - < 20	
	204-658-1	Flam. Liq. 3; H226	, • _•	
	01-2119485493-29	STOT SE 3; H336		
	01-2110-00-00-20			

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice	: When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.
If inhaled	<ul> <li>Remove to fresh air.</li> <li>Keep patient warm and at rest.</li> <li>If breathing is irregular or stopped, administer artificial respiration.</li> <li>If unconscious, place in recovery position and seek medical advice.</li> </ul>
In case of skin contact	<ul> <li>Take off all contaminated clothing immediately.</li> <li>Wash skin thoroughly with soap and water or use recognized skin cleanser.</li> <li>Do NOT use solvents or thinners.</li> <li>Put shower on working place</li> </ul>
In case of eye contact	<ul> <li>Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.</li> <li>Seek medical advice.</li> <li>Put eye-washer on working place</li> <li>3 / 14</li> </ul>

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.2019	
	Remove contact lenses.		
If swallowed	<ul> <li>If accidentally swallowed obtain imme Do NOT induce vomiting. Keep at rest.</li> </ul>	ediate medical attention.	
4.2 Most important symptoms	and effects, both acute and delayed		
Symptoms	: No information available.		
Risks	: No information available.		
4.3 Indication of any immediate medical attention and special treatment needed			

Treatment	: The first aid procedure should be established in consultation
	with the doctor responsible for industrial medicine.
	Seek medical advice.

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

0 0	
Suitable extinguishing media	<ul> <li>Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.</li> <li>Keep containers and surroundings cool with water spray.</li> </ul>
Unsuitable extinguishing media	: Do NOT use water jet.
5.2 Special hazards arising from	the substance or mixture
Specific hazards during firefighting	<ul> <li>As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).</li> <li>Exposure to decomposition products may be a hazard to health.</li> <li>Cool closed containers exposed to fire with water spray.</li> <li>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.</li> <li>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.</li> </ul>

## 5.3 Advice for firefighters

Special protective equipment	:	Wear self-contained breathing apparatus for firefighting if
for firefighters		necessary.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.2019
Personal precautions	<ul> <li>Solvent vapours are heavier than air an floors.</li> <li>Ensure adequate ventilation.</li> <li>Use personal protective equipment.</li> <li>Evacuate personnel to safe areas.</li> <li>Keep people away from and upwind of solution.</li> </ul>	
6.2 Environmental precautions		
Environmental precautions	<ul> <li>Try to prevent the material from entering courses.</li> <li>If the product contaminates rivers and la respective authorities.</li> </ul>	-
6.3 Methods and materials for co	ontainment and cleaning up	
Methods for cleaning up	<ul> <li>Clean with detergents. Avoid solvents. Contain and collect spillages with non-comaterials, e.g. sand, earth, vermiculite, and place in a suitable container. The complexity should be cleaned up immediately with decontaminant. One possible (flammatic comprises water (45 parts by volume)/e (50 parts)/concentrated</li> <li>(d: 0.880) ammonia solution (5 parts). Alternative is sodium carbonate (5 parts)</li> </ul>	diatomaceous earth contaminated area a suitable ole) decontaminant ethanol or isopropanol A non-flammable
	Pick up and transfer to properly labelled Clean contaminated surface thoroughly Dam up. Soak up with inert absorbent material a hazardous waste.	
6.4 Reference to other sections		

#### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

# SECTION 7: Handling and storage

## 7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing.
	Smoking, eating and drinking should be prohibited in the
	application area.
	Avoid inhalation of vapour or mist.
	For personal protection see section 8.
	Thoroughly mix before using
	After using, store in a well-sealed container

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.2019
Advice on protection against fire and explosion	<ul> <li>Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.</li> <li>When transferring from one container to another apply earthing measures and use conductive hose material.</li> <li>No sparking tools should be used.</li> <li>The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.</li> <li>No smoking.</li> </ul>	
7.2 Conditions for safe storage, inc	cluding any incompatibilities	
Requirements for storage areas and containers	: Observe label precautions. Containers which are opened must be kept upright to prevent leakage. Solvent vapours are heavier than air floors.	-

### 7.3 Specific end use(s)

Advice on common storage

: This information is not available.

materials.

Vapours may form explosive mixtures with air.

Keep away from sources of ignition - No smoking.

from source of heat, ignition and direct sunlight.

the technological safety standards.

Electrical installations / working materials must comply with

Store between 5° an 35°C in a dry, well ventilated place away

Store in accordance with the particular national regulations.

: Keep away from oxidizing agents and strongly acid or alkaline

#### **SECTION 8: Exposure controls/personal protection**

#### **8.1 Control parameters**

Components	CAS-No.	Value	Control parameters	Update	Basis
n-butyl	123-86-4	TWA	150 ppm	2007-01-01	ACGIH
acetate			713 mg/m3		
		STEL	200 ppm	2007-01-01	ACGIH
			950 mg/m3		
heptan-2-one	110-43-0	TWA	50 ppm	2000-06-16	2000/39/EC
			238 mg/m3		
Further information	: skin: Identi	fies the poss	ibility of significant upta	ake through the skinIndic	ative
		STEL	100 ppm	2000-06-16	2000/39/EC
			475 mg/m3		

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19

Revision Date 25.09.2017

Print Date 04.02.2019

Further : skin: Ide information :	entifies the possibility of significant uptake through the skinIndicative
DNEL n-butyl acetate	<ul> <li>End Use: Professional use Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 7 ppm</li> <li>End Use: Professional use Exposure routes: Inhalation Potential health effects: Local effects Value: 48 mg/m3</li> </ul>
PNEC n-butyl acetate	: Water Value: 0,18 mg/l Soil Value: 0,093 mg/kg
xposure controls	
Personal protective equipm	ient
Respiratory protection	<ul> <li>Apply technical measures to comply with the occupational exposure limits.</li> <li>This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.</li> <li>Respirator with combination filter for vapour/particulate (EN 141)</li> </ul>
Hand protection	<ul> <li>Solvent-resistant gloves (butyl-rubber) For prolonged or repeated contact use protective gloves. Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact.</li> </ul>

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.2019
	Wash your hands and put on barrier cro	eams
Eye protection	: Chemical resistant goggles must be we	orn.
Skin and body protection	: Skin should be washed after contact. Working clothes must not consist of te dangerous melting behaviour in case o Personnel should wear protective cloth Workers should wear antistatic footwe	of fire. ning.
Environmental exposure con	rols	
General advice	: Try to prevent the material from enteri If the product contaminates rivers and respective authorities.	

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like
Flash point	: > 23 - 55 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: Not applicable
рН	: not determined
Freezing point	: Not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 1,2942 g/cm3
Water solubility	: not determined
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 59 s

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.2019
	6 mm Method: ISO/DIN 2431 '84	
Relative vapour density	: Not applicable	
Evaporation rate	: not determined	
9.2 Other information		
Solids by weight	: 73,7 %	
Volatile organic compounds (VOC) content	: 26,29 %	
SECTION 10: Stability and re	eactivity	
10.1 Reactivity		
None reasonably foreseeabl	e.	
10.2 Chemical stability		
The product is chemically sta	able.	
10.3 Possibility of hazardous re	actions	
Hazardous reactions	: No dangerous reaction known under	conditions of normal use.
10.4 Conditions to avoid		
Conditions to avoid	<ul> <li>Our products were manufactured in c standards to avoid decomposition an defined conditions.</li> <li>Taking the product type into account, the product in its original packaging the it.</li> </ul>	d degrading under the it is advisable to leave
10.5 Incompatible materials		
Materials to avoid	: Keep away from oxidizing agents, str strongly acid materials in order to avo	
10.6 Hazardous decomposition	products	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monox nitrogen (NOx), dense black smoke.	kide (CO), oxides of
	: Not applicable	

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

**Product** 

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.2019
Acute oral toxicity	: Acute toxicity estimate: > 2.000 m	g/kg, Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: > 20 mg/l, 4 h, method	vapour, Calculation
Skin corrosion/irritation	: Repeated or prolonged contact with the of natural fat from the skin resulting in o product may be absorbed through the sk	desiccation of the skin., The
Further information	: The concentration of each substance sho assessing the toxicological effects derive	
Components: heptan-2-one : Acute oral toxicity	: Acute toxicity estimate: 500 mg/kg point estimate	g, Converted acute toxicity

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Toxicity to fish : Remarks: No data is available on the product itself.

#### **12.2 Persistence and degradability**

Biodegradability : No data available

#### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

#### 12.4 Mobility in soil

Mobility	:	No data available
----------	---	-------------------

#### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.2019
12.6 Other adverse effects		

Additional ecological	: The product contains dangerous substances for the
information	environment (see chapter no 3).
	The concentration of each substance should be borne in mind
	in assessing the toxicological effects deriving from the
	preparation.

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Disposal together with normal waste is not allowed. Special disposal required according to local regulations.</li> </ul>
Contaminated packaging	<ul> <li>Empty containers should be taken to an approved waste handling site for recycling or disposal.</li> <li>According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.</li> <li>The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.</li> <li>The following Waste Codes are only suggestions: 150110*</li> </ul>

## **SECTION 14: Transport information**

### 14.1 UN number

ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263

### 14.2 Proper shipping name

ADR	PAINT
IMDG	PAINT
IATA	Paint

### 14.3 Transport hazard class(es)

ADR	: 3
IMDG	: 3

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.201
IATA	: 3	
4.4 Packing group		
ADR		
Packing group	: III	
Classification Code	: F1	
Hazard Identification Number	: 30	
Labels	: 3	
IMDG		
Packing group	: III	
Labels	: 3	
EmS Code	: F-E,S-E	
ІАТА		
Packing group	: III	
Labels	: 3	
4.5 Environmental hazards		
ADR		
Environmentally hazardous	: no	
IMDG		
Marine pollutant	: no	
IATA		
Environmentally hazardous	: no	
4.6 Special precautions for user		
Not applicable		

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  $12\ /\ 14$ 

according to Regulation (EC) No. 830/2015

# MACROBASE OXIDE YELLOW

Version 2.19	Revision Date 25.09.2017	Print Date 04.02.2019
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable	
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable	
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	: Banned and/or restricted	
123-86-4	n-butyl acetate	
108-65-6	2-methoxy-1-methylethyl acetate	
64742-95-6	Hydrocarbons, C9, aromatics	

123-86-4	n-butyl acetate
108-65-6	2-methoxy-1-methylethyl acetate
64742-95-6	Hydrocarbons, C9, aromatics
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

MAL-Code-Number	: 5-6 (1993)
	13.074-m3 air/10 g

Risk classification according to VbF	: Exempt see user defined free text
Water contaminating class	: water endangering

Water contaminating class	-	water endangering
(Germany)		VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

#### 15.2 Chemical safety assessment

No data is available on the product itself.

### **SECTION 16: Other information**

#### Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.

according to Regulation (EC) No. 830/2015

## MACROBASE OXIDE YELLOW

#### Version 2.19

Revision Date 25.09.2017

Print Date 04.02.2019

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.