according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21

Revision Date 21.12.2017

Print Date 04.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	MACROBASE RUBY RED
Product code	:	L0MC0043

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	: Paints, varnishes and enamels
Substance/Mixture	
Chemical nature	: Coloured concentrated base

1.3 Details of the supplier of the safety data sheet

Company	: Lechler SpA
	Via Cecilio 17
	22100 Como- CO-
Telephone	: +39031586111
Telefax	: +39031586206
E-mail address	: safety@lechler.eu
Responsible/issuing person	

1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299 This telephone number is available during office hours only.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Specific target organ toxicity - single exposure, Category 3, Central nervous system H226: Flammable liquid and vapour. H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21	Revision Date 2	1.12.2017	Print Date 04.02.2019
Signal word :	Warning		
Hazard statements :	H226 H336	Flammable liquid and vap May cause drowsiness or	
	cracking.	d exposure may cause skin	dryness or
Precautionary statements :	Prevention: P210	Keep away from heat, hot open flames and other ign smoking.	
	P261	Avoid breathing dust/ fume vapours/ spray.	e/ gas/ mist/
	Response:		
	P303 + P361 + P3	353 IF ON SKIN (or hair): immediately all contamina Rinse skin with water/show	ted clothing.
	P304 + P340 + P3	312 IF INHALED: Remov air and keep comfortable f a POISON CENTER/doct unwell.	for breathing. Call
	P370 + P378	In case of fire: Use dry sa or alcohol-resistant foam t	
	Storage: P403 + P233	Store in a well-ventilated p	place. Keep
		container tightly closed.	

Hazardous components which must be listed on the label:

n-butyl acetate • 123-86-4

Additional Labelling:

EUH208 Contains: n-butyl methacrylate, 2-hydroxyethyl methacrylate., triisotridecyl phosphite. May produce an allergic reaction.

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Fluid pigmented dispersion

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No	[%]

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21

Revision Date 21.12.2017

Print Date 04.02.2019

	Registration number	1272/2008)	
Hexanoic acid, 2-ethyl-, zinc salt, basic	85203-81-2 286-272-3	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Repr. 2; H361d Aquatic Chronic 3; H412	>= 0,25 - < 1
n-butyl methacrylate	97-88-1 202-615-1 01-2119486394-28	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 Note D	>= 0,1 - < 1
2-hydroxyethyl methacrylate	868-77-9 212-782-2 01-2119490169-29	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Note D	>= 0,1 - < 1
triisotridecyl phosphite	77745-66-5 278-758-9 01-2119487302-40	Skin Sens. 1; H317	>= 0,1 - < 1
Substances with a work	place exposure limit :		
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 30 - < 50
barium sulfate	7727-43-7 231-784-4 01-2119491274-35		>= 5 - < 10
2-methoxy-1- methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226	>= 1 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.
If inhaled	 Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: Take off all contaminated clothing immediately.

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21	Revision Date 21.12.2017	Print Date 04.02.2019
	Wash skin thoroughly with soap an skin cleanser. Do NOT use solvents or thinners. Put shower on working place	id water or use recognized
In case of eye contact	 Irrigate copiously with clean, fresh minutes, holding the eyelids apart. Seek medical advice. Put eye-washer on working place Remove contact lenses. 	water for at least 10
If swallowed	: If accidentally swallowed obtain im Do NOT induce vomiting. Keep at rest.	mediate medical attention.
4.2 Most important symptoms and	effects, both acute and delayed	
Symptoms	: No information available.	
Risks	: No information available.	
4.3 Indication of any immediate me	dical attention and special treatment nee	eded
Treatment	: The first aid procedure should be e with the doctor responsible for indu Seek medical advice.	
SECTION 5: Firefighting mea	sures	

5.1 Extinguishing media

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Keep containers and surroundings cool with water spray.
Unsuitable extinguishing media	:	Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	 As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must
	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3 Advice for firefighters

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Revision Date 21.12.2017

Special protective equipment : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Solvent vapours are heavier than air and may spread along floors.
	Ensure adequate ventilation.
	Use personal protective equipment.
	Evacuate personnel to safe areas.
	Keep people away from and upwind of spill/leak.
	Ventilate the area.

6.2 Environmental precautions

Environmental precautions	: Try to prevent the material from entering drains or water
	courses.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	 Clean with detergents. Avoid solvents. Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).
	Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Dam up. Soak up with inert absorbent material and dispose of as hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling
- : Avoid exceeding the given occupational exposure limits (see section 8).

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21	Revision Date 21.12.2017	Print Date 04.02.2019
	Use only in area provided with appro Avoid contact with skin, eyes and clo Smoking, eating and drinking should application area. Avoid inhalation of vapour or mist. For personal protection see section & Thoroughly mix before using After using, store in a well-sealed cor	thing. be prohibited in the 3.
Advice on protection against fire and explosion	 Prevent the creation of flammable or of vapour in air and avoid vapour con the occupational exposure limits. When transferring from one containe earthing measures and use conduction No sparking tools should be used. The product should only be used in a naked lights and other sources of ign excluded. No smoking. 	ncentration higher than r to another apply ve hose material. areas from which all
7.2 Conditions for safe storage, inc	luding any incompatibilities	
Requirements for storage areas and containers	 Observe label precautions. Containers which are opened must b kept upright to prevent leakage. Solvent vapours are heavier than air floors. Vapours may form explosive mixtures Electrical installations / working mate the technological safety standards. Keep away from sources of ignition - Store between 5° an 35°C in a dry, w from source of heat, ignition and dire Store in accordance with the particular 	and may spread along s with air. erials must comply with No smoking. vell ventilated place away oct sunlight.
Advice on common storage	: Keep away from oxidizing agents and materials.	d strongly acid or alkaline
7.3 Specific end use(s)		

: This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 713 mg/m3	2007-01-01	ACGIH

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21

Revision Date 21.12.2017

Print Date 04.02.2019

		STEL	200 ppm 950 mg/m3	2007-01-01	ACGIH
barium sulfate	7727-43-7	TWA	10 mg/m3	2007-01-01	ACGIH
2-methoxy-1- methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m3	2000-06-16	2000/39/EC
Further information	: skin: Ider	ntifies the pose	sibility of significant up	take through the skinl	ndicative
		STEL	100 ppm 550 mg/m3	2000-06-16	2000/39/EC
Further information	: skin: Ider	ntifies the pos	sibility of significant up	take through the skinl	ndicative

DNEL

DNEL n-butyl acetate :	End Use: Professional use Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 7 ppm End Use: Professional use Exposure routes: Inhalation Potential health effects: Local effects Value: 48 mg/m3
barium sulfate :	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 10 mg/m3 End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 10 mg/m3 End Use: Consumer use Exposure routes: Inhalation Potential health effects: Long-term systemic effects
	Value: 10 mg/m3 End Use: Consumer use Exposure routes: Ingestion Potential health effects: Long-term systemic effects
PNEC n-butyl acetate :	Water Value: 0,18 mg/l Soil

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21	Revision Date 21.12.2017	Print Date 04.02.2019
	Value: 0,093 mg/kg	
barium sulfate	: Fresh water Value: 0,115 mg/l	
	Fresh water sediment Value: 600,4 mg/kg	
	Soil Value: 207,7 mg/kg	
8.2 Exposure controls		
Personal protective equipme	nt	
Respiratory protection	: Provide adequate ventilation.	
Hand protection	 Solvent-resistant gloves (butyl-rubber) For prolonged or repeated contact use p Barrier creams may help to protect the should however not be applied once exp Skin should be washed after contact. Wash your hands and put on barrier cre Protective gloves complying with EN 3 Please observe the instructions regardin breakthrough time which are provided 1 gloves. Also take into consideration the under which the product is used, such a abrasion, and the contact time. If used in solution, or mixed with other conditions which differ from EN 374, c CE approved gloves. 	exposed areas of skin, they posure has occurred. eams 374. ng permeability and by the supplier of the e specific local conditions as the danger of cuts, - substances, and under
Eye protection	: Chemical resistant goggles must be wo	rn.
Skin and body protection	: Skin should be washed after contact. Workers should wear antistatic footwea Personnel should wear protective clothi Working clothes must not consist of tex dangerous melting behaviour in case of	ing. xtiles, which show a
Environmental exposure con	trols	
General advice	: Try to prevent the material from enterin If the product contaminates rivers and l respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21	Revision Date 21.12.2017	Print Date 04.02.2019
Appearance Odour	: liquid : solvent-like	
Flash point	: > 23 - 55 °C	
Ignition temperature	: not determined	
Lower explosion limit	: No data available	
Upper explosion limit	: No data available	
Auto-ignition temperature	: Not applicable	
рН	: not determined	
Freezing point	: Not applicable	
Boiling point	: not determined	
Vapour pressure	: 1,000 hPa at 50 °C	
Density	: 1,0966 g/cm3	
Water solubility	: not determined	
Partition coefficient: n- octanol/water Solubility in other solvents	No data availablenot determined	
Flow time	: 65 s 6 mm Method: ISO/DIN 2431 '84	
Relative vapour density	: Not applicable	
Evaporation rate	: not determined	
9.2 Other information		
Solids by weight	: 65,01 %	
Volatile organic compounds (VOC) content	: 34,98 %	

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21

Revision Date 21.12.2017

The product is chemically stable.

10.3 Possibility of hazardous reactions Hazardous reactions : No dangerous reaction known under conditions of normal use. 10.4 Conditions to avoid Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions. Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it. 10.5 Incompatible materials Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. 10.6 Hazardous decomposition products Hazardaya decomposition Carbon diavida (CO2) carbon man ~

products	nitrogen (NOx), dense black smoke.
Thermal decomposition	: Not applicable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product		
Acute inhalation toxicity	:	Inhalation of airborne droplets may cause irritation of the respiratory tract.
Skin corrosion/irritation	:	Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
Further information	:	The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.
Components:		

barium sulfate :		
Acute oral toxicity	:	Acute toxicity estimate: 500 mg/kg, Converted acute toxicity point estimate

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21

Revision Date 21.12.2017

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish

Remarks: No data is available on the product itself.

12.2 Persistence and degradability

Biodegradability : No data available

12.3 Bioaccumulative potential

12.4 Mobility in soil

Mobility	: No data available
----------	---------------------

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological	: The product contains dangerous substances for the
information	environment (see chapter no 3).
	The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the proparation
	preparation.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Contaminated packaging	 Empty containers should be taken to an approved waste handling site for recycling or disposal. According to the European Waste Catalogue, Waste Codes

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21

Revision Date 21.12.2017

Print Date 04.02.2019

are not product specific, but application specific. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions: 150110*

SECTION 14: Transport information

14.1 UN number

ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263

14.2 Proper shipping name

ADR	PAINT
IMDG	PAINT
IATA	Paint

14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3

IMDG

Packing group	:	III
Labels	:	3
EmS Code	:	F - E,S - E

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21	Revision Date 21.12.2017	Print Date 04.02.2019
IATA		
Packing group	: III	
Labels	: 3	
14.5 Environmental hazards		
ADR		
Environmentally hazardous	: no	
IMDG		
Marine pollutant	: no	
IATA		
Environmentally hazardous	: no	
14.6 Special precautions for user		
Not applicable		
14.7 Transport in bulk according t Not applicable for product as s	o Annex II of MARPOL 73/78 and the IBC upplied.	Code
SECTION 15: Regulatory info	ormation	

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	: Banned and/or restricted

123-86-4	n-butyl acetate
108-65-6	2-methoxy-1-methylethyl acetate
13 / 14	

according to Regulation (EC) No. 830/2015

MACROBASE RUBY RED

Version 2.21

Revision Date 21.12.2017

Print Date 04.02.2019

	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
70657-70-4	2-methoxypropyl acetate
MAL-Code-Number	: 5-6 (1993) 11.084-m3 air/10 g

Risk classification according to VbF	:	Exempt see user defined free text
Water contaminating class (Germany)	:	highly water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.