according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19

Revision Date 22.07.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	MACROBASE CARBON BLACK
Product code	:	L0MC0087

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	: Paints, varnishes and enamels
Substance/Mixture	
Chemical nature	: Coloured concentrated base

1.3 Details of the supplier of the safety data sheet

Company	: Lechler SpA
	Via Cecilio 17
	22100 Como- CO-
Telephone	: +39031586111
Telefax	: +39031586206
E-mail address	: safety@lechler.eu
Responsible/issuing person	

1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299 This telephone number is available during office hours only. (8.00-18.00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Specific target organ toxicity - single H336: May cause drowsiness or dizziness. exposure, Category 3

H226: Flammable liquid and vapour.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Warning

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19	Revision Date 22.07.2016		Print Date 04.02.2019
Hazard statements	: H226 H336	Flammable liquid and vap May cause drowsiness or	
		d exposure may cause skin	
Precautionary statements	P210	Keep away from heat, hot	surfaces, sparks,
		open flames and other ign smoking.	
	P261 Response:	Avoid breathing vapours.	
	P303 + P361 + F	2353 IF ON SKIN (or hair): immediately all contamina Rinse skin with water/show	ted clothing.
	P304 + P340 + F	P312 IF INHALED: Remov air and keep comfortable a POISON CENTER or do you feel unwell.	for breathing. Call
	P370 + P378	In case of fire: Use dry sa or alcohol-resistant foam t	
	Storage: P403 + P233	Store in a well-ventilated p container tightly closed.	blace. Keep

Hazardous components which must be listed on the label:

• 123-86-4 n-butyl acetate

Additional Labelling:

EUH208 Contains: n-butyl methacrylate, 2-hydroxyethyl methacrylate. May produce an allergic reaction.

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Fluid pigmented dispersion

Hazardous components

Chemical Name	CAS-No. EC-No.	Classification (REGULATION (EC) No	Concentration [%]
	Registration number	1272/2008)	
n-butyl methacrylate	97-88-1 202-615-1	Flam. Liq. 3; H226 Skin Irrit. 2; H315	>= 0,1 - < 1

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19

Revision Date 22.07.2016

Print Date 04.02.2019

	01-2119486394-28	Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335	
2-hydroxyethyl methacrylate	868-77-9 212-782-2 01-2119490169-29	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 0,1 - < 1
Substances with a wo	rkplace exposure limit :		
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 30 - < 50
2-methoxy-1- methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226	>= 15 - < 17,5
Carbon black	1333-86-4 215-609-9 01-2119384822-32		>= 5 - < 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt seek media advice. Never give anything by mouth to an unconscious person.	cal
If inhaled	Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.	
In case of skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognize skin cleanser. Do NOT use solvents or thinners. Put shower on working place	ed
In case of eye contact	Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Seek medical advice. Put eye-washer on working place Remove contact lenses.	
If swallowed	If accidentally swallowed obtain immediate medical attentio Do NOT induce vomiting.	n.

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19	Revision Date 22.07.2016	Print Date 04.02.2019
	Keep at rest.	
4.2 Most important symptoms and e	ffects, both acute and delayed	
Symptoms	: No information available.	
Risks	: No information available.	
4.3 Indication of any immediate med	lical attention and special treatment need	led
Treatment	: The first aid procedure should be es with the doctor responsible for indus Seek medical advice.	
SECTION 5: Firefighting meas	sures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use water spray, alcohol-resistant for carbon dioxide. Keep containers and surroundings c	-
Unsuitable extinguishing media	: Do NOT use water jet.	
5.2 Special hazards arising from t	the substance or mixture	
Specific hazards during firefighting	 As the product contains combustible will produce dense black smoke con products of combustion (see section Exposure to decomposition products health. Cool closed containers exposed to fi Collect contaminated fire extinguishi must not be discharged into drains. Fire residues and contaminated fire be disposed of in accordance with loce 	itaining hazardous 10). Is may be a hazard to ire with water spray. Ing water separately. This extinguishing water must
5.3 Advice for firefighters		
Special protective equipment for firefighters	: Wear self-contained breathing appar necessary.	ratus for firefighting if

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Solvent vapours are heavier than air and may spread along floors.
	Ensure adequate ventilation. Use personal protective equipment.

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19	Revision Date 22.07.2016	Print Date 04.02.2019
	Evacuate personnel to safe areas. Keep people away from and upwind of a Ventilate the area.	spill/leak.
6.2 Environmental precautions		
Environmental precautions	 Try to prevent the material from entering courses. If the product contaminates rivers and la respective authorities. 	-
6.3 Methods and materials for con	tainment and cleaning up	
Methods for cleaning up	 Clean with detergents. Avoid solvents. Contain and collect spillages with non-ormaterials, e.g. sand, earth, vermiculite, and place in a suitable container. The orshould be cleaned up immediately with decontaminant. One possible (flammatic comprises water (45 parts by volume)/e (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). Alternative is sodium carbonate (5 parts) Pick up and transfer to properly labelled Clean contaminated surface thoroughly Dam up. Soak up with inert absorbent material a hazardous waste. 	diatomaceous earth contaminated area a suitable ole) decontaminant ethanol or isopropanol A non-flammable s)/water (95 parts). d containers.
6.4 Reference to other sections		

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8. Thoroughly mix before using After using, store in a well-sealed container
Advice on protection against fire and explosion	:	Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19	Revision Date 22.07.2016	Print Date 04.02.2019
	When transferring from one container to earthing measures and use conductive No sparking tools should be used. The product should only be used in area naked lights and other sources of ignitio excluded. No smoking.	hose material. as from which all
7.2 Conditions for safe storage, inc	cluding any incompatibilities	
Requirements for storage areas and containers	 Observe label precautions. Containers which are opened must be of kept upright to prevent leakage. Solvent vapours are heavier than air an floors. Vapours may form explosive mixtures w Electrical installations / working materia the technological safety standards. Keep away from sources of ignition - No Store between 5° an 35°C in a dry, well from source of heat, ignition and direct s Store in accordance with the particular restored. 	d may spread along /ith air. ls must comply with o smoking. ventilated place away sunlight.
Advice on common storage	: Keep away from oxidising agents and st materials.	trongly acid or alkaline
7.3 Specific end use(s)		
	: This information is not available.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	C	AS-No.	Value	Control parameters	Update	Basis
n-butyl acetate	12	23-86-4	TWA	150 ppm 713 mg/m3		ACGIH
			STEL	200 ppm 950 mg/m3		ACGIH
2-methoxy-1- methylethyl acetate	10	08-65-6	TWA	50 ppm 275 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identi	fies the possi	ibility of significant upta	ake through the skinIndic	ative
			STEL	100 ppm 550 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identi	fies the possi	ibility of significant upta	ake through the skinIndic	ative
carbon black	13	33-86-4	TWA			ACGIH

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

ersion 2.19	Revision Date 22.07.2016	Print Date 04.02.201
	3,5 mg/m3	
DNEL n-butyl acetate	 End Use: Professional use Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 7 ppm 	
	End Use: Professional use Exposure routes: Inhalation Potential health effects: Local effects Value: 48 mg/m3	
PNEC n-butyl acetate	: Water Value: 0,18 mg/l	
	Soil Value: 0,093 mg/kg	
2 Exposure controls		
Personal protective equipme	ent	
Respiratory protection	 Apply technical measures to comply with the exposure limits. This should be achieved by a good general exportically feasible- by the use of a local exl If the occupational exposure limits cannot be cases suitable respiratory equipment should short period of time. Respirator with combination filter for vapour 	extraction and -if haust ventilation. e met, in exceptional be worn only for a
Hand protection	 Solvent-resistant gloves (butyl-rubber) For prolonged or repeated contact use protect Protective gloves complying with EN 374. Please observe the instructions regarding per breakthrough time which are provided by th gloves. Also take into consideration the spec under which the product is used, such as the abrasion, and the contact time. If used in solution, or mixed with other subs conditions which differ from EN 374, contact CE approved gloves. Barrier creams may help to protect the exposur should however not be applied once exposur Skin should be washed after contact. 	rmeability and e supplier of the cific local conditions danger of cuts, stances, and under ct the supplier of the sed areas of skin, they

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19	Revision Date 22.07.2016	Print Date 04.02.2019	
	Wash your hands and put on barrier creams		
Eye protection	: Chemical resistant goggles must be worn.		
Skin and body protection	: Skin should be washed after contact. Working clothes must not consist of textiles, dangerous melting behaviour in case of fire. Personnel should wear protective clothing. Workers should wear antistatic footwear.	which show a	
Environmental exposure contr	ols		
General advice	: Try to prevent the material from entering dra If the product contaminates rivers and lakes or respective authorities.		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like
Flash point	: > 23 - 55 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: not applicable
рН	: not determined
Freezing point	: not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 1,0486 g/cm3
Water solubility	: not determined
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 100 s
	8 / 14

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19	Revision Date 22.07.2016	Print Date 04.02.2019
	6 mm Method: ISO/DIN 2431 '84	
Relative vapour density	: not applicable	
Evaporation rate	: not determined	
9.2 Other information		
Solids by weight	: 54,41 %	
Volatile organic compounds (VOC) content	: 45,58 %	
SECTION 10: Stability and r	eactivity	
10.1 Reactivity		
None reasonably foreseeabl	e.	
10.2 Chemical stability		
The product is chemically sta	able.	
10.3 Possibility of hazardous re	actions	
Hazardous reactions	: No dangerous reaction known under	conditions of normal use.
10.4 Conditions to avoid		
Conditions to avoid	 Our products were manufactured in c standards to avoid decomposition and defined conditions. Taking the product type into account, the product in its original packaging th it. 	d degrading under the it is advisable to leave
10.5 Incompatible materials		
Materials to avoid	: Keep away from oxidising agents, strostrongly acid materials in order to avo	
10.6 Hazardous decomposition	products	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monox nitrogen (NOx), dense black smoke.	(CO), oxides of
	: not applicable	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19	Revision Date 22.07.2016	Print Date 04.02.2019	
Acute inhalation toxicity	: Exposure to component solvent vapour the stated occupational exposure limit r effects., Such as: mucous membrane in irritation, adverse effects on kidney, liv system. Symptoms and signs: headache muscular weakness, drowsiness and in consciousness., Inhalation of airborne c of the respiratory tract.	may result in adverse health ritation, respiratory system er and central nervous e, dizziness, fatigue, extreme cases loss of	
Skin corrosion/irritation	: Repeated or prolonged contact with the of natural fat from the skin resulting in product may be absorbed through the sl	desiccation of the skin., The	
Further information	: The concentration of each substance sh assessing the toxicological effects deriv		

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish : Remarks: No data is available on the product itself.

12.2 Persistence and degradability

Biodegradability : No data available

12.3 Bioaccumulative potential

Bioaccumulation : No data available

12.4 Mobility in soil

Mobility : No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19	Revision Date 22.07.2016	Print Date 04.02.2019
Additional ecological information	: There is no data available for this pro	oduct.
SECTION 13: Disposal cons	iderations	
13.1 Waste treatment methods		
Product	 The product should not be allowed to courses or the soil. Disposal together with normal waste disposal required according to local r 	is not allowed. Special
Contaminated packaging	: Empty containers should be taken to handling site for recycling or disposa According to the European Waste Ca are not product specific, but applicat	ll. atalogue, Waste Codes

The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions: 150110*

SECTION 14: Transport information

14.1 UN number

ADR	: UN 1263
IMDG	: UN 1263
ΙΑΤΑ	: UN 1263

14.2 Proper shipping name

ADR	PAINT
IMDG	PAINT
IATA	Paint

14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19

Revision Date 22.07.2016

Print Date 04.02.2019

ADR

Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E,S-E
IATA	
Packing group	: III
Labels	: 3
14.5 Environmental hazards	
ADR	
Environmentally hazardous	: no
IMDG	
Marine pollutant	: no
IATA	
Environmentally hazardous	: no
14.6 Special precautions for user	
Remarks	 Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 Packages smaller than or equal to 30 litres, not goods/merchandise of Class 3

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19

Revision Date 22.07.2016

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	: Banned and/or restricted

123-86-4	n-butyl acetate
108-65-6	2-methoxy-1-methylethyl acetate
70657-70-4	2-methoxypropyl acetate

MAL-Code-Number (DK)	: 3-6 (1993) 1.285-m3 air/10 g
Risk classification according to VbF	: Exempt see user defined free text
Water contaminating class (Germany)	: slightly water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical Safety Assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

according to Regulation (EC) No. 830/2015

MACROBASE CARBON BLACK

Version 2.19

Revision Date 22.07.2016

Print Date 04.02.2019

H336 May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.