

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MACROBASE COOL YELLOW REDUCED  
Product code : L0MC0210

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Paints, varnishes and enamels  
Chemical nature : Coloured concentrated base

#### 1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA  
Via Cecilio 17  
22100 Como- CO-  
Telephone : +39031586111  
Telefax : +39031586206  
E-mail address : [safety@lechler.eu](mailto:safety@lechler.eu)  
Responsible/issuing person

#### 1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299

This telephone number is available during office hours only.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.  
Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.
Precautionary statements	:	EUH066 Repeated exposure may cause skin dryness or cracking. <b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous components which must be listed on the label:

- 123-86-4 n-butyl acetate

### Additional Labelling:

EUH208 Contains: triisotridecyl phosphite, 2-hydroxyethyl methacrylate. May produce an allergic reaction.

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Fluid pigmented dispersion

#### Hazardous components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC) No	Concentration [%]
---------------	-------------------	---------------------------------------	----------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

	Registration number	1272/2008)	
heptan-2-one	110-43-0 203-767-1 01-2119902391-49	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332	>= 5 - < 10
triisotridecyl phosphite	77745-66-5 278-758-9 01-2119487302-40	Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 0,25 - < 1
Hexanoic acid, 2-ethyl-, zinc salt, basic	85203-81-2 286-272-3	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Repr. 2; H361d Aquatic Chronic 3; H412	>= 0,25 - < 1
2-hydroxyethyl methacrylate	868-77-9 212-782-2 01-2119490169-29	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Note D	>= 0,1 - < 1
Substances with a workplace exposure limit :			
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 20 - < 25
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226	>= 1 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
Put shower on working place
- In case of eye contact : Irrigate copiously with clean, fresh water for at least 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

minutes, holding the eyelids apart.  
Seek medical advice.  
Put eye-washer on working place  
Remove contact lenses.

If swallowed : If accidentally swallowed obtain immediate medical attention.  
Do NOT induce vomiting.  
Keep at rest.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.  
Seek medical advice.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Keep containers and surroundings cool with water spray.

Unsuitable extinguishing media : Do NOT use water jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

## SECTION 6: Accidental release measures

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.  
Ensure adequate ventilation.  
Use personal protective equipment.  
Evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Ventilate the area.

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).  
  
Pick up and transfer to properly labelled containers.  
Clean contaminated surface thoroughly.  
Dam up.  
Soak up with inert absorbent material and dispose of as hazardous waste.

### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid inhalation of vapour or mist.  
For personal protection see section 8.  
Thoroughly mix before using

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

After using, store in a well-sealed container

Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
When transferring from one container to another apply earthing measures and use conductive hose material.  
No sparking tools should be used.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Solvent vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep away from sources of ignition - No smoking.  
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.  
Store in accordance with the particular national regulations.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

German storage class : 3 Flammable liquids

### 7.3 Specific end use(s)

: This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
n-butyl acetate	123-86-4	TWA	50 ppm	2016-03-01	ACGIH
		STEL	150 ppm	2016-03-01	ACGIH
heptan-2-one	110-43-0	TWA	50 ppm 238 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			

**SAFETY DATA SHEET**

according to Regulation (EC) No. 830/2015

**MACROBASE COOL YELLOW REDUCED**

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

		STEL	100 ppm 475 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		TWA	50 ppm 275 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			

**DNEL**

2-hydroxyethyl methacrylate : End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: Chronic effects  
Value: 1,3 mg/kg

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Chronic effects  
Value: 4,9 mg/m3

End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Chronic effects  
Value: 0,83 mg/kg

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Chronic effects  
Value: 2,9 mg/m3

End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: Chronic effects  
Value: 0,83 mg/kg

n-butyl acetate : End Use: Professional use  
Exposure routes: Skin contact  
Potential health effects: Local effects  
Exposure time: 8 h  
Value: 7 ppm

End Use: Professional use  
Exposure routes: Inhalation  
Potential health effects: Local effects  
Value: 48 mg/m3

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

### PNEC

2-hydroxyethyl methacrylate : Fresh water  
Value: 0,482 mg/l

Marine water  
Value: 0,482 mg/l

Sewage treatment plant  
Value: 10 mg/l

Intermittent use/release  
Value: 1 mg/l

Fresh water sediment  
Value: 3,79 mg/kg

Marine sediment  
Value: 3,79 mg/kg

Soil  
Value: 0,476 mg/kg

n-butyl acetate : Water  
Value: 0,18 mg/l

Soil  
Value: 0,093 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.  
Respirator with combination filter for vapour/particulate (EN 141)

Hand protection : Solvent-resistant gloves (butyl-rubber) recommended. For prolonged or repeated contact use protective gloves. Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
If used in solution, or mixed with other substances, and under



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

conditions which differ from EN 374, contact the supplier of the CE approved gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.  
Personnel should wear protective clothing.  
Flame retardant antistatic protective clothing.  
Workers should wear antistatic footwear.

### Environmental exposure controls

General advice : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid  
Odour : solvent-like  
Flash point : > 23 - 55 °C  
Ignition temperature : not determined  
Lower explosion limit : No data available  
Upper explosion limit : No data available  
Auto-ignition temperature : Not applicable  
pH : not determined  
Freezing point : Not applicable  
Boiling point : not determined  
Vapour pressure : 1,000 hPa  
at 50 °C  
Density : 1,037 g/cm<sup>3</sup>  
Water solubility : not determined

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

Partition coefficient: n-octanol/water	:	No data available
Solubility in other solvents	:	not determined
Flow time	:	59 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	:	Not applicable
Evaporation rate	:	not determined

### 9.2 Other information

Solids by weight	:	68,6 %
Volatile organic compounds (VOC) content	:	31,4 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

None reasonably foreseeable.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.  
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

Thermal decomposition : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Product

- Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method
- Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method
- Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
- Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

##### Components:

##### **heptan-2-one :**

- Acute oral toxicity : Acute toxicity estimate: 500 mg/kg, Converted acute toxicity point estimate

### SECTION 12: Ecological information

#### 12.1 Toxicity

- Toxicity to fish :  
Remarks:  
No data is available on the product itself.

#### 12.2 Persistence and degradability

- Biodegradability : No data available

#### 12.3 Bioaccumulative potential

- Bioaccumulation : No data available

#### 12.4 Mobility in soil

- Mobility : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3).  
The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
The following Waste Codes are only suggestions:150110\*

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

### 14.2 Proper shipping name

ADR PAINT

IMDG PAINT

IATA Paint

### 14.3 Transport hazard class(es)

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

**ADR** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

#### ADR

Packing group : III

Classification Code : F1

Hazard Identification Number : 30

Labels : 3

#### IMDG

Packing group : III

Labels : 3

EmS Code : F - E,S - E

#### IATA

Packing group : III

Labels : 3

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

#### IATA

Environmentally hazardous : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted

108-65-6	2-methoxy-1-methylethyl acetate
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
70657-70-4	2-methoxypropyl acetate

MAL-Code-Number : 5-6 (1993)  
10.671-m<sup>3</sup> air/10 g

German storage class (TRGS 510) : 3: Flammable liquids

Risk classification according to VbF : Exempt  
see user defined free text

Water contaminating class (Germany) : water endangering  
VWWWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

#### 15.2 Chemical safety assessment

No data is available on the product itself.

### SECTION 16: Other information

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MACROBASE COOL YELLOW REDUCED

Version 2.20

Revision Date 14.01.2019

Print Date 04.02.2019

---

### Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.