according to Regulation (EC) No. 830/2015

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : EPOFAN THINNER

Product code : L0000535

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Paints, varnishes and enamels

Substance/Mixture

Chemical nature : Thinner for coatings

#### 1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA

Via Cecilio 17

22100 Como- CO-

 Telephone
 : +39031586111

 Telefax
 : +39031586206

 E-mail address
 : safety@lechler.eu

Responsible/issuing person

### 1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299

This telephone number is available during office hours only.

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single H336: May cause drowsiness or dizziness.

exposure, Category 3

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention**:

P210 Keep away from heat/sparks/open

flames/hot surfaces. No smoking.

P233 Keep container tightly closed. P261 Avoid breathing vapours.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/doctor.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

• 78-93-3 butanone

• 78-83-1 2-methylpropan-1-ol

#### 2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Liquid

#### **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No	[%]
	Registration number	1272/2008)	
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 30 - < 50

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

		Skin Irrit. 2; H315 Note C	
butanone	78-93-3 201-159-0 01-2119457290-43	EUH066 Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 25 - < 30
2-methylpropan-1-ol	78-83-1 201-148-0 01-2119484609-23	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 15 - < 17,5
Substances with a work	place exposure limit :		
1-methoxy-2-propanol	107-98-2 203-539-1 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 12,5
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 5 - < 10
2-ethoxy-1-methylethyl acetate	54839-24-6 259-370-9 01-2119475116-39	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5 - < 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : When symptoms persist or in all cases of doubt seek medical

advice.

Never give anything by mouth to an unconscious person.

If inhaled : Remove to fresh air.

Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial

respiration.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Take off all contaminated clothing immediately.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Do NOT use solvents or thinners. Put shower on working place

In case of eye contact : Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart.

Seek medical advice.

Put eye-washer on working place

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

Remove contact lenses.

If swallowed If accidentally swallowed obtain immediate medical attention.

Do NOT induce vomiting.

Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** : No information available.

: No information available. Risks

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation

with the doctor responsible for industrial medicine.

Seek medical advice.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Keep containers and surroundings cool with water spray.

Unsuitable extinguishing

media

: Do NOT use water jet.

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: As the product contains combustible organic components, fire

will produce dense black smoke containing hazardous

products of combustion (see section 10).

Exposure to decomposition products may be a hazard to

health.

Cool closed containers exposed to fire with water spray. Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

Personal precautions : Solvent vapours are heavier than air and may spread along

floors.

Ensure adequate ventilation.

Use personal protective equipment. Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Ventilate the area.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.

Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area

should be cleaned up immediately with a suitable

decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol

(50 parts)/concentrated

(d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).

Pick up and transfer to properly labelled containers.

Clean contaminated surface thoroughly.

Dam up.

Soak up with inert absorbent material and dispose of as

hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Use only in area provided with appropriate exhaust ventilation.

Avoid contact with skin, eyes and clothing.

Smoking, eating and drinking should be prohibited in the

application area.

Avoid inhalation of vapour or mist. For personal protection see section 8.

Thoroughly mix before using

After using, store in a well-sealed container

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

Advice on protection against fire and explosion

: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than

the occupational exposure limits.

When transferring from one container to another apply earthing measures and use conductive hose material.

No sparking tools should be used.

The product should only be used in areas from which all naked lights and other sources of ignition have been

excluded. No smoking.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Observe label precautions.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Solvent vapours are heavier than air and may spread along

floors.

Vapours may form explosive mixtures with air.

Electrical installations / working materials must comply with

the technological safety standards.

Keep away from sources of ignition - No smoking.

Store between 5° an 35°C in a dry, well ventilated place away

from source of heat, ignition and direct sunlight.

Store in accordance with the particular national regulations.

Advice on common storage

: Keep away from oxidizing agents and strongly acid or alkaline

materials.

### 7.3 Specific end use(s)

: This information is not available.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Components	CAS	S-No.	Value	Control parameters	Update	Basis
xylenes	1330-20-7		TWA	50 ppm	2000-06-16	2000/39/EC
				221 mg/m3		
Further information	: S	skin: Identifies the possibility of significant uptake through the skinIndicative				
			STEL	100 ppm 442 mg/m3	2000-06-16	2000/39/EC
Further information	: S	: skin: Identifies the possibility of significant uptake through the skinIndicative				
butanone	78-9	93-3	TWA	200 ppm	2000-06-16	2000/39/EC
				600 mg/m3		

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

Further information	:	Indicative				
			STEL	300 ppm 900 mg/m3	2000-06-16	2000/39/EC
Further information		Indicative				
2- methylpropan- 1-ol	73	8-83-1	TWA	50 ppm	2007-01-01	ACGIH
1- methoxypropa n-2-ol	10	07-98-2	TWA	100 ppm 375 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative				
			STEL	150 ppm 568 mg/m3	2000-06-16	2000/39/EC
Further information	:	: skin: Identifies the possibility of significant uptake through the skinIndicative				
n-butyl acetate	12	23-86-4	TWA	150 ppm 713 mg/m3	2007-01-01	ACGIH
			STEL	200 ppm 950 mg/m3	2007-01-01	ACGIH

DNEL

n-butyl acetate : End Use: Professional use

Exposure routes: Skin contact Potential health effects: Local effects

Exposure time: 8 h Value: 7 ppm

End Use: Professional use Exposure routes: Inhalation

Potential health effects: Local effects

Value: 48 mg/m3

**PNEC** 

n-butyl acetate : Water

Value: 0,18 mg/l

Soil

Value: 0,093 mg/kg

#### 8.2 Exposure controls

# Personal protective equipment

Respiratory protection : Apply technical measures to comply with the occupational

exposure limits.

This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a

short period of time.

Respirator with combination filter for vapour/particulate (EN 141)

Hand protection : Solvent-resistant gloves (butyl-rubber)

For prolonged or repeated contact use protective gloves.

Protective gloves complying with EN 374.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts,

abrasion, and the contact time.

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the

CE approved gloves.

Barrier creams may help to protect the exposed areas of skin, they

should however not be applied once exposure has occurred.

Skin should be washed after contact.

Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.

Working clothes must not consist of textiles, which show a

dangerous melting behaviour in case of fire. Personnel should wear protective clothing. Workers should wear antistatic footwear.

#### **Environmental exposure controls**

General advice : Try to prevent the material from entering drains or water courses.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Odour : solvent-like

Flash point :  $0 - < 21 \,^{\circ}\text{C}$ 

Ignition temperature : not determined

Lower explosion limit : No data available

Upper explosion limit : No data available

Auto-ignition temperature : Not applicable

according to Regulation (EC) No. 830/2015

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

рН : not determined

Freezing point : Not applicable

Boiling point : not determined

: 1,000 hPa Vapour pressure

at 50 °C

Density : 0,8522 g/cm3

Water solubility : not determined

Partition coefficient: n-

octanol/water

: No data available

Solubility in other solvents : not determined

Relative vapour density : Not applicable

Evaporation rate : not determined

9.2 Other information

Volatile organic compounds : 100 %

(VOC) content

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

None reasonably foreseeable.

## 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety

standards to avoid decomposition and degrading under the

defined conditions.

Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic reactions.

according to Regulation (EC) No. 830/2015

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

### 10.6 Hazardous decomposition products

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of

nitrogen (NOx), dense black smoke.

Thermal decomposition : Not applicable

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

**Product** 

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation

method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal

of natural fat from the skin resulting in desiccation of the skin., The

product may be absorbed through the skin.

Serious eye damage/eye

irritation

: The liquid splashed in the eyes may cause irritation and reversible

damage.

Further information : The concentration of each substance should be borne in mind in

assessing the toxicological effects deriving from the preparation.

**Components:** 

xylene:

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity

point estimate

2-ethoxy-1-methylethyl acetate:

Acute oral toxicity : LDLo: 5.000 mg/kg, Rat(male and female)

Acute inhalation toxicity : LDLo: > 6,99 mg/l, 4 h, Rat(male and female),

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Toxicity to fish

Remarks:

No data is available on the product itself.

according to Regulation (EC) No. 830/2015

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

Toxicity to fish

2-ethoxy-1-methylethyl : LC50: 140 mg/l acetate : Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

NOEC: 47,5 mg/l Exposure time: 96 h

Species: Oryzias latipes (Orange-red killifish)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

2-ethoxy-1-methylethyl : NOEC: >= 100 mg/l acetate Exposure time: 21 d

Species: Daphnia magna (Water flea)

### 12.2 Persistence and degradability

Biodegradability : No data available

#### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

#### 12.4 Mobility in soil

Mobility : No data available

## 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

Additional ecological

information

: There is no data available for this product.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Disposal together with normal waste is not allowed. Special

disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

handling site for recycling or disposal.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions: 150110\*

# **SECTION 14: Transport information**

#### 14.1 UN number

**ADR** : UN 1263

**IMDG** : UN 1263

IATA : UN 1263

#### 14.2 Proper shipping name

ADR PAINT RELATED MATERIAL

IMDG PAINT RELATED MATERIAL

IATA PAINT RELATED MATERIAL

# 14.3 Transport hazard class(es)

ADR : 3

**IMDG** : 3

**IATA** : 3

# 14.4 Packing group

### **ADR**

Packing group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

#### **IMDG**

Packing group : II
Labels : 3

according to Regulation (EC) No. 830/2015

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

EmS Code : F-E,S-E

**IATA** 

Packing group : II Labels : 3

### 14.5 Environmental hazards

**ADR** 

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

**IATA** 

Environmentally hazardous : no

## 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation

(Article 59).

: Not applicable

**REACH** - List of substances

subject to authorisation

(Annex XIV)

: Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

: Banned and/or restricted

# **EPOFAN THINNER**

Version 2.35 Revision Date 05.12.2017 Print Date 31.01.2019

78-83-1	2-methylpropan-1-ol
107-98-2	1-methoxy-2-propanol
123-86-4	n-butyl acetate

MAL-Code-Number : 5-3 (1993)

3.769-m3 air/10 g

Risk classification according to

VbF

: Flash point less than 21 °C, at 15 °C not miscible in water

Specially dangerous flammable liquids

Water contaminating class

(Germany)

: water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

#### 15.2 Chemical safety assessment

No data is available on the product itself.

### **SECTION 16: Other information**

#### Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.