

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : POLYDUR PLASTIC
Product code : L0040465

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Paints, varnishes and enamels
Chemical nature : Thick polyester putty

1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA
Via Cecilio 17
22100 Como- CO-
Telephone : +39031586111
Telefax : +39031586206
E-mail address : safety@lechler.eu
Responsible/issuing person

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P201 Obtain special instructions before use.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label:

- 100-42-5 styrene
- 136-52-7 cobalt bis(2-ethylhexanoate)

2.3 Other hazards

None known.

The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

3.2 Mixtures

Chemical nature : Fluid pigmented dispersion

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
styrene	100-42-5 202-851-5 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Note D	>= 15 - < 17,5
cobalt bis(2-ethylhexanoate)	136-52-7 205-250-6 01-2119524678-29	Eye Irrit. 2; H319 Skin Sens. 1A; H317 Repr. 1B; H360F Aquatic Acute 1; H400 Aquatic Chronic 3; H412 (Acute M=1)	>= 0,1 - < 0,25
N-ethyl-2-pyrrolidone	2687-91-4 220-250-6 01-2119472138-36	Eye Dam. 1; H318 Repr. 1B; H360Df	>= 0,1 - < 0,3
Substances with a workplace exposure limit :			
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6 238-877-9		>= 30 - < 50
barium sulfate	7727-43-7 231-784-4 01-2119491274-35		>= 5 - < 10
copper chromite black spinel	68186-91-4 269-053-7 01-2119966123-40		>= 5 - < 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : When symptoms persist or in all cases of doubt seek medical advice.
Never give anything by mouth to an unconscious person.

If inhaled : Remove to fresh air.
Keep patient warm and at rest.

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

- If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Do NOT use solvents or thinners.
Put shower on working place
- In case of eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
Seek medical advice.
Put eye-washer on working place
Remove contact lenses.
- If swallowed : If accidentally swallowed obtain immediate medical attention.
Do NOT induce vomiting.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.
Seek medical advice.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Keep containers and surroundings cool with water spray.
- Unsuitable extinguishing media : Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).
Exposure to decomposition products may be a hazard to health.
Cool closed containers exposed to fire with water spray.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

be disposed of in accordance with local regulations.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.
Ensure adequate ventilation.
Use personal protective equipment.
Evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ventilate the area.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).

Pick up and transfer to properly labelled containers.
Clean contaminated surface thoroughly.
Dam up.
Soak up with inert absorbent material and dispose of as hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

section 8).

Use only in area provided with appropriate exhaust ventilation.

Avoid contact with skin, eyes and clothing.

Smoking, eating and drinking should be prohibited in the application area.

Avoid inhalation of vapour or mist.

For personal protection see section 8.

Thoroughly mix before using

After using, store in a well-sealed container

Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
When transferring from one container to another apply earthing measures and use conductive hose material.
No sparking tools should be used.
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Observe label precautions.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Solvent vapours are heavier than air and may spread along floors.
Vapours may form explosive mixtures with air.
Electrical installations / working materials must comply with the technological safety standards.
Keep away from sources of ignition - No smoking.
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.
Store in accordance with the particular national regulations.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

German storage class : 3 Flammable liquids

7.3 Specific end use(s)

: This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Talc	14807-96-	TWA		2013-03-01	ACGIH

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

(Mg ₃ H ₂ (SiO ₃) ₄)	6		2 mg/m ³		
styrene	100-42-5	TWA	20 ppm	2018-03-20	ACGIH
		STEL	40 ppm	2018-03-20	ACGIH
barium sulfate	7727-43-7	TWA	5 mg/m ³	2014-03-01	ACGIH
Copper chromite black spinel	68186-91-4	TWA	0,5 mg/m ³	2013-03-01	ACGIH
Further information	: chromium				
		TWA	0,1 mg/m ³	2015-04-10	ACGIH
Further information	: Manganese				
		TWA	0,02 mg/m ³	2015-04-10	ACGIH
Further information	: Manganese				
		TWA	0,2 mg/m ³	2017-01-31	2017/164/EU
Further information	: Manganese				
		TWA	0,05 mg/m ³	2017-01-31	2017/164/EU
Further information	: Manganese				

DNEL

styrene

: End Use: Workers
 Exposure routes: Dermal
 Potential health effects: Long-term systemic effects
 Value: 406 mg/kg

End Use: Workers
 Exposure routes: Inhalation
 Potential health effects: Long-term systemic effects
 Value: 85 mg/m³

End Use: Workers
 Exposure routes: Inhalation
 Potential health effects: Acute systemic effects
 Value: 289 mg/m³

End Use: Workers
 Exposure routes: Inhalation
 Potential health effects: Acute local effects
 Value: 306 mg/m³

End Use: Consumers
 Exposure routes: Oral
 Potential health effects: Long-term systemic effects
 Value: 2,1 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

End Use: Consumers
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 343 mg/kg

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 10 mg/m³

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Acute systemic effects
Value: 174,25 mg/m³

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Acute local effects
Value: 182,75 mg/m³

cobalt bis(2-ethylhexanoate) : End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects
Value: 0,00276 mg/m³

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term local effects
Value: 0,0037 mg/m³

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term local effects
Value: 0,2351 mg/m³

N-ethyl-2-pyrrolidone : End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term local effects
Value: 10,05 mg/m³

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Acute local effects
Value: 20,1 mg/m³

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 16,75 mg/m³

End Use: Workers
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 4 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

barium sulfate : End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 10 mg/m³

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 10 mg/m³

End Use: Consumer use
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 10 mg/m³

End Use: Consumer use
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects
Value: 13000 mg/kg

PNEC
styrene : Fresh water
Value: 0,028 mg/l

Marine water
Value: 0,014 mg/l

Fresh water sediment
Value: 0,614 mg/kg

Marine sediment
Value: 0,307 mg/kg

Soil
Value: 0,2 mg/kg

Sewage treatment plant
Value: 5 mg/l

cobalt bis(2-ethylhexanoate) : Fresh water
Value: 0,0006 mg/l

Marine water
Value: 0,00236 mg/l

Fresh water sediment
Value: 9,5 mg/kg

Marine sediment
Value: 9,5 mg/kg

Soil
Value: 10,9 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

	Sewage treatment plant Value: 0,37 mg/l
N-ethyl-2-pyrrolidone	: Fresh water Value: 0,25 mg/l
	Marine water Value: 0,025 mg/l
	Fresh water sediment Value: 1,91 mg/kg
	Marine sediment Value: 0,19 mg/kg
	Soil Value: 0,23 mg/kg
	Sewage treatment plant Value: 10 mg/l
	Intermittent use/release Value: 1 mg/l
barium sulfate	: Fresh water Value: 0,115 mg/l
	Fresh water sediment Value: 600,4 mg/kg
	Soil Value: 207,7 mg/kg

8.2 Exposure controls

Personal protective equipment

- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.
Respirator with combination filter for vapour/particulate (EN 141)
- Hand protection : Solvent-resistant gloves (butyl-rubber)
For prolonged or repeated contact use protective gloves. Protective gloves complying with EN 374.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

danger of cuts, abrasion, and the contact time.
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
Skin should be washed after contact.
Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.
Personnel should wear protective clothing.
Flame retardant antistatic protective clothing.
Workers should wear antistatic footwear.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Odour : solvent-like
Flash point : > 23 - 55 °C
Ignition temperature : not determined
Lower explosion limit : No data available
Upper explosion limit : No data available
Auto-ignition temperature : Not applicable
pH : not determined
Freezing point : Not applicable
Boiling point : not determined
Vapour pressure : 1,000 hPa
at 50 °C
Density : 1,9 g/cm³
Water solubility : not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

Partition coefficient: n-octanol/water	:	No data available
Solubility in other solvents	:	not determined
Viscosity, kinematic	:	> 20,5 mm ² /s at 40 °C
Flow time	:	65 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	:	Not applicable
Evaporation rate	:	not determined

9.2 Other information

Solids by weight	:	84,8 %
Volatile organic compounds (VOC) content	:	15,2 %

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

Thermal decomposition : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

- Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, Calculation method
- Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
- Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

Components:

styrene :

- Acute oral toxicity : LD50: 5.000 mg/kg, Rat
- Acute inhalation toxicity : LC50: 11,8 mg/l, 4 h, Rat,
- Acute dermal toxicity : LD50: > 2.000 mg/kg, Rat, OECD Test Guideline 402

cobalt bis(2-ethylhexanoate) :

- Acute oral toxicity : LD50: 3.129 mg/kg, Rat, OECD Test Guideline 425
- Acute dermal toxicity : LD50: > 2.000 mg/kg, Rat, OECD Test Guideline 402

SECTION 12: Ecological information

12.1 Toxicity

- Toxicity to fish :
Remarks:
No data is available on the product itself.
- Toxicity to fish
styrene : LC50: 4,02 mg/l
Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)
- cobalt bis(2-ethylhexanoate) : LC50: 48 mg/l
Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)
- N-ethyl-2-pyrrolidone : LC50: > 446 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

Exposure time: 96 h

cobalt bis(2-ethylhexanoate) : 1
Toxicity to fish (Chronic toxicity)
cobalt bis(2-ethylhexanoate) : NOEC: 0,21 mg/l
Exposure time: 34 d
mortality
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)
styrene : NOEC: 1,01 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

cobalt bis(2-ethylhexanoate) : 0,0608 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Biodegradability : No data available

12.3 Bioaccumulative potential

Bioaccumulation : No data available

12.4 Mobility in soil

Mobility : No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
According to the European Waste Catalogue, Waste Codes

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

are not product specific, but application specific.
The Waste code should be assigned in discussion between
the user, the producer and the waste disposal company.
The following Waste Codes are only suggestions: 150110*

SECTION 14: Transport information

14.1 UN number

ADR : UN 3269

IMDG : UN 3269

IATA : UN 3269

14.2 Proper shipping name

ADR POLYESTER RESIN KIT

IMDG POLYESTER RESIN KIT

IATA Polyester resin kit

14.3 Transport hazard class(es)

ADR : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADR

Packing group : III

Classification Code : F1

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-A,S-D

IATA

Packing group : III

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA

Environmentally hazardous : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted

2687-91-4	N-ethyl-2-pyrrolidone
-----------	-----------------------

MAL-Code-Number : 4-6 (1993)
2.712-m3 air/10 g

Storage class (TRGS 510) : 3: Flammable liquids

Risk classification according : Exempt

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

to VbF see user defined free text

Water contaminating class : obviously hazardous to water
(Germany)
VWWWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H360F	May damage fertility.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

List of references

Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP)
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).
Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products
This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Key or legend to abbreviations and acronyms used in the safety data sheet

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

POLYDUR PLASTIC

Version 1.10

Revision Date 19.03.2020

Print Date 23.03.2020

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.