

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MEGALACK UHS CLEARCOAT  
Product code : L0ML0920

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Paints, varnishes and enamels  
Chemical nature : Dual compound colourless clearcoat

#### 1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA  
Via Cecilio 17  
22100 Como- CO-  
Telephone : +39031586111  
Telefax : +39031586206  
E-mail address : safety@lechler.eu  
Responsible/issuing person

#### 1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299

This telephone number is available during office hours only.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET



according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	<p>EUH066 Repeated exposure may cause skin dryness or cracking.</p> <p><b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection.</p> <p><b>Response:</b> P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.</p>

Hazardous components which must be listed on the label:

- 123-86-4 n-butyl acetate
- 104810-47-1 reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- omega-hydroxypoly(oxyethylene) and alpha
- 1065336-91-5 Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
- 97-86-9 isobutyl methacrylate

### 2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

## SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

**MEGALACK UHS CLEARCOAT**

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

Chemical nature : Liquid solution

**Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
2-butoxyethyl acetate	112-07-2 203-933-3 01-2119475112-47	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 1 - < 5
ethyl acetate	141-78-6 205-500-4 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 5
acetone	67-64-1 200-662-2 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 1 - < 5
2-methylpropan-2-ol	75-65-0 200-889-7 01-2119444321-51	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335	>= 1 - < 5
reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha	104810-47-1 400-830-7 01-0000015075-76-0017	Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 0,25 - < 1
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40-0000	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 (Acute M=1) (Chronic M=1)	>= 0,25 - < 1
isobutyl methacrylate	97-86-9 202-613-0 01-2119488331-38	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Acute 1; H400 Note D	>= 0,1 - < 0,25
Substances with a workplace exposure limit :			
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 25 - < 30

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
Put shower on working place
- In case of eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.  
Seek medical advice.  
Put eye-washer on working place  
Remove contact lenses.
- If swallowed : If accidentally swallowed obtain immediate medical attention.  
Do NOT induce vomiting.  
Keep at rest.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.  
Seek medical advice.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

Keep containers and surroundings cool with water spray.

Unsuitable extinguishing media : Do NOT use water jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.  
Ensure adequate ventilation.  
Use personal protective equipment.  
Evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Ventilate the area.

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

(d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).

Pick up and transfer to properly labelled containers.  
Clean contaminated surface thoroughly.  
Dam up.  
Soak up with inert absorbent material and dispose of as hazardous waste.

### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid inhalation of vapour or mist.  
For personal protection see section 8.  
Thoroughly mix before using  
After using, store in a well-sealed container

Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
When transferring from one container to another apply earthing measures and use conductive hose material.  
No sparking tools should be used.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Solvent vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep away from sources of ignition - No smoking.  
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

Store in accordance with the particular national regulations.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

German storage class : 3 Flammable liquids

### 7.3 Specific end use(s)

: This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
n-butyl acetate	123-86-4	TWA	50 ppm	2016-03-01	ACGIH
		STEL	150 ppm	2016-03-01	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	50 ppm 333 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
ethyl acetate	141-78-6	TWA	400 ppm	2013-03-01	ACGIH
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017-01-31	2017/164/EU
		STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017-01-31	2017/164/EU
acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	Indicative			
2-methylpropan-2-ol	75-65-0	TWA	100 ppm		ACGIH

DNEL

2-butoxyethyl acetate

: End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Acute local effects  
Value: 200 mg/m<sup>3</sup>

End Use: Consumers

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

Exposure routes: Dermal  
Potential health effects: Acute systemic effects  
Value: 72 mg/kg

End Use: Consumers  
Exposure routes: Oral  
Potential health effects: Acute systemic effects  
Value: 36 mg/kg

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 80 mg/m<sup>3</sup>

End Use: Consumers  
Exposure routes: Dermal  
Potential health effects: Long-term systemic effects  
Value: 102 mg/kg

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Acute local effects  
Value: 333 mg/m<sup>3</sup>

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 133 mg/m<sup>3</sup>

End Use: Workers  
Exposure routes: Dermal  
Potential health effects: Long-term systemic effects  
Value: 169 mg/kg

n-butyl acetate : End Use: Professional use  
Exposure routes: Skin contact  
Potential health effects: Local effects  
Exposure time: 8 h  
Value: 7 ppm

End Use: Professional use  
Exposure routes: Inhalation  
Potential health effects: Local effects  
Value: 48 mg/m<sup>3</sup>

PNEC  
2-butoxyethyl acetate : Fresh water  
Value: 0,304 mg/l

Marine water  
Value: 0,03 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

Fresh water sediment

Value: 2,03 mg/kg

Marine sediment

Value: 0,203 mg/kg

Soil

Value: 0,415 mg/kg

Sewage treatment plant

Value: 90 mg/l

n-butyl acetate

: Water

Value: 0,18 mg/l

Soil

Value: 0,093 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Respiratory protection

: Provide adequate ventilation.

Hand protection

: Solvent-resistant gloves (butyl-rubber) recommended.  
For prolonged or repeated contact use protective gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams  
Protective gloves complying with EN 374.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.

Eye protection

: Chemical resistant goggles must be worn.

Skin and body protection

: Skin should be washed after contact.  
Workers should wear antistatic footwear.  
Personnel should wear protective clothing.  
Flame retardant antistatic protective clothing.

#### Environmental exposure controls

General advice

: Try to prevent the material from entering drains or water

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

courses.

If the product contaminates rivers and lakes or drains inform respective authorities.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like
Flash point	: 0 - < 21 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: Not applicable
pH	: not determined
Freezing point	: Not applicable
Boiling point	: not determined
Vapour pressure	: 1 hPa at 50 °C
Density	: 1,0213 g/cm <sup>3</sup>
Water solubility	: not determined
Partition coefficient: n-octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 90 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	: Not applicable
Evaporation rate	: not determined

#### 9.2 Other information

Solids by weight	: 62,87 %
Volatile organic compounds	: 37,12 %

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

(VOC) content

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

None reasonably foreseeable.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

#### 10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.  
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

#### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

Thermal decomposition : Not applicable

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Product

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.

Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

### Components:

#### **2-butoxyethyl acetate :**

Acute oral toxicity : LD50: 1.880 mg/kg, Rat  
Acute inhalation toxicity : LC0: 400 ppm, 4 h, Rat,  
Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate  
: LD50: 1.500 mg/kg, Rabbit

#### **acetone :**

Acute oral toxicity : LD50: 5.800 mg/kg, Rat  
Acute inhalation toxicity : LC50: 21 ppm, 8 h, Rat(female),

#### **Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate :**

Acute oral toxicity : LD50: 3.230 mg/kg, Rat

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish :  
Remarks:  
No data is available on the product itself.

Toxicity to fish  
acetone : LC50: 4.042 mg/l  
Exposure time: 14 d  
  
Species: Fish

Reaction mass of  
Bis(1,2,2,6,6-pentamethyl-4-  
piperidyl) sebacate and  
Methyl 1,2,2,6,6-  
pentamethyl-4-piperidyl  
sebacate : LC50: 0,97 mg/l  
Exposure time: 96 h  
  
Species: Lepomis macrochirus (Bluegill sunfish)  
Method: OECD Test Guideline 203  
  
LC50: 7,9 mg/l  
Exposure time: 96 h  
  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: OECD Test Guideline 203

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

LC50: 0,9 mg/l  
Exposure time: 96 h

Species: Brachydanio rerio (zebrafish)  
semi-static test Method: OECD Test Guideline 203

Reaction mass of : 1  
Bis(1,2,2,6,6-pentamethyl-4-  
piperidyl) sebacate and  
Methyl 1,2,2,6,6-  
pentamethyl-4-piperidyl  
sebacate

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Reaction mass of : NOEC: 1 mg/l  
Bis(1,2,2,6,6-pentamethyl-4-  
piperidyl) sebacate and Exposure time: 21 d  
Methyl 1,2,2,6,6- Species: Daphnia magna (Water flea)  
pentamethyl-4-piperidyl Method: OECD Test Guideline 211  
sebacate

### 12.2 Persistence and degradability

Biodegradability : No data available

### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

### 12.4 Mobility in soil

Mobility : No data available

### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3).  
The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
The following Waste Codes are only suggestions:150110\*

### SECTION 14: Transport information

#### 14.1 UN number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

#### 14.2 Proper shipping name

ADR PAINT

IMDG PAINT

IATA Paint

#### 14.3 Transport hazard class(es)

ADR : 3

IMDG : 3

IATA : 3

#### 14.4 Packing group

ADR

Packing group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

IMDG

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

Packing group : II  
Labels : 3  
EmS Code : F-E,S-E

### IATA

Packing group : II  
Labels : 3

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

#### IATA

Environmentally hazardous : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles : Banned and/or restricted

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

(Annex XVII)

64742-95-6	Hydrocarbons, C9, aromatics
------------	-----------------------------

MAL-Code-Number : 2-5 (1993)  
627-m3 air/10 g

German storage class : 3: Flammable liquids  
(TRGS 510)

Risk classification according to VbF : Flash point less than 21 °C, at 15 °C not miscible in water  
Specially dangerous flammable liquids

Water contaminating class (Germany) : water endangering  
VWWWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.  
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

### 15.2 Chemical safety assessment

No data is available on the product itself.

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## MEGALACK UHS CLEARCOAT

Version 1.14

Revision Date 23.01.2019

Print Date 25.01.2019

---

materials or in any process, unless specified in the text.