
Product name	:	MoTip Paint Remover
Article number	:	090410
Supplier / Producer	:	MOTIP DUPLI B.V. Wolframweg 2 NL-8471 XC WOLVEGA
Telephone number	:	+31 561 – 69 44 00
Telefax number	:	+31 561 – 69 44 31

Product description

High quality tool to remove old layers of lacquer on surfaces of stone, concrete, asphalt, metal and wood.

Applications

Paintwork
Stonework
Pavement

Product characteristics

User-friendly
Very effective
Gel structure
Spray pattern approximately 8 centimetre wide

Physical and Chemical Characteristics

Contents	:	500 ml
VOC-content	:	Approximately 98% w/w
Colour	:	Transparent
Scent	:	Characteristic
Relative density at 20°C	:	1,25 g/ml
Yield	:	1,5 g/sec
Vapour pressure at 20°C	:	3 to 4 bar
Coverage	:	Approximately 0,8 m ²



Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Before use, test the compatibility of the surface.

Apply paint remover generously and allow to take effect. The time to take effect depends on the quality and age of the lacquer to be removed.

Then, remove with a tool appropriate for this purpose. When required, repeat the treatment.

Contaminated paint remover should be regarded as chemical waste.