

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version		Revision Date:	Date of last issue: -
1.0	GB / EN	18.10.2019	Date of first issue: 18.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem UV Clear

Product code : 154.528

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Paints, Coatings

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH
Esinger Steinweg 50
25436 Uetersen
Germany
info@vosschemie.de

Telephone : 04122 717 0
Telefax : 04122 717158

Responsible Department : Laboratory

04122 717 0
sds@vosschemie.de

1.4 Emergency telephone number

Telephone : Giftinformationszentrum (GIZ)-Nord,
Göttingen, Deutschland
0551 19240

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version
1.0

GB / EN

Revision Date:
18.10.2019

Date of last issue: -
Date of first issue: 18.10.2019

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P261 Avoid breathing mist or vapours.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version
1.0

GB/EN

Revision Date:
18.10.2019

Date of last issue: -
Date of first issue: 18.10.2019

attention.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label:

Urethane Methacrylate
2,2-bis(acryloyloxymethyl)butyl acrylate
Methacrylic acid, monoester with propane-1,2-diol
pentaerythritol tetrakis(3-mercaptopropionate)
2-propenoic acid, reaction products with pentaerythritol
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Urethane Methacrylate	Not Assigned	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 30 - <= 50
2,2-bis(acryloyloxymethyl)butyl acrylate	15625-89-5 239-701-3 607-111-00-9 01-2119489896-11	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 6 - <= 11
Tetrahydrofurfuryl methacrylate	2455-24-5	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	>= 6 - <= 10
Methacrylic acid, monoester with propane-1,2-diol	27813-02-1 248-666-3 01-2119490226-37	Eye Irrit. 2; H319 Skin Sens. 1B; H317	>= 4 - <= 7.5
ethanol	64-17-5 200-578-6 603-002-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 3 - <= 6

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version
1.0

GB/EN

Revision Date:
18.10.2019

Date of last issue: -
Date of first issue: 18.10.2019

	01-2119457610-43		
2-propenoic acid, reaction products with pentaerythritol	1245638-61-2 01-2119490003-49	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 2; H411	$\geq 2 - \leq 4.8$
pentaerythritol tetrakis(3-mercaptopropionate)	7575-23-7 231-472-8 01-2119486981-23	Acute Tox. 4; H302 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M factor (chronic) = 10	$\geq 2 - \leq 4.5$
2-hydroxy-2-methylpropiophenone	7473-98-5 231-272-0 01-2119472306-39	Acute Tox. 4; H302 Aquatic Chronic 3; H412	$\geq 2 - \leq 4$
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	84434-11-7 282-810-6 01-2119987994-10	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	≤ 1.3
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	≤ 0.8
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	162881-26-7 423-340-5 015-189-00-5 01-2119489401-38	Skin Sens. 1; H317 Aquatic Chronic 4; H413	≤ 0.1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Do not leave the victim unattended.
Take off contaminated clothing and shoes immediately.
Wash contaminated clothing before re-use.
Show this safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

- Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Harmful if swallowed, in contact with skin or if inhaled.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
- Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Use water spray to cool unopened containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version		Revision Date:	Date of last issue: -
1.0	GB / EN	18.10.2019	Date of first issue: 18.10.2019

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

In the event of fire and/or explosion do not breathe fumes.
The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g. by containment or oil barriers).
Do not flush into surface water or sanitary sewer system.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Wear personal protective equipment.

Advice on protection against fire and explosion : No special protective measures against fire required.
Normal measures for preventive fire protection.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container.
Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Storage must be in accordance with the BetrSichV (Germany).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version
1.0

GB/EN

Revision Date:
18.10.2019

Date of last issue: -
Date of first issue: 18.10.2019

Advice on common storage : Keep away from food and drink.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m ³	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2-bis(acryloyloxymethyl) butyl acrylate	Consumers	Oral	Long-term systemic effects	1.39 mg/kg
	Consumers	Skin contact	Long-term systemic effects	0.48 mg/kg
	Workers	Skin contact	Long-term systemic effects	0.8 mg/kg
	Consumers	Inhalation	Long-term systemic effects	4.9 mg/m ³
	Workers	Inhalation	Long-term systemic effects	16.2 mg/m ³
Methacrylic acid, monoester with propane-1,2-diol	Workers	Inhalation	Long-term systemic effects	14.7 mg/m ³
	Workers	Skin contact	Long-term systemic effects	4.2 mg/kg
	Consumers	Inhalation	Long-term systemic effects	8.8 mg/m ³
pentaerythritol tetrakis(3-mercaptopropionate)	Consumers	Skin contact, Oral	Long-term systemic effects	2.5 mg/kg
	Workers	Inhalation	Long-term systemic effects	1.74 mg/m ³
	Workers	Dermal	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	2.5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	0.43 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version
1.0

GB / EN

Revision Date:
18.10.2019

Date of last issue: -
Date of first issue: 18.10.2019

			effects	
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	Workers	Inhalation	Long-term systemic effects	5.88 mg/m3
	Workers	Skin contact	Long-term systemic effects	1.7 mg/kg
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Workers	Inhalation	Long-term systemic effects	21 mg/m3
	Workers	Skin contact	Long-term systemic effects	3 mg/kg
	Consumers	Inhalation	Long-term systemic effects	5.2 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	1.5 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2-bis(acryloyloxymethyl)butyl acrylate	Fresh water	0.00087 mg/l
	Marine water	0.000087 mg/l
	Fresh water sediment	0.017 mg/kg
	Marine sediment	0.002 mg/kg
	Sewage treatment plant	6.25 mg/l
	Soil	0.003 mg/kg
	Oral (Secondary Poisoning)	10 mg/kg
Methacrylic acid, monoester with propane-1,2-diol	Fresh water	0.904 mg/l
	Marine water	0.904 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	6.28 mg/kg
	Marine sediment	6.28 mg/kg
	Soil	0.727 mg/kg
pentaerythritol tetrakis(3-mercaptopropionate)	Fresh water	0.00003 mg/l
	Sewage treatment plant	2.39 mg/l
	Fresh water sediment	0.00102 mg/l
	Soil	0.000184 mg/kg dry weight (d.w.)
2-hydroxy-2-methylpropiophenone	Fresh water	0.002 mg/l
	Marine water	0.0002 mg/l
	Sewage treatment plant	45 mg/l
	Fresh water sediment	0.009 mg/kg
	Marine sediment	0.001 mg/kg
	Soil	0.001 mg/kg
2-propenoic acid, reaction products with pentaerythritol	Fresh water	0.003 mg/l
	Marine water	0.0003 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1.73 mg/kg
	Marine sediment	0.173 mg/kg
	Soil	0.34 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version
1.0

GB / EN

Revision Date:
18.10.2019

Date of last issue: -
Date of first issue: 18.10.2019

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	Fresh water	0.001 mg/l
	Marine water	0.0001 mg/l
	Fresh water	0.24 mg/kg
	Marine sediment	0.024 mg/kg
	Soil	0.047 mg/kg
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Fresh water	0.001 mg/l
	Marine water	0.001 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	0.712 mg/kg
	Marine sediment	0.712 mg/kg
	Soil	20 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : butyl-rubber

Break through time : > 480 min

Glove thickness : >= 0.4 mm

Directive : DIN EN 374

Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapour type (A-P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version		Revision Date:	Date of last issue: -
1.0	GB / EN	18.10.2019	Date of first issue: 18.10.2019

In case of inadequate ventilation wear respiratory protection.

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

Environmental exposure controls

Soil : Avoid subsoil penetration.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: translucent
Odour	: characteristic
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Density	: ca. 1.1 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: Not applicable
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version		Revision Date:	Date of last issue: -
1.0	GB / EN	18.10.2019	Date of first issue: 18.10.2019

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed, in contact with skin or if inhaled.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 886.22 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: < 2,000 mg/kg Method: Expert judgement

Components:

Urethane Methacrylate:

Acute oral toxicity	:	Acute toxicity estimate: 500 mg/kg Method: Expert judgement
Acute inhalation toxicity	:	Acute toxicity estimate: 11 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Expert judgement

2,2-bis(acryloyloxymethyl)butyl acrylate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.55 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,170 mg/kg

Tetrahydrofurfuryl methacrylate:

Acute oral toxicity : LD50 Oral (Rat): 3,945 mg/kg
Method: OECD Test Guideline 401

Methacrylic acid, monoester with propane-1,2-diol:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

ethanol:

Acute oral toxicity : LD50 Oral (Rat): 10,470 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 117 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

2-propenoic acid, reaction products with pentaerythritol:

Acute oral toxicity : LD50 Oral (Rat): 620 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402

pentaerythritol tetrakis(3-mercaptopropionate):

Acute oral toxicity : LD50 (Rat): > 1,000 - < 2,000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat): 3,363 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

2-hydroxy-2-methylpropiophenone:

Acute oral toxicity : LD50 Oral (Rat): 1,694 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rat): 6,929 mg/kg
Method: OECD Test Guideline 402

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

butanone:

Acute oral toxicity : LD50 Oral (Rat): 3,460 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,000 mg/kg
Method: OECD Test Guideline 402

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

Urethane Methacrylate:

Result : Skin irritation

Tetrahydrofurfuryl methacrylate:

Result : Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

2-propenoic acid, reaction products with pentaerythritol:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Urethane Methacrylate:

Result	: Moderate eye irritation
--------	---------------------------

Tetrahydrofurfuryl methacrylate:

Result	: Moderate eye irritation
--------	---------------------------

Methacrylic acid, monoester with propane-1,2-diol:

Result	: Moderate eye irritation
--------	---------------------------

ethanol:

Result	: Mild eye irritation
--------	-----------------------

2-propenoic acid, reaction products with pentaerythritol:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

2,2-bis(acryloyloxymethyl)butyl acrylate:

Exposure routes	: Skin contact
Species	: Humans
Result	: positive

Methacrylic acid, monoester with propane-1,2-diol:

Assessment	: The product is a skin sensitiser, sub-category 1B.
------------	--

2-propenoic acid, reaction products with pentaerythritol:

Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: The product is a skin sensitiser, sub-category 1B.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version		Revision Date:	Date of last issue: -
1.0	GB / EN	18.10.2019	Date of first issue: 18.10.2019

pentaerythritol tetrakis(3-mercaptopropionate):

Exposure routes	: Dermal
Species	: Guinea pig
Assessment	: The product is a skin sensitizer, sub-category 1A.
Method	: OECD Test Guideline 406
Result	: positive

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Species	: Mouse
Method	: OECD Test Guideline 429
Result	: The product is a skin sensitizer, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

Tetrahydrofurfuryl methacrylate:

Assessment	: May cause respiratory irritation.
------------	-------------------------------------

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

2,2-bis(acryloyloxymethyl)butyl acrylate:

Species	: Mouse
NOAEL	: > 200 mg/kg
Application Route	: Dermal
Exposure time	: 16

Species	: Rat
NOAEL	: > 200 mg/kg
Application Route	: Dermal
Exposure time	: 16

Species	: Rat
NOAEL	: > 250 mg/kg
Application Route	: Oral
Exposure time	: 28

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urethane Methacrylate:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

2,2-bis(acryloyloxymethyl)butyl acrylate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0.87 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 19.9 mg/l
Exposure time: 48 h
Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae : EC50 (Scenedesmus subspicatus): 18.8 mg/l
End point: Growth rate
Exposure time: 72 h
Method: Regulation (EC) No. 440/2008, Annex, C.3

M-Factor (Acute aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Methacrylic acid, monoester with propane-1,2-diol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 493 mg/l
Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 143 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 97.2 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other : NOEC: 45.2 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

aquatic invertebrates (Chronic toxicity)
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

ethanol:

Toxicity to fish : LC50 (Fish): 11,200 mg/l
Exposure time: 96 h
This product has no known ecotoxicological effects.

Toxicity to fish (Chronic toxicity) : NOEC: 250 mg/l
Species: Fish

2-propenoic acid, reaction products with pentaerythritol:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 3.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 13 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (algae)): 33 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

pentaerythritol tetrakis(3-mercaptopropionate):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.42 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.35 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

M-Factor (Acute aquatic toxicity) :

: 1

M-Factor (Chronic aquatic toxicity) : 10

2-hydroxy-2-methylpropiophenone:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 160 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 119 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 1.95 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 1.89 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.26 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 1.01 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
End point: mortality
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 1,972 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	GB / EN 18.10.2019	Date of first issue: 18.10.2019

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

12.2 Persistence and degradability

Components:

2,2-bis(acryloyloxymethyl)butyl acrylate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 82 %
Exposure time: 28 d

Methacrylic acid, monoester with propane-1,2-diol:

Biodegradability : Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

2-propenoic acid, reaction products with pentaerythritol:

Biodegradability : Biodegradation: 14 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

pentaerythritol tetrakis(3-mercaptopropionate):

Biodegradability : Result: Not rapidly biodegradable
Biodegradation: 26 %
Exposure time: 28 d

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Biodegradability : Biodegradation: < 10 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

2,2-bis(acryloyloxymethyl)butyl acrylate:

Bioaccumulation : Bioconcentration factor (BCF): 300

Partition coefficient: n-octanol/water : log Pow: 4.35 (23 °C)
Method: OECD Test Guideline 107

Tetrahydrofurfuryl methacrylate:

Partition coefficient: n-octanol/water : log Pow: 1.76 (22.6 °C)

Methacrylic acid, monoester with propane-1,2-diol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version		Revision Date:	Date of last issue: -
1.0	GB / EN	18.10.2019	Date of first issue: 18.10.2019

Partition coefficient: n-octanol/water : log Pow: 0.97 (20 °C)

ethanol:

Partition coefficient: n-octanol/water : log Pow: -0.3

2-propenoic acid, reaction products with pentaerythritol:

Partition coefficient: n-octanol/water : log Pow: 3.11

pentaerythritol tetrakis(3-mercaptopropionate):

Bioaccumulation : Bioconcentration factor (BCF): 23.7

Partition coefficient: n-octanol/water : log Pow: 2.8 (30 °C)

2-hydroxy-2-methylpropiophenone:

Partition coefficient: n-octanol/water : Pow: 41.5 (25 °C)
log Pow: 1.62 (25 °C)
pH: 5.75

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Partition coefficient: n-octanol/water : log Pow: 2.91 (25 °C)
pH: 4.4

butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3 (40 °C)
pH: 7

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Partition coefficient: n-octanol/water : log Pow: 5.8 (22 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Do not dispose of with domestic refuse. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Dispose of in accordance with local regulations. Send to a licensed waste management company.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Packaging that is not properly emptied must be disposed of as the unused product. Dispose of in accordance with local regulations.
Waste Code	: The following Waste Codes are only suggestions: 08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN	: UN 3082
ADR	: UN 3082
RID	: UN 3082
IMDG	: UN 3082
IATA	: UN 3082

14.2 UN proper shipping name

ADN	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ADR	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-bis(acryloyloxymethyl)butyl acrylate, 2-propenoic acid, reaction products with pentaerythritol)
RID	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-bis(acryloyloxymethyl)butyl acrylate, 2-propenoic acid, reaction products with pentaerythritol)
IMDG	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-bis(acryloyloxymethyl)butyl acrylate, 2-propenoic acid, reaction products with pentaerythritol)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

IATA : Environmentally hazardous substance, liquid, n.o.s.
(2,2-bis(acryloyloxymethyl)butyl acrylate, 2-propenoic acid,
reaction products with pentaerythritol)

14.3 Transport hazard class(es)

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADN
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

ADR
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

RID
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG
Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)
Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Class 9 - Miscellaneous dangerous substances and articles

IATA (Passenger)
Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Class 9 - Miscellaneous dangerous substances and articles

14.5 Environmental hazards

ADN
Environmentally hazardous : yes

ADR

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

Environmentally hazardous : yes

RID

Environmentally hazardous : no

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E1 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: < 350 g/l
VOC content for the product in a ready to use condition.

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	18.10.2019	Date of first issue: 18.10.2019

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Mari-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem UV Clear

Version	Revision Date:	Date of last issue: -
1.0	GB / EN 18.10.2019	Date of first issue: 18.10.2019

time Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H302
Acute Tox. 4	H332
Acute Tox. 4	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 1	H410

Classification procedure:

Calculation method
Calculation method
Expert judgement and weight of evidence determination.
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.