



Technical Information

Product name	:	MoTip Sanding aid	
Article number	:	04057	
Supplier / Producer	:	MOTIP DUPLI B.V.	
		Wolframweg 2	
		NL-8471 XC WOLVEGA	
		Telephone number	+31 561 – 69 44 00
		Telefax number	+31 561 – 69 44 31

Product description

High quality black control lacquer as aid for sanding.

Product characteristics

Easy in use
Fast drying

Physical and Chemical Characteristics

Contents	:	500 ml
Base	:	Nitro-cellulose binder
Colour	:	Black
VOC-content	:	Approximately 92% w/w
Coverage	:	3 to 4 m ²
Sandable	:	After 5 to 10 minutes

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease.

Treatment

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply a thin layer of sanding aid and allow to dry. Sand the surface till the control lacquer is completely removed.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.