



Product Name : MoTip Fibre Putty Filled
Article Number : 000053 000070
Contents : 250 gram 1.000 gram

Supplier / Producer : MOTIP DUPLI B.V.
Wolframweg 2
NL-8471 XC WOLVEGA
Telephone number +31 561 – 69 44 00
Telefax number +31 561 – 69 44 31

Product description

High quality 2 component fibreglass putty with special fillers to fill holes in surfaces of steel, aluminium, wood, concrete and polyester.

Product characteristics

Easy to sand
Excellent filling properties
High impact resistance
Re-sprayable with all lacquer systems
Resistant to chemicals and weather influences
Excellent adhesion

Physical and Chemical Characteristics

Base Putty : Polyester resin
Base Harder : Benzoyl peroxide
Density : 1,90 Kg/dm³
Harder to be added : 2,5%
Potlife : 3 to 5 minutes
Layer thickness to apply : Up to 2 centimetres
Sandable after : approximately 30 minutes
Re-Sprayable after : approximately 1 hour
Heat resistant : To 120°C

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Processing temperature 15 – 25°C.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

Treatment

The surface should be clean, dry and free of grease. Mix the required amount of putty with the harder. Apply in the desired layer thickness. After hardening, sand and when desired apply a fine putty.

The drying time depends on the ambient temperature.

After use, directly clean the tools used.

Do not store the surplus material, mixed with harder, in the can.