

Printing date 26.11.2018 Version number 1 Revision: 26.11.2018

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier CODE 1000

· Trade name: SWIN MISCHLACK

· Article number: SW-XXXX-*

· Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Environmental release category ERC8c Widespread use leading to inclusion into/onto article (indoor)
- · Application of the substance / the mixture Coating material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SWIN Lacksysteme

Boschweg 5

D-48351 Everswinkel

info@swinsysteme.de

- · Further information obtainable from: +49 2582-67613 / +49 2582-67677
- · Emergency telephone number: Giftnotruf Berlin: ++49 (0) 30 19240

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

· Signal word Warning

- · Hazard-determining components of labelling:
- n-butyl acetate
- · Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)



Printing date 26.11.2018 Version number 1 Revision: 26.11.2018

Trade name: SWIN MISCHLACK

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards -
- · Results of PBT and vPvB assessment
- **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|---|--|---------|
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX | n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336 | 25-50% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX | 2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 | 2.5-10% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX | xylene ♠ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 2.5-10% |
| CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47-XXXX | 2-butoxyethyl acetate Acute Tox. 4, H312; Acute Tox. 4, H332 | ≤2.5% |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: Personal protection for the First Aider.
- · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)



Printing date 26.11.2018 Version number 1 Revision: 26.11.2018

Trade name: SWIN MISCHLACK

(Contd. of page 2)

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Restrict the quantity stored at the work place.

· Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Suitable material for receptacles and pipes: steel or stainless steel.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

| · Ingredients wit | h limit values tl | hat reauire | monitoring a | at the workplace: |
|-------------------|-------------------|-------------|--------------|-------------------|
| | | | | |

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm

Sk

(Contd. on page 4)



Printing date 26.11.2018 Version number 1 Revision: 26.11.2018

Trade name: SWIN MISCHLACK

(Contd. of page 3)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P2

· Protection of hands:

Only use chemical-protective gloves with CE-labelling of category III.



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be checked prior to the application.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber (Ansell Sol-Vex®)

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

Value for the permeation: Level ≤ 1

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact => 480 minutes gloves made of the following materials are suitable:

HPPE-laminatet film (Ansell Barrier®)

· Eye protection:



Tightly sealed goggles

· Body protection:

Protective clothing, anti-static (TYVEK® CLASSIC PLUS)

Safety shoes/boots, antstatic

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

Odour: AromaticOdour threshold: Not determined.

· pH-value Not applicable.

(Contd. on page 5)



Printing date 26.11.2018 Version number 1 Revision: 26.11.2018

Trade name: SWIN MISCHLACK

| | (Contd. of page |
|--|---|
| Change in condition Melting point/freezing point: Initial boiling point and boiling range: | Undetermined. : 124 °C |
| Flash point: | 23 - 60 °C |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | 315 °C |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.2 Vol % |
| Upper: | 7.5 Vol % |
| Vapour pressure at 20 °C: | 10.7 hPa |
| Density | 1.00 - 1.70 g/ml |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: | DIN 53211 (6 mm) - 38 sec |
| Dynamic: | Not determined. |
| Kinematic at 20 °C: | 100 s (ISO 6 mm) |
| Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 26.11.2018 Version number 1 Revision: 26.11.2018

Trade name: SWIN MISCHLACK

(Contd. of page 5)

· STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European waste catalogue | | |
|----------------------------|---|--|
| 08 00 00 | WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS | |
| 08 01 00 | wastes from MFSU and removal of paint and varnish | |
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances | |

· Uncleaned packaging:

15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00: packaging (including separately collected municipal packaging waste)

15 01 10*: packaging containing residues of or contaminated by dangerous substances

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

| · UN-Number | |
|------------------|---------------|
| · ADR, ADN, IMDG | not regulated |
| IATA | UN1263 |

· UN proper shipping name

· ADR, ADN, IMDG not regulated · IATA PAINT

(Contd. on page 7)



Printing date 26.11.2018 Version number 1 Revision: 26.11.2018

Trade name: SWIN MISCHLACK

| | (Contd. of page |
|--|--|
| · Transport hazard class(es) | |
| · ADR, ADN, IMDG | |
| · Class | not regulated |
| · IATA | |
| | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · Packing group | |
| · ADR, IMDG | not regulated |
| · IATÁ | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| Transport in bulk according to Annex I | I of Marpol |
| and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| · <i>ADR</i> | |
| Remarks: | No dangerous goods in containers of 450 litres made capacity acc. to ADR 2.2.3.1.5.1 |
| · IMDG | |
| · Remarks: | No dangerous goods in containers of 30 litres material capacity acc. to IMDG 2.2.3.1.5 |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: -
- · Contact: -

(Contd. on page 8)



Printing date 26.11.2018 Version number 1 Revision: 26.11.2018

Trade name: SWIN MISCHLACK

(Contd. of page 7)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

an.