

Product Description

Drying wood oil for maintenance of larch, pine, pressure treated wood and dark hard woods.

The product has a good penetration into the wood, creating a hydrophobic surface that stabilizes and prevents shrinkage cracks in the wood.

B3 Wood Oil containing active UV filter against the sun's harmful rays and is slightly thixotropic, which gives the product a light anti-drip effect.

Directions for use

Use on varnishes, paint and the like.

Weathered wood such as Spruce, Pine and Larch must be cleaned with appropriate cleaner.

Weathered hardwood such as Teak, Mahogany, and the like sanded to fresh wood.

Contaminated surfaces must be cleaned with appropriate cleaner.

Apply the Wood oil with a sponge, brush or roller. Repeat the treatment until the wood appears uniformly and saturated, however, without forming surface film.

Retreatment is usually 1-2 times a year or as needed.

Contains agents that protect the surface against fouling. For exterior use only.

Degrease very oily woods such as Teak and Iroko by wiping the surface with white spirit before treatment with wood oil.

The wood must be clean, dry and sustainable. The substrate must also be sanded and without previous treatment

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

The product should not be used without the addition of pigment.

Technical data

Binder:	Alkyd resin
Type:	Wood Oil, Water-borne
Gloss:	
Vol. dry:	Approx. 22%
Colours:	Clear, can be tinted in transparent shades
Drying:	1-2 hours, recoatable after approx. 16 hours at 20 ° C 65% RH.
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Should not be thinned
Coverage:	5-10 m ² /ltr. Depending on the absorption
Tools:	Brush, cloth or sponge
Mal-Code:	00-1 (1993)

