according to 1907/2006/EC, Article 31 Version number 4 (replaces version 3)

Printing date 30.01.2023



Revision: 30.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Q 20-100 Fiberglass

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC9a Coatings and paints, thinners, paint removers
- Application of the substance / the mixture Knife filler/ Surfacer

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Q-Company Int. GmbH Lentföhrdener Strasse 12 – 14 D-24576 Weddelbrook, Germany

msds@qrefinish.com Tel +49 (0)4192 891420

www.qrefinish.com

· 1.4 Emergency telephone number: +49 (0)551-19240 (Giftinformationszentrum-Nord)

## **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

health hazard

*Repr. 2* H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2H315Causes skin irritation.Eye Irrit. 2H319Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

• Hazard pictograms



· Signal word Danger

(Contd. on page 2)

GB

according to 1907/2006/EC, Article 31 Version number 4 (replaces version 3)

Printing date 30.01.2023

Revision: 30.01.2023

#### Trade name: Q 20-100 Fiberglass

(Contd. of page 1) · Hazard-determining components of labelling: Styrene maleic anhydride Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4methylphenyl)amino]-· Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child. H372 Causes damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

### **SECTION 3:** Composition/information on ingredients

#### · 3.2 Mixtures

<sup>·</sup> Description: Mixture of substances listed below with nonhazardous additions.

EINECS: 202-851-5       Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372;         Reg.nr.: 01-2119457861-32       Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315;         Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412         EC number: 911-490-9       Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl) amino]- $\textcircled{Eye Dam. 1, H318; } Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412   $	ous components:		
$ \begin{array}{c} E thanol \ 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)\\ amino]-\\ \textcircledleft \\ \hline e ye \ Dam. \ 1, \ H318; \ \textcircledleft \\ Acute \ Tox. \ 4, \ H302; \ Skin \ Irrit. \ 2, \\ H315; \ Skin \ Sens. \ 1, \ H317; \ Aquatic \ Chronic \ 3, \ H412 \\ \hline cAS: \ 108-31-6 \\ \hline eINECS: \ 203-571-6 \\ \hline Resp. \ Sens. \ 1, \ H334; \ STOT \ RE \ 1, \ H372; \ \textcircledleft \\ Skin \ Corr. \ 1B, \\ H314; \ Eye \ Dam. \ 1, \ H318; \ \textcircledleft \\ Acute \ Tox. \ 4, \ H302; \ Skin \ Sens. \\ \end{array} $	: 202-851-5 01-2119457861-32 Eye Irrit. 2, H319;	Acute Tox. 4, H332; Skin Irrit. 2, H315;	<i>≥10-≤20%</i>
EINECS: 203-571-6 Reg.nr.: 01-2119472428-31 H314; Eye Dam. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens.	Ethanol 2-[[2-(2-h amino]-	ydroxyethoxy)ethyl] (4-methylphenyl) ; ① Acute Tox. 4, H302; Skin Irrit. 2,	<i>≥</i> 0.1-<1%
Specific concentration limit: Skin Sens. 1A; H317: $C \ge 0.001$ %	: 203-571-6 01-2119472428-31 (01-2119472428-31) (01-211947248-31) (01-211947248-31) (01-211947248-31) (01-211947248-31) (01-219	318;	≥0.001-<0.1



according to 1907/2006/EC, Article 31 Version number 4 (replaces version 3)

Printing date 30.01.2023

REFINISH

Revision: 30.01.2023

Trade name: Q 20-100 Fiberglass

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet

• 5.2 Special hazards arising from the substance or mixture

- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- $\cdot$  6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

## · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

• *Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.* 

(Contd. on page 4)

<sup>-</sup> GB

according to 1907/2006/EC, Article 31 Version number 4 (replaces version 3)

Printing date 30.01.2023

Revision: 30.01.2023

Trade name: Q 20-100 Fiberglass

(Contd. of page 3)

*Protect against electrostatic charges. Keep respiratory protective device available.* 

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- **Requirements to be met by storerooms and receptacles:** No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 100-42-5 Styrene

WEL Short-term value: 1080 mg/m<sup>3</sup>, 250 ppm Long-term value: 430 mg/m<sup>3</sup>, 100 ppm

#### 108-31-6 maleic anhydride

WEL Short-term value: 3 mg/m<sup>3</sup> Long-term value: 1 mg/m<sup>3</sup> Sen

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- · Respiratory protection:

*Filter A/P2 (EN 141, EN 143)* 



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq 0.7 \text{ mm}$ 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the



according to 1907/2006/EC, Article 31

Printing date 30.01.2023 Version number 4 (replaces version 3)

REFINISH

Revision: 30.01.2023

#### Trade name: Q 20-100 Fiberglass

· Solids content (weight-%):

(Contd. of page 4) resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material** Value for the permeation: Level  $\leq 6$ 

## · Eye/face protection

Tightly sealed goggles

#### **SECTION 9: Physical and chemical properties** • 9.1 Information on basic physical and chemical properties · General Information · Physical state Fluid · Colour: Green · Odour: Characteristic · Odour threshold: Not determined. • Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling range 145.2 °C (100-42-5 Styrene) · Flammability Flammable. · Lower and upper explosion limit 1.2 Vol % (100-42-5 Styrene) · Lower: · Upper: 8.9 Vol % (100-42-5 Styrene) · Flash point: 31 °C (DIN 53213) · Ignition temperature: 480 °C (DIN 51794) • Decomposition temperature: Not determined. Not determined · pH · Viscosity: · Kinematic viscosity Not determined. · Dynamic at 20 °C: 60,000-80,000 mPas · Solubility · water: Not miscible or difficult to mix. · Partition coefficient n-octanol/water (log value) Not determined. 6 hPa (100-42-5 Styrene) · Vapour pressure at 20 °C: · Density and/or relative density · Density at 20 °C: 1.633 g/cm<sup>3</sup> (DIN 53217) Not determined. · Relative density Not determined. · Vapour density • 9.2 Other information · Appearance: · Form: Viscous · Important information on protection of health and environment, and on safety. • Auto-ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Solvent content: · VOC (EC) 0 35 %

80.3 %

(Contd. on page 6)

*Version number 4 (replaces version 3)* 

Printing date 30.01.2023



Revision: 30.01.2023

Trade name: Q 20-100 Fiberglass

		(Contd. of page
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical hazard of	classes	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- *Respiratory or skin sensitisation May cause an allergic skin reaction.*
- · Reproductive toxicity Suspected of damaging the unborn child.
- · STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

(Contd. on page 7)

GB

according to 1907/2006/EC, Article 31 Version number 4 (replaces version 3)

Printing date 30.01.2023



Revision: 30.01.2023

Trade name: Q 20-100 Fiberglass

(Contd. of page 6)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- $\cdot$  Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation


Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3269
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN3269 POLYESTER RESIN KIT POLYESTER RESIN KIT
· 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	3 (F3) Flammable liquids. 3
· IMDG, IATA	
Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III



Version number 4 (replaces version 3)



Revision: 30.01.2023

Trade name: Q 20-100 Fiberglass

	(Contd. of page
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. - F-E,S-D A
• 14.7 Maritime transport in bulk according to IM instruments	<i>to</i> Not applicable.
· Transport/Additional information:	
• ADR • Limited quantities (LQ) • Transport category • Tunnel restriction code	5L 3 E
• IMDG • Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU


· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:



• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 9)



Version number 4 (replaces version 3)



Revision: 30.01.2023

## Trade name: Q 20-100 Fiberglass

Printing date 30.01.2023

	(Contd. of page 8)
H335 May cause respiratory irritation.	
H361d Suspected of damaging the unborn child.	
H372 Causes damage to organs through prolonged or repeated exposure.	
H412 Harmful to aquatic life with long lasting effects.	
EUH071 Corrosive to the respiratory tract.	
1 2	
Classification according to Regulation (EC) No 1272/2008	1 . 1.
The classification of the mixture is generally based on the calculation method using substance	data according
to Regulation (EC) No 1272/2008.	
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulatio	ons Concerning the
International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	<i>a</i>
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreeme	nt Concerning the
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B	
Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Dam. 1. Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Resp. Sens. 1: Respiratory sensitisation – Category 1	
Skin Sens. 1: Skin sensitisation – Category 1	
Skin Sens. 1A: Skin sensitisation – Category 1A	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
• * Data compared to the previous version altered.	