



Q 20-400

1K NC -Putty

Characteristics

1K NC Multi Filler Paste is a one component, ready to use product, based on nitrocellulose resins. Designed for spot repair work to fill small imperfections such as scratches, pinholes and stone chip damages. Easy to apply, dries quickly in thin layers. This product creates smooth coating with minimal shrinkage and very good flexibility. It can be applied over polyester putties and acrylic primers. Suitable also for metal surfaces, including steel, aluminium and zinc-coated surfaces.


Physical Characteristics



Polyester



2004/42/II B(c)(540) max. 540 g/l



12 month

Density: 1.67 – 1.69 g/cm³

Application

Prior to application, the surface must be cleaned, dried, degreased and matted with abrasives. Apply the filler paste in very thin layers at 20°C and allow it to dry for 15 - 30 minutes between coats. Total film thickness should not exceed 70 - 80 µm.

Drying



30 - 50 min
depending on the thickness



P240-P400



P240-P400

Storage



Store the product in a ventilated place. Keep away from direct exposure to sunlight. Keep between +5°C and 20°C.

Safety



For more informations check the safety data sheet.



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products. Copyright: Q-Company Int. GmbH, all rights reserved.