

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: SILICONE REMOVER SLOW

Trade code: L0000695

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Coatings and paints, thinners, paint removers

Degreasing agent Liquid

Professional uses

Uses advised against: N.A.

1.3. Details of the supplier of the safety data sheet

Company: Lechler SpA - Via Cecilio, 17 - 22100 Como - CO - Italy

Telephone: +39031586111

First Email: safety@lechler.eu

1.4. Emergency telephone number

UNITED KINGDOM: Emergency Number 0044 1606738600 - This telephone number is available during office hours only (8.45-16.45). UNITED STATES OF AMERICA: Emergency Contact: Lechler SPA -Tel. +39-031-586301 (8.00-18.00).

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

- Flam. Liq. 2 Highly flammable liquid and vapour.
- Eye Irrit. 2 Causes serious eye irritation.
- STOT SE 3 May cause drowsiness or dizziness.
- Asp. Tox. 1 May be fatal if swallowed and enters airways.

Adverse physicochemical, human health and environmental effects:

No other hazards 2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Hazard statements

- H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

ethyl acetate

propan-2-ol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

Results of PBT and vPvB assessment Not a PBT, vPvB substance as per the criteria of the REACH Regulation. Endocrine disrupting properties-Toxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Endocrine disrupting properties-Ecotoxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: SILICONE REMOVER SLOW

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥80 - ≤90 %	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC:919-857-5	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, DECLP(*)	01-2119463258-33
≥10 - ≤12.5 %	ethyl acetate	CAS:141-78-6 EC:205-500-4 Index:607-022- 00-5	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	01-2119475103-46
≥3 - ≤5 %	propan-2-ol	CAS:67-63-0 EC:200-661-7 Index:603-117- 00-0	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	01-2119457558-25

(*)DECLP Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008.

The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment. Remove all sources of ignition. Remove persons to safety. See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight. Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
ethyl acetate CAS: 141-78-6	EU		Long Term: 734 mg/m3 - 200 ppm; Short Term: 1468 mg/m3 - 400 ppm Behaviour Indicative 2017/164/EU
	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	
propan-2-ol CAS: 67-63-0	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	
	ACGIH		Long Term: 200 ppm; Short Term: 400 ppm A4, BEI - Eye and URT irr, CNS impair
Biological limit values			
propan-2-ol CAS: 67-63-0	Value: 2 m		one ; Medium: Urine gical Exposure Indices
	Biological Indicator: Acetone; Sampling Period: End of turn; End of working week Value: 40 mg/L; Medium: Urine Remark: Maximum allowable occupational exposure limits in the workplace - Table 3. Adopted Biological Exposu		
	Biological Indicator: Acetone; Sampling Period: End of turn Value: 50 mg/L; Medium: Blood Remark: Croatia. Biological Exposure Limits		
	Value: 86 r	nicromol per lit	one; Sampling Period: End of turn tre; Medium: Blood al Exposure Limits
	Value: 50 r	ng/L; Medium:	one; Sampling Period: End of turn Urine al Exposure Limits
	Value: 86 r	nicromol per lit	one; Sampling Period: End of turn tre; Medium: Urine al Exposure Limits
	Value: 25 r	ng/L; Medium:	one; Sampling Period: Immediately after exposure or after working hours Blood ogical limit values
	Value: 25 r	ng/L; Medium:	one; Sampling Period: Immediately after exposure or after working hours Urine ogical limit values
		ndicator: Aceto ng/L; Medium:	one; Sampling Period: End of turn; End of working week Urine

Remark: Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices for work

Biological Indicator: Acetone; Sampling Period: End of turn; End of working week Value: 40 mg/L; Medium: Urine Remark: Portuguese Norm 1796 - Biological Exposure Indices

Biological Indicator: Acetone; Sampling Period: End of turn Value: 50 mg/L; Medium: Urine Remark: Romania. Biological limit values

Biological Indicator: Acetone; Sampling Period: End of turn Value: 25 mg/L; Medium: Blood Remark: Slovenia. BAT-values

Biological Indicator: Acetone; Sampling Period: End of turn Value: 25 mg/L; Medium: Urine Remark: Slovenia. BAT-values

Biological Indicator: Acetone; Sampling Period: FSL Value: 40 mg/L; Medium: Urine Remark: Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure Values

Biological Indicator: Acetone; Sampling Period: Immediately after exposure or after working hours Value: 25 mg/L; Medium: Urine Remark: Svizzera. Lista di valori BAT

Biological Indicator: Acetone; Sampling Period: Immediately after exposure or after working hours Value: 4 Millimoles per liter; Medium: Urine Remark: Svizzera. Lista di valori BAT

Biological Indicator: Acetone; Sampling Period: Immediately after exposure or after working hours Value: 25 mg/L; Medium: Blood Remark: Svizzera. Lista di valori BAT

Biological Indicator: Acetone; Sampling Period: Immediately after exposure or after working hours Value: 4 Millimoles per liter; Medium: Blood Remark: Svizzera. Lista di valori BAT

Biological Indicator: Acetone; Sampling Period: End of turn; End of working week Value: 40 mg/L; Medium: Urine Remark: ACGIH - Indicatori di Esposizione Biologica (BEI)

Biological Indicator: Acetone; Sampling Period: End of workday at end of workweek Value: 40 mg/L; Medium: Urine Remark: VE.Biological Exposure Limits

Predicted No Effect Concentration (PNEC) values

propan-2-ol CAS: 67-63-0	Exposure Route: Fresh Water; PNEC Limit: 140.9 mg/l			
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 140.9 mg/l			
	Exposure Route: Marine water; PNEC Limit: 140.9 mg/l			
	Exposure Route: Freshwater sediments; PNEC Limit: 552 mg/kg			
	Exposure Route: Marine water sediments; PNEC Limit: 552 mg/kg			
	Exposure Route: Soil; PNEC Limit: 28 mg/kg			
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 2251 mg/l			
Derived No Effect Level	(DNEL) values			
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics	- Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Professional: 208 mg/kg			
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Professional: 871 mg/m3			
	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Consumer: 125 mg/kg			
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Consumer: 185 mg/m3			
	Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects Consumer: 125 mg/kg			
propan-2-ol CAS: 67-63-0	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects			
Date 03/04/2025	Production Name SILICONE REMOVER SLOW			

	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Consumer: 89 mg/m3					
	Exposure Route: Oral; Exposure Frequency: Long Term, systemic effects					
	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects					
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Professional: 500 mg/m3					
8.2. Exposure controls	5					
Eye protection:						
Use close fitting	Use close fitting safety goggles, don't use eye lens.					
Protection for skin:	Protection for skin:					
Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.						
Protection for hands:						
Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.						
Respiratory protection:						
Use adequate p	rotective respiratory equipment.					
Thermal Hazards:						
N.A.						
Environmental exposure	controls:					
N.A.						
Hygienic and Technical r	neasures					
N.A.						

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Liquid Colour: Colourless Odour: N.A. pH: Not Relevant Kinematic viscosity: <= 20,5 mm2/sec (40 °C) Melting point / freezing point: N.A. Initial boiling point and boiling range: N.A. Flash point: < 23°C Upper/lower flammability or explosive limits: N.A. Vapour density: N.A. Vapour pressure: N.A. Relative density: 0.79 g/cm3 Solubility in water: N.A. Solubility in oil: N.A. Partition coefficient (n-octanol/water): N.A. Auto-ignition temperature: N.A. Decomposition temperature: N.A. Flammability: The product is classified Flam. Liq. 2 H225 Kinematic viscosity m2/s (40°C) $\leq 20,5 \text{ mm2/sec}$ (40 °C) Viscosity: = 26.00 s - Method: ASTM D 1200 82 - Section: 2.00 mm Particle characteristics: Particle size: N.A. 9.2. Other information Evaporation rate: N.A.

Evaporation rate: N.A. Miscibility: N.A. Conductivity: N.A. No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

	nformation on hazard cl Toxicological Informat	asses as defined	Regulation (EC) No 1272/20	008		
	a) acute toxicity	-	lot classified			
	-,,		ased on available data, the class	sification criteria are not met		
	b) skin corrosior	n/irritation	lot classified			
			Based on available data, the classification criteria are not met			
	c) serious eye da	amage/irritation	The product is classified: Eye Irrit. 2(H319)			
	d) respiratory or	skin sensitisation	lot classified			
			ased on available data, the class	sification criteria are not met		
	e) germ cell mut	tagenicity	lot classified			
			ased on available data, the class	sification criteria are not met		
	f) carcinogenicity	y	lot classified			
			ased on available data, the class	sification criteria are not met		
	g) reproductive	toxicity	Not classified			
			ased on available data, the class	sification criteria are not met		
	h) STOT-single exposurei) STOT-repeated exposurej) aspiration hazard		The product is classified: STOT SE 3(H336)			
			Not classified			
			Based on available data, the classification criteria are not met			
			he product is classified: Asp. To:	x. 1(H304)		
	Toxicological informati	ion on main com	nents of the mixture:			
	Hydrocarbons, C9-C11, n- a) acute toxicity alkanes, isoalkanes, cyclics, < 2% aromatics		LD50 Oral Rat > 5000 m	ıg/kg	OECD Test Guideline 401	
			LC50 Inhalation Rat > 50	000 mg/l 4h	OECD Test Guideline 403	
			LD50 Skin Rabbit > 500	0 mg/kg	OECD Test Guideline 402	
		f) carcinogenicity	Carcinogenicity - Not cl classified in accordance Regulation (EC) 1272/20	with Note P, Annex VI of EC		
	ethyl acetate	a) acute toxicity	LD50 Oral Rat = 5620 m	ıg/kg		
			LC50 Inhalation Rat = 5	6 mg/l 4h		
			LD50 Skin Rabbit > 180	00 mg/kg		
	propan-2-ol	a) acute toxicity	LD50 Oral Rat = 5840 m	ng/kg		
			LC50 Inhalation Rat > 10	0000 Ppm 6h		

11.2. Information on other hazards

Endocrine disrupting properties:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	, EINECS: 919- 857-5	a) Aquatic acute toxicity: LL50 Fish Oncorhynchus mykiss (rainbow trout) > 1000 mg/L 96 H
		e) Plant toxicity : NOELR Algae Pseudokirchneriella subcapitata (green algae) = 100 mg/L 72 H
		e) Plant toxicity : EL50 Algae Pseudokirchneriella subcapitata (green algae) > 1000 mg/L 72 H
		a) Aquatic acute toxicity: EL50 Invertebrates Daphnia magna Straus > 1000 mg/kg 48h
ethyl acetate	CAS: 141-78-6 - EINECS: 205- 500-4 - INDEX: 607-022-00-5	a) Aquatic acute toxicity : LC50 Fish = 230 mg/L 96 H
		a) Aquatic acute toxicity : EC50 Invertebrates Daphnia (water flea) > 2500 mg/L 24 H
		e) Plant toxicity: EC50 Algae > 100 mg/L 72 H
propan-2-ol	CAS: 67-63-0 - EINECS: 200- 661-7 - INDEX: 603-117-00-0	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (fathead minnow) = 9640 mg/L 96 H
		a) Aquatic acute toxicity : EC50 Invertebrates Daphnia magna (Water flea) > 10000 mg/L 24 H
		e) Plant toxicity: EC50 Algae Scenedesmus quadricauda (Green algae) = 1800 mg/L 7 D

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

12.6. Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT RELATED MATERIAL IATA-Shipping Name: PAINT RELATED MATERIAL IMDG-Shipping Name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR-Class: 3 IATA-Class: 3

IMDG-Class: 3 14.4. Packing group ADR-Packing Group: II IATA-Packing group: II IMDG-Packing group: II 14.5. Environmental hazards Toxic ingredients quantity: 0.00 Very toxic ingredients quantity: 0.00 Marine pollutant: No Environmental Pollutant: No IMDG-EMS: F-E, S-E 14.6. Special precautions for user Road and Rail (ADR-RID): ADR exempt: ADR-Label: 3 ADR - Hazard identification number: 33 ADR-Special Provisions: 163 367 640C 650 ADR-Transport category (Tunnel restriction code): 2 (D/E) Air (IATA): IATA-Passenger Aircraft: 353 IATA-Cargo Aircraft: 364 IATA-Label: 3 IATA-Subsidiary hazards: -IATA-Erg: 3L IATA-Special Provisions: A3 A72 A192 Sea (IMDG): IMDG-Stowage and handling: Category B IMDG-Segregation: -IMDG-Subsidiary hazards: -IMDG-Special Provisions: 163 367 14.7. Maritime transport in bulk according to IMO instruments ΝΑ

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP) Regulation (EU) n. 2021/849 (ATP 17 CLP) Regulation (EU) n. 2022/692 (ATP 18 CLP) Regulation (EU) n. 2020/878

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40 Restrictions related to the substances contained: 75

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)			
Product belongs to category: P5c	5000	50000			
Regulation (EU) No 649/2012 (PIC reg	ulation)				
	No substances listed				
German Water Hazard Class.					
2: Hazard to waters					
German Lagerklasse according to TRGS	5 510:				
LGK 3					
SVHC Substances:					
No SVHC substances present in concentration $>= 0.1\%$					
DIRECTIVE 2010/75/EU (VOC directive)					
Volatile Organic compounds - VOCs = 100.00 %					
Volatile Organic compounds - VOCs = 790.00 g/L					
Estimated Total Content of Water 0.00 %					
Estimated Total Solid Content 0.00 %					
Classification according to VbF					
Classification according to VbF A I - Flash point less than 21 °C, at 15 °C not miscible in water					
Mal-Code (Denmark)					

Mal-Code (Denmark)	Mal Factor	Unit of Measure	Revision Status / Number	Regulatory Base
1 - 3	205	m3 air/10 g	1993	Administrative determined MAL- Factors

Biocides

REGULATION (EC) No 528/2012

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description		
EUH066	Repeated exposure may cause skin dryness	s or cracking.	
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H304	May be fatal if swallowed and enters airway	/5.	
H319	Causes serious eye irritation.		
H336	May cause drowsiness or dizziness.		
Code	Hazard class and hazard category	Description	
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2	
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3	
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1	
3.3/2	Eye Irrit. 2	Eye irritation, Category 2	
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method
Asp. Tox. 1, H304	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended. This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

- AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

- BCF: Biological Concentration Factor
- BEI: Biological Exposure Index
- BOD: Biochemical Oxygen Demand
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- CAV: Poison Center
- CE: European Community
- CLP: Classification, Labeling, Packaging.
- CMR: Carcinogenic, Mutagenic and Reprotoxic
- COD: Chemical Oxygen Demand
- COV: Volatile Organic Compound
- CSA: Chemical Safety Assessment
- CSR: Chemical Safety Report
- DMEL: Derived Minimal Effect Level
- DNEL: Derived No Effect Level.
- DPD: Dangerous Preparations Directive
- DSD: Dangerous Substances Directive
- EC50: Half Maximal Effective Concentration
- ECHA: European Chemicals Agency
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ES: Exposure Scenario
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- IARC: International Agency for Research on Cancer
- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
- IC50: half maximal inhibitory concentration
- ICAO: International Civil Aviation Organization.
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
- IMDG: International Maritime Code for Dangerous Goods.
- INCI: International Nomenclature of Cosmetic Ingredients.
- IRCCS: Scientific Institute for Research, Hospitalization and Health Care
- KAFH: KAFH
- KSt: Explosion coefficient.
- LC50: Lethal concentration, for 50 percent of test population.
- LD50: Lethal dose, for 50 percent of test population.
- LDLo: Leathal Dose Low
- N.A.: Not Applicable
- N/A: Not Applicable
- N/D: Not defined/ Not available
- NA: Not available
- NIOSH: National Institute for Occupational Safety and Health
- NOAEL: No Observed Adverse Effect Level
- OSHA: Occupational Safety and Health Administration
- PBT: Persistent, Bioaccumulative and Toxic
- PGK: Packaging Instruction
- PNEC: Predicted No Effect Concentration.
- **PSG:** Passengers
- RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
- STEL: Short Term Exposure limit.
- STOT: Specific Target Organ Toxicity.
- TLV: Threshold Limiting Value.
- TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
- vPvB: Very Persistent, Very Bioaccumulative.
- WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information