# Safety Data Sheet MACROFAN UHS AIRTECH MAX HARDENER Safety Data Sheet dated 09/02/2023 version 1



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

### Mixture identification:

Trade name: MACROFAN UHS AIRTECH MAX HARDENER

Trade code: L0MH0390

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Coatings and paints, thinners, paint removers

Poliysocyanic compound - professional use

Liquid solution

Uses advised against: N.A.

# 1.3. Details of the supplier of the safety data sheet

Company: Lechler SpA - Via Cecilio, 17 - 22100 Como - CO - Italy Telephone: +39031586111

First Email: safety@lechler.eu

### 1.4. Emergency telephone number

UNITED KINGDOM: Emergency Number 0044 1606738600 - This telephone number is available during office hours only (8.45-16.45). UNITED STATES OF AMERICA: Emergency Contact: Lechler SPA -Tel. +39-031-586301 (8.00-18.00).

# **SECTION 2: Hazards identification**



2.1. Classification of the substance or mixture

# Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3	Flammable liquid and vapour.
Acute Tox. 4	Harmful if inhaled.
Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2	Causes serious eye irritation.
Skin Sens. 1	May cause an allergic skin reaction.
STOT SE 3	May cause respiratory irritation.
STOT SE 3	May cause drowsiness or dizziness.
STOT RE 2	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	May be fatal if swallowed and enters airways.
Adverse physicocher	nical, human health and environmental effects:
No other ha	nzards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

#### Hazard pictograms and Signal Word



### **Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

### **Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P331 Do NOT induce vomiting.
- P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.

### **Special Provisions:**

EUH204 Contains isocyanates. May produce an allergic reaction.

### Contains

Hexamethylene-1,6-diisocyanate Homopolymer

n-butyl acetate

xylene

2-ethoxy-1-methylethyl acetate

# Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

### 2.3. Other hazards

Results of PBT and vPvB assessment Not a PBT, vPvB substance as per the criteria of the REACH Regulation. Endocrine disrupting properties-Toxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Endocrine disrupting properties-Ecotoxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other Hazards: No other hazards

## **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

N.A.

## 3.2. Mixtures

Mixture identification: MACROFAN UHS AIRTECH MAX HARDENER

# Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name		Ident. Numb.	Classification	Registration Numb	per
≥50 - ≤55 %	Hexamethylen Homopolymer	e-1,6-diisocyanate	EC:931-297-3	Acute Tox. 4, H332; STOT SE 3, H335; Skin Sens. 1, H317	01-2119488934-20	
≥25 - ≤30 %	n-butyl acetato	e	CAS:123-86-4 EC:204-658-1 Index:607-025- 00-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	01-2119485493-29	
≥15 - ≤20 %	xylene		CAS:1330-20-7 EC:215-535-7 Index:601-022- 00-9	Flam. Liq. 3, H226; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 3, H412; STOT SE 3, H335	01-2119488216-32	
≥5 - ≤7 %	2-ethoxy-1-me	ethylethyl acetate	CAS:54839-24-6 EC:259-370-9 Index:603-177- 00-8	Flam. Liq. 3, H226; STOT SE 3, H336	01-2119475116-39	
Date (	)3/04/2025	Production Name	MACROFAN UHS	AIRTECH MAX HARDENER		Pac

# SECTION 4: First aid measures

## 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

## 4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media:

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

# 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

## 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

# 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

# 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand Wash with plenty of water.

# 6.4. Reference to other sections

# See also section 8 and 13

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# 7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

### 7.3. Specific end use(s)

Recommendation(s)

None in particular Industrial sector specific solutions:

idustrial sector specific solution

None in particular

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

### **Community Occupational Exposure Limits (OEL)**

	OEL Type	Country	Occupational Exposure Limit
Hexamethylene-1,6- diisocyanate Homopolymer	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 0.02 mg/m3 Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific
	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Short Term: 0.07 mg/m3 The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categor
n-butyl acetate CAS: 123-86-4	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 724 mg/m3 - 150 ppm; Short Term: 966 mg/m3 - 200 ppm
	EU		Long Term: 241 mg/m3 - 50 ppm; Short Term: 723 mg/m3 - 150 ppm Behaviour Indicative 2019/1831/EU
	ACGIH		Long Term: 50 ppm; Short Term: 150 ppm Eye and URT irr
xylene CAS: 1330-20-7	ACGIH		Long Term: 20 ppm A4, BEI - URT and eye irr; hematologic eff; CNS impair
	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 220 mg/m3 - 50 ppm; Short Term: 441 mg/m3 - 100 ppm Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to
	EU		Long Term: 221 mg/m3 - 50 ppm; Short Term: 442 mg/m3 - 100 ppm Behaviour Indicative 2000/39/EC

	EU	Identifies the possibility of significant uptake through the skin
Biological limit values		
xylene CAS: 1330-20-7	Biological Indicator: xylen Value: 1.5 mg/L; Medium Remark: Croatia. Biologic	e; Sampling Period: End of turn : Blood al Exposure Limits
	Biological Indicator: Meth Value: 1.5 g/l; Medium: L Remark: New Zealand. Bi	ylhippuric acid; Sampling Period: End of turn Irine ological Exposure Indices
	Biological Indicator: xylen Value: 1.5 mg/L; Medium Remark: Slovakia. Biologi	e; Sampling Period: End of turn : Blood cal Limit Values
	Biological Indicator: sum Value: 2000 mg/L; Mediu Remark: Slovakia. Biologi	of 2,3,4-methylhippuric acid; Sampling Period: End of turn m: Urine cal Limit Values
	Biological Indicator: meth Value: 3 g/l; Medium: Uri Remark: Romania. Biolog	ylhypuric acid; Sampling Period: End of turn ne ical limit values
	Biological Indicator: meth Value: 2 g/l; Medium: Uri Remark: Slovenia. BAT-va	ylhippuric acid (all isomers); Sampling Period: End of turn ne alues
	Biological Indicator: xylen Value: 1.5 mg/L; Medium Remark: TRGS 903 - Biolo	e; Sampling Period: Immediately after exposure or after working hours : Blood ogical limit values
	Biological Indicator: meth after working hours Value: 2 g/l; Medium: Uri Remark: TRGS 903 - Biolo	ylhippuric acid (all isomers); Sampling Period: Immediately after exposure or ne ogical limit values
	Biological Indicator: Meth Value: 2 mg/L; Medium: I Remark: South Africa. Ha	ylhippuric acid; Sampling Period: Last 4 hours of shift Jrine zardous Chemical Substances Regulations, Biological Exposure Indices.
	Biological Indicator: total week Value: 800 mg/L; Medium Remark: Occupational exp	(o-, m-, p-)methylhippuric acid; Sampling Period: End of turn; End of working n: Urine posure limits based on biological monitoring (JSOH).
	Biological Indicator: meth work day / at the end of a Value: 1.5 g/l; Medium: L Remark: Austria. Regulati	yl hippuric acid; Sampling Period: At the end of a work week / at the end of a a shift Jrine on on health surveillance in the workplace 2014
	Biological Indicator: xylen Value: 1 mg/L; Medium: I Remark: Austria. Regulati	e; Sampling Period: End of workday Blood on on health surveillance in the workplace 2014
	Biological Indicator: Meth Value: 2 mg/L; Medium: I Remark: Kenya. Occupati Limits	ylhippuric acid; Sampling Period: At the end of exposure, in 4 hours Jrine onal Safety and Health Act (CAP.514), Schedule I, Table 3 Biological Exposure
	Biological Indicator: meth Value: 5 Millimoles per lite Remark: Finland. Biologic	yl hippuric acid; Sampling Period: After shift er; Medium: Urine al limit values
	Biological Indicator: meth hours Value: 2 g/l; Medium: Uri Remark: Svizzera. Lista d	yl hippuric acid; Sampling Period: Immediately after exposure or after working ne i valori BAT

# Predicted No Effect Concentration (PNEC) values

Hexamethylene-1,6- diisocyanate	Exposure Route: Fresh Water; PNEC Limit: 0.1 mg/l
Homopolymer	Exposure Pouto: Freshwater sodiments: DNEC Limit: 2530 mg/kg.dn/ weight

Exposure Route: Freshwater sediments; PNEC Limit: 2530 mg/kg dry weight (d.w.) Exposure Route: Marine water; PNEC Limit: 0.01 mg/l Exposure Route: Marine water sediments; PNEC Limit: 253 mg/kg dry weight (d.w.)

	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l
	Exposure Route: Soil; PNEC Limit: 505 mg/kg dry weight (d.w.)
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 1 mg/l
n-butyl acetate CAS: 123-86-4	Exposure Route: Fresh Water; PNEC Limit: 0.18 mg/l
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.36 mg/l
	Exposure Route: Marine water; PNEC Limit: 0.01 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 0.98 mg/kg
	Exposure Route: Marine water sediments; PNEC Limit: 0.09 mg/kg
	Exposure Route: Soil; PNEC Limit: 0.09 mg/kg
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 35.6 mg/l
xylene CAS: 1330-20-7	Exposure Route: Fresh Water; PNEC Limit: 0.32 mg/l
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.32 mg/l
	Exposure Route: Marine water; PNEC Limit: 0.32 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 12.46 mg/kg
	Exposure Route: Marine water sediments; PNEC Limit: 12.46 mg/kg
	Exposure Route: Soil; PNEC Limit: 2.31 mg/kg
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.58 mg/l
2-ethoxy-1-methylethyl acetate CAS: 54839-24-6	Exposure Route: Fresh Water; PNEC Limit: 2 mg/l
	Exposure Route: Marine water: PNEC Limit: 0.2 mg/l
	Exposure Route: Intermittent releases (fresh water): PNEC Limit: 2 mg/l
	Exposure Route: Freshwater sediments: PNEC Limit: 8.2 mg/l
	Exposure Route: Marine water sediments: PNEC   imit: 0.67 mg/l
	Exposure Route: Microorganisms in sewage treatments: PNFC Limit: 62.5 mg/l
	Exposure Route: Oral: PNEC Limit: 117 mg/l
Derived No Effect Level	Exposure Route: Oral; PNEC Limit: 117 mg/l
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 600 mg/m3
<b>Derived No Effect Level</b> Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 600 mg/m3
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 300 mg/m3
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.)
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.)
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Consumer: 35.7 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Consumer: 35.7 mg/m3
Derived No Effect Level Hexamethylene-1,6- diisocyanate Homopolymer n-butyl acetate CAS: 123-86-4	Exposure Route: Oral; PNEC Limit: 117 mg/l (DNEL) values Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Professional: 0.5 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 1 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 600 mg/m3 Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 11 mg/kg dry weight (d.w.) Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Consumer: 35.7 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Consumer: 300 mg/m3 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Consumer: 300 mg/m3

	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Consumer: 6 mg/kg dry weight (d.w.)
	Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects Consumer: 6 mg/kg dry weight (d.w.)
	Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects Consumer: 2 mg/kg dry weight (d.w.)
	Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects Consumer: 2 mg/kg dry weight (d.w.)
xylene CAS: 1330-20-7	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Consumer: 65.3 mg/m3
	Exposure Route: Oral; Exposure Frequency: Long Term, systemic effects Consumer: 12.5 mg/kg
	Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Professional: 442 mg/kg
	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Professional: 212 mg/kg
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Professional: 221 mg/m3
2-ethoxy-1-methylethyl acetate CAS: 54839-24-6	Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 2366 mg/m3; Worker Professional: 2366 mg/kg; Consumer: 1420 mg/m3
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 152 mg/m3; Worker Professional: 152 mg/m3; Consumer: 181 mg/m3
	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 103 mg/kg; Worker Professional: 103 mg/kg; Consumer: 62 mg/kg
	Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects Consumer: 13.1 mg/kg
8.2. Exposure controls	
Eye protection:	
Use close fitting	safety goggles, don't use eye lens.
Protection for skin:	
Use clothing that	t provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
Protection for hands:	· · · · · ·
Use protective g	loves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards: N.A. Environmental exposure controls: N.A.

Hygienic and Technical measures N.A.

# SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties Physical State: Liquid Colour: Colourless Odour: N.A. pH: Not Relevant Kinematic viscosity: <= 14 mm2/sec (40 °C) Melting point / freezing point: N.A. Initial boiling point and boiling range: N.A. Flash point: 23°C / 60°C Upper/lower flammability or explosive limits: N.A. Vapour density: N.A. Vapour pressure: N.A. Relative density: 1.01 g/cm3 Solubility in water: N.A. Solubility in oil: N.A. Partition coefficient (n-octanol/water): N.A. Auto-ignition temperature: N.A. Decomposition temperature: N.A. Flammability: The product is classified Flam. Liq. 3 H226 Kinematic viscosity m2/s (40°C) <= 14 mm2/sec (40 °C) Viscosity: = 17.00 s - Method: ASTM D 1200 82 - Section: 3.00 mm Particle characteristics: Particle size: N.A.

# 9.2. Other information

Evaporation rate: N.A. Miscibility: N.A. Conductivity: N.A. No other relevant information

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Stable under normal conditions

# 10.2. Chemical stability

Data not available.

# 10.3. Possibility of hazardous reactions

None.

# 10.4. Conditions to avoid

Stable under normal conditions.

# **10.5.** Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

### 10.6. Hazardous decomposition products

None.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Toxicological Information of the Preparation

a) acute toxicity			The product is classified: Acute Tox. 4(H332) ATEmix - Dermal : 7105.94 mg/kg bw			
			ATEmix - Inhalation (Vapours): 16.5112 mg/l			
	b) skin corrosion/	'irritation	The product is classified: Skin Irrit. 2(H315)			
	c) serious eye da	mage/irritation	The product is classified: Eye Irrit. 2(H319)			
	d) respiratory or	skin sensitisation	The product is classified: Skin Sens. 1(H317) Not classified			
	e) germ cell muta	agenicity				
			Based on available data, the classification criteria are not met Not classified			
	f) carcinogenicity					
			Based on available data, the classification criteria are not met			
	g) reproductive to	oxicity	Not classified			
			Based on available data, the classification criteria are not met			
	h) STOT-single ex	xposure	The product is classified: STOT SE 3(H335), STOT SE 3(H336) The product is classified: STOT RE 2(H373)			
	i) STOT-repeated	exposure				
j) aspiration hazard		ird	The product is classified: Asp. Tox. 1(H304)			
Toxicolo	gical informatio	on on main com	ponents of the mixture:			
Hexamethylene-1,6- a) acute toxicity diisocyanate Homopolymer		a) acute toxicity	LD50 Oral Rat > 2000 mg/kg	OECD Test Guideline 423		
			LD50 Skin Rat > 2000 mg/kg	OECD Test Guideline 402		
			LC50 Inhalation Rat = 0.39 mg/l 4h	OECD Test Guideline 403		
n-butyl a	cetate	a) acute toxicity	LD50 Oral Rat = 10760 mg/kg	OECD Test Guideline 423		
			LC50 Inhalation > 20 mg/l 4h			
			LD50 Skin Rabbit > 14112 mg/kg	OECD Test Guideline 402		

xylene	a) acute toxicity	LD50 Oral Mouse = 5627 mg/kg LC50 Inhalation Rat = 6700 Ppm 4h LD50 Skin Rabbit > 5000 mg/kg	
2-ethoxy-1-methylethyl acetate	a) acute toxicity	LD50 Oral Rat > 5000	OECD Test Guideline 401
		LC50 Inhalation Mist Rat > 6.99 4h	OECD Test Guideline 403

### 11.2. Information on other hazards

## Endocrine disrupting properties:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

# List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

## List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Hexamethylene-1,6-diisocyanate Homopolymer	EINECS: 931- 297-3	a) Aquatic acute toxicity : LC50 Fish Danio rerio (zebra fish) > 100 mg/L 96 H - ,,Directive 67/548/EEC, Annex V, C.1.
		a) Aquatic acute toxicity: EC50 Invertebrates Daphnia magna (Water flea) > 100 mg/L 48h
n-butyl acetate	CAS: 123-86-4 - EINECS: 204- 658-1 - INDEX: 607-025-00-1	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (fathead minnow) = 18 mg/L 96 H OECD Test Guideline 203
		a) Aquatic acute toxicity: EC50 Invertebrates Daphnia magna (Water flea) = 44 mg/L 48 H OECD Test Guideline 202
		e) Plant toxicity : EC50 Algae Selenastrum capricornutum (green algae) = 397 mg/L 72 H OECD Test Guideline 201
		c) Bacteria toxicity : IC50 Microorganisms Tetrahymena pyriformis = 356 mg/L 40 H
xylene	CAS: 1330-20-7 - EINECS: 215- 535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss (rainbow trout) = 2.6 mg/L 96 H
		a) Aquatic acute toxicity : IC50 Invertebrates Daphnia magna (Water flea) = 1 mg/L 24 H
		e) Plant toxicity : EC0 Algae Pseudokirchneriella subcapitata (green algae) = $0.44 \text{ mg/L} 72 \text{ H}$
		<ul> <li>b) Aquatic chronic toxicity : NOEC Fish Oncorhynchus mykiss (rainbow trout)</li> <li>&gt; 1.3 mg/L 56 D</li> </ul>
		e) Plant toxicity : Algae Pseudokirchneriella subcapitata (green algae) = $4.36$ mg/L 72 H
2-ethoxy-1-methylethyl acetate	CAS: 54839-24- 6 - EINECS: 259-370-9 - INDEX: 603- 177-00-8	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss (rainbow trout) = 140 mg/L 96 H OECD Test Guideline 203
		a) Aquatic acute toxicity: EC50 Invertebrates Daphnia magna (Water flea) = 110 mg/L 48 H OECD Test Guideline 202

e) Plant toxicity : EC50 Algae Desmodesmus subspicatus (green algae) > 100 mg/L 72 H OECD Test Guideline 201

c) Bacteria toxicity : EC10 Microorganisms Pseudomonas putida = 560 mg/L 16 H  $\,$ 

b) Aquatic chronic toxicity : NOEC Invertebrates Daphnia magna (Water flea) >= 100 mg/L 21 D

a) Aquatic acute toxicity : NOEC Fish Oryzias latipes (Orange-red killifish) = 47.5 mg/L 96 H

e) Plant toxicity : NOEC Algae Desmodesmus subspicatus (green algae) >= 100 mg/L 72 H

# 12.2. Persistence and degradability

N.A.

# 12.3. Bioaccumulative potential

N.A.

# 12.4. Mobility in soil

N.A.

## 12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

# **12.6. Endocrine disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7. Other adverse effects

N.A.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

# **SECTION 14: Transport information**

### 14.1. UN number or ID number

1263

# 14.2. UN proper shipping name

ADR-Shipping Name: PAINT RELATED MATERIAL IATA-Shipping Name: PAINT RELATED MATERIAL IMDG-Shipping Name: PAINT RELATED MATERIAL

# 14.3. Transport hazard class(es)

ADR-Class: 3 IATA-Class: 3 IMDG-Class: 3

## 14.4. Packing group

ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

# 14.5. Environmental hazards

Toxic ingredients quantity: 0.00 Very toxic ingredients quantity: 0.00 Marine pollutant: No Environmental Pollutant: No IMDG-EMS: F-E, S-E

#### 14.6. Special precautions for user

Road and Rail (ADR-RID): ADR exempt: ADR-Label: 3 ADR - Hazard identification number: -ADR-Special Provisions: 163 367 650 ADR-Transport category (Tunnel restriction code): 3 (E) Air (IATA): IATA-Passenger Aircraft: 355 IATA-Cargo Aircraft: 366 IATA-Label: 3 IATA-Subsidiary hazards: -IATA-Erg: 3L IATA-Special Provisions: A3 A72 A192 Sea (IMDG): IMDG-Stowage and handling: Category A IMDG-Segregation: -IMDG-Subsidiary hazards: -IMDG-Subsidiary hazards: -IMDG-Special Provisions: 163 223 367 955 **14.7. Maritime transport in bulk according to IMO instruments** N.A.

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP) Regulation (EU) n. 2021/849 (ATP 17 CLP) Regulation (EU) n. 2020/878 Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product: 3, 40 Restrictions related to the substances contained: 74, 75 Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according Lower-tier threshold (tonnes) Upper-tier threshold (tonnes) to Annex 1, part 1 50000 Product belongs to category: P5c 5000 Regulation (EU) No 649/2012 (PIC regulation) No substances listed German Water Hazard Class. 3: Severe hazard to waters SVHC Substances: No data available DIRECTIVE 2010/75/EU (VOC directive)

Volatile Organic compounds - VOCs = 48.21 % Volatile Organic compounds - VOCs = 486.88 g/L Estimated Total Content of Water 0.00 % Estimated Total Solid Content 51.79 %

Biocides

REGULATION (EC) No 528/2012

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

### **SECTION 16: Other information**

Code	Description		
EUH066	Repeated exposure may cause skin dryness or cracking.		
H226	Flammable liquid and vapour.		
H304	May be fatal if swallowed and enters airw	ays.	
H312	Harmful in contact with skin.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H373	May cause damage to organs through prolonged or repeated exposure.		
H412	Harmful to aquatic life with long lasting effects.		
Code	Hazard class and hazard category	Description	
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3	
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4	
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4	
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1	
3.2/2	Skin Irrit. 2	Skin irritation, Category 2	
3.3/2	Eye Irrit. 2	Eye irritation, Category 2	
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1	
3.8/3	STOT SE 3	Specific target organ toxicity $-$ single exposure, Category 3	
3.9/2	STOT RE 2	Specific target organ toxicity $-$ repeated exposure, Category 2	
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
2.6/3	On basis of test data
3.1/4/Inhal	Calculation method
3.2/2	Calculation method
3.3/2	Calculation method
3.4.2/1	Calculation method
3.8/3	Calculation method
3.8/3	Calculation method
3.9/2	Calculation method
3.10/1	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor **BEI:** Biological Exposure Index BOD: Biochemical Oxygen Demand CAS: Chemical Abstracts Service (division of the American Chemical Society). CAV: Poison Center CE: European Community CLP: Classification, Labeling, Packaging. CMR: Carcinogenic, Mutagenic and Reprotoxic COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment CSR: Chemical Safety Report DMEL: Derived Minimal Effect Level DNEL: Derived No Effect Level. DPD: Dangerous Preparations Directive DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration ECHA: European Chemicals Agency EINECS: European Inventory of Existing Commercial Chemical Substances. ES: Exposure Scenario GefStoffVO: Ordinance on Hazardous Substances, Germany. GHS: Globally Harmonized System of Classification and Labeling of Chemicals. IARC: International Agency for Research on Cancer IATA: International Air Transport Association. IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA). IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization. ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO). IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients. IRCCS: Scientific Institute for Research, Hospitalization and Health Care KAFH: KAFH KSt: Explosion coefficient. LC50: Lethal concentration, for 50 percent of test population. LD50: Lethal dose, for 50 percent of test population. LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable N/D: Not defined/ Not available NA: Not available NIOSH: National Institute for Occupational Safety and Health NOAEL: No Observed Adverse Effect Level OSHA: Occupational Safety and Health Administration PBT: Persistent, Bioaccumulative and Toxic PGK: Packaging Instruction PNEC: Predicted No Effect Concentration. **PSG:** Passengers RID: Regulation Concerning the International Transport of Dangerous Goods by Rail. STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. TLV: Threshold Limiting Value. TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard). vPvB: Very Persistent, Very Bioaccumulative. WGK: German Water Hazard Class.