Trade name :

Revision date : Print date :

SWIN 70-102-6 Plastic cleaner 16.05.2023 04.07.2023

Version (Revision) :

3.2.0 (3.1.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SWIN 70-102-6 Plastic cleaner (34611) PROPAN-2-OL ; CAS No. : 67-63-0 ; EC No. : 200-661-7 ; Index No. : 603-117-00-0 ; REACH No. : 01-2119457558-25

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Washing and cleaning products

1.3 Details of the supplier of the safety data sheet

Supplier

SWIN Lacksysteme Inh. Ludwig Schöne e.K

Street : Boschweg 5

Postal code/City: 48351 Everswinkel

Telephone : +49(0)2582/67613

Telefax: +49(0)258267677

Information contact : info@swinsysteme.de

1.4 Emergency telephone number

Poison Information Center Göttingen (GIZ-Nord) Phone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2; H225 - Flammable liquids : Category 2; Highly flammable liquid and vapour. Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation. STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Exclamation mark (GHS07)

Signal word Danger Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eve irritation. H336 May cause drowsiness or dizziness. **Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P370+P378 In case of fire: Use foam to extinguish.

Trade name :	SWIN 70-102-6 Plastic cleaner		
Revision date :	16.05.2023	Version (Revision) :	3.2.0 (3.1.0)
Print date :	04.07.2023		

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to disposal.

2.3 Other hazards

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : PROPAN-2-OL Index No. : 603-117-00-0 EC No. : 200-661-7 REACH No. : 01-2119457558-25 CAS No. : 67-63-0 Purity : 100 % [mass]

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

Following inhalation

Inhalation of vapours or spray/mists

Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Provide fresh air.

In case of skin contact After contact with skin, wash immediately with plenty of water and soap.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed Dizziness Headache Nausea Impairment of vision Vomiting

4.3 Indication of any immediate medical attention and special treatment needed None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

Trade name :	SWIN 70-102-6 Plastic cleaner		
Revision date :	16.05.2023	Version (Revision) :	3.2.0 (3.1.0)
Print date :	04.07.2023		

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic Carbon monoxide Carbon dioxide (CO2)

5.3 Advice for firefighters

Do not inhale explosion and combustion gases. Special protective equipment for firefighters Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

For non-emergency personnel

Use personal protection equipment. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

For emergency responders

Use appropriate respiratory protection. Remove persons to safety. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

6.4 Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment (refer to section 8). Avoid: generation/formation of aerosols

It is recommended to design all work processes always so that the following is excluded: Inhalation Skin contact Eye contact

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Take precautionary measures against static discharges.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Usual measures for fire prevention. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of heat (e.g. hot surfaces), sparks

Trade name :	SWIN 70-102-6 Plastic cleaner		
Revision date :	16.05.2023	Version (Revision) :	3.2.0 (3.1.0)
Print date :	04.07.2023		

and open flames. Provide earthing of containers, equipment, pumps and ventilation facilities. Use only antistatically equipped (spark-free) tools. Wear anti-static footwear and clothing Take precautionary measures against static discharges.

Measures to prevent aerosol and dust generation

Vapours/aerosols must be exhausted directly at the point of origin. Use only in well-ventilated areas. **Environmental precautions**

Shafts and sewers must be protected from entry of the product.

7.2 Conditions for safe storage, including any incompatibilities Hints on joint storage

Storage class (TRGS 510): 3

Further information on storage conditions

Keep container tightly closed. Keep/Store only in original container.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

Occupational exposure lim	nit values
PROPAN-2-OL ; CAS No. : 67-63-0	
Limit value type (country of origin) :	TRGS 900 (D)
Limit value :	200 ppm / 500 mg/m ³
Peak limitation :	2(II)
Remark :	Y
Version :	23.06.2022
Biological limit values	
PROPAN-2-OL ; CAS No. : 67-63-0	
Limit value type (country of origin) :	TRGS 903 (D)
Parameter :	Acetone / Whole blood (B) / End of exposure or end o
Limit value :	25 mg/l
Version :	25.02.2022
Limit value type (country of origin) :	TRGS 903 (D)
Parameter :	Acetone / Urine (U) / End of exposure or end of shift
Limit value :	25 mg/l
Version :	25.02.2022
DNEL-/PNEC-values	
DNEL/DMEL	
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Limit value :	888 mg/kg bw/day
Limit value type :	DNEL worker (systemic)

Inhalation

500 mg/m³

Limit value : PNEC

Exposure route :

PNEC	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	140,9 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	140,9 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	552 mg/kg
Limit value type :	PNEC (Sediment, marine water)
Limit value :	552 mg/kg

Page : 4 / 10

of shift

Trade name :

Revision date : Print date :

SWIN 70-102-6 Plastic cleaner 16.05.2023 04.07.2023

Version (Revision) :

3.2.0 (3.1.0)

Limit value type : Limit value : Limit value type : Limit value :

PNEC (Soil) 28 mg/kg PNEC (Sewage treatment plant) 2251 mg/l

8.2 Exposure controls



Personal protection equipment

Eye/face protection

Eye glasses with side protection

Skin protection

Hand protection

Suitable material : Butyl caoutchouc (butyl rubber) Thickness of the glove material : 0.7 mm Breakthrough time: 480 min Recommended glove articles EN ISO 374

Remark : Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Overall

Suitable protective clothing : For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes). Chemical resistant safety shoes Only wear fitting, comfortable and clean protective clothing.

Required properties : antistatic. flame-resistant heat-resistant

Respiratory protection

Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection necessary at: exceeding exposure limit values aerosol or mist formation. spray application

Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter: Filter type: A2P2

General information

Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state :	Liquid				
Odour :	characteri	stic			
Appearance					
Colour : colourless					
Safety character	istics				
Melting point/freezing	g point :		approx.	-89	°C
Initial boiling point an range :	nd boiling	(1013 hPa)	approx.	82	°C
Decomposition tempe	erature :			No data available	

Page : 5 / 10

Trade name : Revision date : Print date :	SWIN 70-102-6 Plastic cleaner 16.05.2023 04.07.2023		Version (Rev	ision) :	3.2.0 (3.1.0)
Flash point :		approx.	12	°C	DIN 51755 part 1
Auto-ignition tem	perature :	approx.	399 - 455	°C	DIN 51794
Lower explosion l	imit :		2	Vol-%	
Upper explosion li	mit :		12	Vol-%	
Vapour pressure :	(20 °C)	approx.	48	hPa	
Density :	(20 °C)	approx.	0,79	g/cm ³	DIN 51757
Water solubility :	(20 °C)		miscible		
pH-value:	(20 °C)		not applicable		
Partition coefficie octanol/water :	nt n-		No data available		
Viscosity :	(20 °C)		2,43	mPa*s	
Odour threshold :			No data available		
Relative vapour de	ensity: (20 °C)		No data available		
Vapourisation rate	e :		No data available		
Maximum VOC co	ntent (EC) :		100	Weight-%	1999/13/EC

Not fulfilling criteria for hazard class "Flammable Solids".

100 Weight-% 1999/13/EC 785 g/l 2004/42/EC

Oxidising liquids : Explosive properties :

Flammable solids :

Flammable gases :

9.2 Other information

VOC-value :

None

SECTION 10: Stability and reactivity

10.1 Reactivity

Information is given in subsection 10.3.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

In use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Not applicable.

GHS/CLP criteria are not met. GHS/CLP criteria are not met.

10.5 Incompatible materials

Exothermic reaction with:

Acid , Oxidising agent, strong.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity

ļ

Parameter :	LD50
Exposure route :	Oral
Species :	Rat
Effective dose :	5840 mg/kg
Method :	OECD 401
Acute dermal toxicity	
Parameter :	LD50
Exposure route :	Dermal

Page: 6 / 10

Trade name :

Revision date : Print date :

SWIN 70-102-6 Plastic cleaner 16.05.2023 04.07.2023

Version (Revision) :

3.2.0 (3.1.0)

Species : Rabbit Effective dose : > 13400 mg/kg Method : OECD 402 Acute inhalation toxicity Parameter : LC50 Exposure route : Inhalation (vapour) Species : Rat > 20 mg/l Effective dose : Exposure time : 6 h Method : OECD 403 Corrosive/irritant effect on skin/eyes Skin corrosion/irritation

Based on available data, the classification criteria are not met. Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Based on available data, the classification criteria are not met.

Acute (short-term) fish toxicity Parameter :

Species : Evaluation parameter : Effective dose : Exposure time : Method : Parameter : Species : Evaluation parameter : Effective dose : Exposure time : Method :

LC50 Pimephales promelas (fathead minnow) Acute (short-term) fish toxicity 9640 mg/l 96 h OFCD 203 LC50 Daphnia magna (Big water flea) Acute (short-term) toxicity to crustacea > 10000 mg/l 24 h **OECD 202**

Page : 7 / 10

Trade name :

Revision date : Print date : SWIN 70-102-6 Plastic cleaner 16.05.2023 04.07.2023

Version (Revision) :

3.2.0 (3.1.0)

Acute (short-term) toxicity to algae and cyanobacteria Parameter : EC50 Species : Scenedesmus subspicatus Evaluation parameter : Acute (short-term) algae toxicity Effective dose : > 100 mg/l Exposure time : 72 h 12.2 Persistence and degradability Biodegradation Parameter : DOC reduction Degree of elimination Inoculum : Evaluation parameter : Aerobic 53 % Degradation rate : Test duration : 5 D 12.3 Bioaccumulative potential No information available. 12.4 Mobility in soil No information available. 12.5 Results of PBT and vPvB assessment This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII. 12.6 Endocrine disrupting properties No information available. 12.7 Other adverse effects No information available. **SECTION 13: Disposal considerations** 13.1 Waste treatment methods Dispose according to legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information

14.1 UN number or ID number

UN 1219 14.2 UN proper shipping name Land transport (ADR/RID) ISOPROPANOL Sea transport (IMDG) ISOPROPANOL Air transport (ICAO-TI / IATA-DGR) ISOPROPANOL 14.3 Transport hazard class(es) Land transport (ADR/RID) Class(es): 3 **Classification code :** F1 Hazard identification number (Kemler 33 No.): Tunnel restriction code : D/E **Special Provisions :** LQ1I·E2 Hazard label(s) : 3

Trade name :	SWIN 70-102-6 Plastic cleaner		
Revision date :	16.05.2023	Version (Revision) :	3.2.0 (3.1.0)
Print date :	04.07.2023		

Sea transport (IMDG)	
Class(es) :	3
EmS-No. :	F-E / S-D
Special Provisions :	LQ 1 I · E 2
Hazard label(s) :	3
Air transport (ICAO-TI / IATA-DGR)	
Class(es) :	3
Special Provisions :	E 2
Hazard label(s) :	3
14.4 Packing group	
II	
14.5 Environmental hazards	

- Land transport (ADR/RID): No Sea transport (IMDG): No Air transport (ICAO-TI / IATA-DGR): No
- 14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 3, 40, 75

Other regulations (EU)

Restrictions of use in accordance with regulation (EC) 2019/1148 on the marketing and use of explosives precursors

None

Labelling for contents according to regulation (EC) No. 648/2004

None

National regulations Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

No allocation to the classes I, II and III.

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

15.2 Chemical Safety Assessment

For this substance / mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

None

Trade name :	SWIN 70-102-6 Plastic cleaner		
Revision date :	16.05.2023	Version (Revision) :	3.2.0 (3.1.0)
Print date :	04.07.2023		

16.2 Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route AGW = Occupational Exposure Limits ATE = Acute Toxicity Estimates AwSV = Ordinance on facilities for the handling of substances hazardous to water DMEL = Derived Minimal Effect Levels DNEL = Derived No Effect Level ECx = effective concentrationH (8.1) = skin resorptive / risk of skin absorption IATA = International Air Transport Association ICAO = International Civil Aviation Organization IMDG = International Maritime Code for Dangerous Goods LCx/LDx/LLx = Lethal Concentration/Dose/Loading for x % of a population of test organisms MARPOL = International Convention for the Prevention of Marine Pollution from Ships NOAEC/NOAEL = No Observed Adverse Effect Concentration/Level NOEC/NOEL = No Observed Effect Concentration/Level OECD = Organisation for Economic Co-operation and Development PBT = Persistent, bioaccumulative and toxic PNEC = Predicted No Effect Concentration RID = Règlement concernant le transport international ferroviaire des marchandises dangereuses RCP = reciprocal calculation procedure S(a/h/ah) (8.1) = risk of sensitisation (of the respiratory tract/of the skin/of the respiratory tract and the skin) SVHC = Substances of Very high Concern STEL = Short-Time-Exposure Limit TRGS = Technical rules for hazardous substances TWA = Time Weighted Average VOC = volatile organic compounds vPvB = very persistent and very bioaccumulative VwVwS = Administrative regulation of substances hazardous to water WGK = water hazard class acc. ordinance on facilities for handling substances that are hazardous to water (AwSV) Y (8.1) = No risk of fetal damage will have to be feared, if the occupational exposure limit values (AGW) and the biological limit values (BGW) are observed. Z (8.1) = The risk of fetal damage must be feared, even if the occupational exposure limit values (AGW) and the biological limit values (BGW) are observed. 16.3 Key literature references and sources for data None 16.4 Relevant H- and EUH-phrases (Number and full text) H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

16.5 Training advice

None

16.6 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.