

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 18 (replaces version 17) Printing date 03.06.2022 Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML
- · Article number: 000784
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category Flux agents for casting
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Preparation
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

- *Formerly known as Motip Dupli B.V.
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



H315 Causes skin irritation. Skin Irrit. 2

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 03.06.2022 Version number 18 (replaces version 17) Revision: 30.03.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

 $Hydrocarbons,\ C6-C7,\ n\hbox{-}alkanes,\ isoalkanes,\ cyclics,\ <5\%\ n\hbox{-}hexane$ pentane

propan-2-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|---|--|-----------|
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21 | propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | _ 20-<25% |
| EC number: 921-024-6 Reg.nr.: 01-2119475514-35 | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 | 12.5-<20% |
| CAS: 109-66-0 EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30 | pentane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 EUH066 | 12.5-<20% |

(Contd. on page 3)

Printing date 03.06.2022 Version number 18 (replaces version 17) Revision: 30.03.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

| CAS: 106-97-8 | butane (containing < 0,1 % butadiene (203-450-8)) | 12.5-<20% |
|---|---|-----------|
| EINECS: 203-448-7 Index number: 601-004-00-0 | Flam. Gas 1A, H220 | |
| Reg.nr.: 01-2119474691-32 | Fress. Gas (Comp.), H280 | |
| CAS: 75-28-5 | isobutane (containing < 0,1 % butadiene (203-450-8)) | 12.5-<20% |
| EINECS: 200-857-2 | 🅸 Flam. Gas 1A, H220 | |
| | Press. Gas (Comp.), H280 | |
| Reg.nr.: 01-2119485395-27 | | |
| EC number: 918-481-9 Reg.nr.: 01-2119457273-39 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 5-<10% |
| | ♦ Asp. Tox. 1, H304 EUH066 | |
| CAS: 67-63-0 | propan-2-ol | 2.5-<5% |
| EINECS: 200-661-7 | 🚸 Flam. Liq. 2, H225 | _ |
| | ♦ Eye Irrit. 2, H319; STOT SE 3, H336 | |
| Reg.nr.: 01-2119457558-25 | | |

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 03.06.2022 *Version number 18 (replaces version 17)* Revision: 30.03.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- \cdot 7.3 *Specific end use*(s) *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



(Contd. on page 5)

Printing date 03.06.2022 Version number 18 (replaces version 17) Revision: 30.03.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

(Contd. of page 4)

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Colourless
Fruit-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

• Lower: 0.6 Vol %
• Upper: 10.9 Vol %

Flash point: Not applicable, as aerosol.
 Ignition temperature: >200 °C (>392 °F)
 Decomposition temperature: Not determined.

• pH Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg)

· Density and/or relative density

Density at 20 °C (68 °F):
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

• Explosive properties: Not determined.

· Solvent content:

• Organic solvents: 95.8 % • VOC (EC) --- 613.1 g/l

(Contd. on page 6)

Printing date 03.06.2022 Version number 18 (replaces version 17) Revision: 30.03.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

| | (Contd. of page |
|--|---|
| VOC-EU% | 95.80 % |
| Solids content: | 0.2 % |
| Change in condition | |
| Evaporation rate | Not applicable. |
| Information with regard to physical hazard | classes |
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Extremely flammable aerosol. Pressurised container: |
| | May burst if heated. |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Void |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit flamm | able |
| gases in contact with water | Void |
| Oxidising liquids | Void |
| Oxidising solids | Void |
| Organic peroxides | Void |
| Corrosive to metals | Void |
| Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

| | | ant for classification: 7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | |
|------------|------------|--|-------------|
| | - | | |
| Oral | LD50 | >5840 mg/kg (rat) | |
| Dermal | LD50 | >2920 mg/kg (rab) | |
| Inhalative | LC50/4h | >25.2 mg/l (rat) | |
| 109-66-0 p | entane | | |
| Oral | LD50 | >5000 mg/kg (rat) | |
| Inhalative | LC50/4h | 25.3 mg/l (rat) | |
| Hydrocarb | ons, C10-C | 13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | |
| Oral | LD50 | >5000 mg/kg (rat) | |
| Dermal | LD50 | >3000 mg/kg (rab) | |
| Inhalative | LC50/4 h | >4951 mg/m3 (rat) | |
| | | (Cor | ntd. on pag |

– GF

Printing date 03.06.2022 Version number 18 (replaces version 17) Revision: 30.03.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

(Contd. of page 6)

| 67-63-0 pr | 67-63-0 propan-2-ol | | conta. or page of |
|------------|---------------------|----------------------|-------------------|
| Oral | LD50 | 5840 mg/kg (rat) | |
| Dermal | LD50 | 13900 mg/kg (rabbit) | |
| Inhalative | LC50 | >25 mg/l (rat) | |
| | | LC 50: 6h | |

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

| 12.1 1021011 | 1211 1000009 | | |
|----------------|---|--|--|
| · Aquatic toxi | · Aquatic toxicity: | | |
| Hydrocarbo | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | | |
| EC50 / 48 h | EC50 / 48 h 3 mg/l (daphnia magna) | | |
| EC50 / 72 h | 30-100 mg/l (algae) | | |
| LC50 / 96 h | LC50 / 96 h 11.4 mg/l (fish) | | |
| 109-66-0 рег | 109-66-0 pentane | | |
| EC50 / 48 h | 9.7 mg/l (daphnia magna) | | |
| EC50 / 96 h | 4.26 mg/l (fish) | | |
| LC50 / 96 h | 4.26 mg/l (fish) | | |
| 67-63-0 proj | 67-63-0 propan-2-ol | | |
| LC50/96h | 9640 mg/l (pimephales promelas; 96h) | | |
| LC50 / 24 h | 9714 mg/l (daphnia magna) | | |

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Version number 18 (replaces version 17) Revision: 30.03.2022 Printing date 03.06.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

(Contd. of page 7)

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

| SECTION 14: Transport information | |
|---|---|
| · 14.1 UN number or ID number · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOU. AEROSOLS, MARINE POLLUTANT AEROSOLS, flammable |
| 14.3 Transport hazard class(es) | |
| ADR | |
| | |
| Class | 2 5F Gases. |
| · Label · IMDG | 2.1 |
| | 216 |
| Class Label | 2.1 Gases. 2.1 |
| · IATA | 2,1 |
| · Class | 2.1 Gases. |
| · Label | 2.1 |
| 14.4 Packing group ADR, IMDG, IATA | not regulated |
| 14.5 Environmental hazards: Marine pollutant: Special marking (ADR): | Symbol (fish and tree) Symbol (fish and tree) |
| · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Code | Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity about 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: |
| | Segregation as for class 9. Stow "separated from" class except for division 1.4. (Contd. on page |

(Contd. on page 9)

Printing date 03.06.2022 Version number 18 (replaces version 17) Revision: 30.03.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

| | (Contd. of page |
|---|---|
| | For AEROSOLS with a capacity above 1 litre: |
| | Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS: |
| | Segregation as for the appropriate subdivision of class 2 |
| · 14.7 Maritime transport in bulk accordi | ing to IMO |
| instruments | Not applicable. |
| · Transport/Additional information: | |
| · <i>ADR</i> | |
| · Limited quantities (LQ) | IL |
| Excepted quantities (EQ) | Code: E0 |
| ~ | Not permitted as Excepted Quantity |
| Transport category | 2 |
| · Tunnel restriction code | D |
| · IMDG | |
| · Limited quantities (LQ) | IL |
| Excepted quantities (\widetilde{EQ}) | Code: E0 |
| ~ | Not permitted as Excepted Quantity |
| | Code: E0 |
| | Not permitted as Excepted Quantity |
| · UN ''Model Regulation'': | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY |
| | HAZARDOUS |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 10)

Printing date 03.06.2022 Version number 18 (replaces version 17) Revision: 30.03.2022

Trade name: MOTIP CAR CARE COCKPITSPRAY 'APPLE' 600 ML

(Contd. of page 9)

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

GB