

Version number 3 (replaces version 2)

Revision: 15.02.2024

1 Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier CODE 3003 · Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER · Article number: 20-199-1 · UFI: 3110-802C-500K-SH1X 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites • Product category PC9a Coatings and paints, thinners, paint removers · Process category PROC11 Non industrial spraying PROC7 Industrial spraying • Environmental release category ERC8c Widespread use leading to inclusion into/onto article (indoor) · Application of the substance / the mixture Coating material · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Swin Lacksysteme GmbH Boschweg 5 D-48351 Everswinkel info@swin-lack.de · Further information obtainable from: Laboratory department +49 2582-67613 / +49 2582-67677 · 1.4 Emergency telephone number: Giftinformationszentrum Göttingen (GIZ-Nord) Phone: +49 (0)551-19240 **2** Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS08 health hazard STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. GHS07 Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2) EU



Version number 3 (replaces version 2)

Revision: 15.02.2024

Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER

Hazard pictog	(Contd. of page 1
<u>く ()) く ()</u>	
GHS02 GH	IS07 GHS08
Signal word D	anger
	nining components of labelling:
xylene	
	hloriert,maleinsäureanhydried,modifiziert
ethylbenzene	
Hazard statem	ents ble liquid and vapour.
H332 Harmful	
H315 Causes s	
	erious eye irritation.
	se an allergic skin reaction.
	se respiratory irritation.
	se damage to the hearing organs through prolonged or repeated exposure.
	fatal if swallowed and enters airways.
Precautionary	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. N smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+F	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin wit water [or shower].
P305+P351+F	2338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, a present and easy to do. Continue rinsing.
P337+P313	<i>If eye irritation persists: Get medical advice/attention.</i>
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
2.3 Other haza	
	r and vPvB assessment
PBT: Not appl	
vPvB: Not app	licable.

3 Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	50-100%		
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119892111-44-XXXX	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	2.5-10%		
CAS: 68609-36-9	Polypropylen, chloriert, maleinsäure anhydried, modifiziert ♦ Skin Sens. 1, H317	<i>≤</i> 2.5%		
(Contd. on pa				



Version number 3 (replaces version 2)

Revision: 15.02.2024

Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER

• Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

4 First aid measures

- 4.1 Description of first aid measures
- General information: Personal protection for the First Aider.
- After inhalation:
- Supply fresh air.
- Seek medical treatment in case of complaints.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to section 13.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

7 Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Restrict the quantity stored at the work place.
- Information about fire and explosion protection: Fumes can combine with air to form an explosive mixture. Flammable gas-air mixtures may form in empty receptacles. Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.

(Contd. on page 4)

EU



Version number 3 (replaces version 2)

Revision: 15.02.2024

Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.*
- Suitable material for receptacles and pipes: steel or stainless steel.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

100-41-4 ethylbenzene

IOELV Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.
- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A2/P2

Hand protection

Only use chemical-protective gloves with CE-labelling of category III.



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be checked prior to the application.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber (Ansell Sol-Vex®)

Recommended thickness of the material: $\geq 0.4 \text{ mm}$

· Penetration time of glove material

Value for the permeation: Level ≤ 1

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®)

(Contd. on page 5)

EU



Version number 3 (replaces version 2)

Revision: 15.02.2024

(Contd. of page 4)

Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER

· Eye/face protection



Tightly sealed goggles

Body protection:

Protective clothing, anti-static (TYVEK® CLASSIC PLUS) Safety shoes/boots, antstatic

9 Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Physical state Fluid · Colour: Colourless · Odour: Aromatic Not determined. · Odour threshold: • *Melting point/freezing point:* Undetermined. · Boiling point or initial boiling point and boiling 140 °C range · Flammability Flammable. · Lower and upper explosion limit · Lower: 1.1 Vol % 7 Vol % · Upper: 23 - 60 °C · Flash point: 430 °C • Auto-ignition temperature: Not determined. · Decomposition temperature: · pH-value Not applicable. · Viscosity: · Kinematic viscosity at 20 °C 11 s (DIN 53211/4) · Dynamic: Not determined. · Solubility · water: Not miscible or difficult to mix. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 6.7 hPa · Density and/or relative density · Relative density Not determined. · Densitv Not determined. · Vapour density • 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Change in condition Not determined. · Evaporation rate · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void Void · Aerosols Void • Oxidising gases Gases under pressure Void (Contd. on page 6)



Version number 3 (replaces version 2)

Revision: 15.02.2024

Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER

		(Contd. of page 5)
· Flammable liquids	Flammable liquid and vapour.	
· Flammable solids	Void	
• Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

10 Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

· Skin corrosion/irritation Causes skin irritation.

- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation.

• **STOT-repeated exposure** May cause damage to the hearing organs through prolonged or repeated exposure. • **Aspiration hazard** May be fatal if swallowed and enters airways.

• 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)



Version number 3 (replaces version 2)

Revision: 15.02.2024

Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MESU and removal of paint and varnish

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00: packaging (including separately collected municipal packaging waste)

15 01 10*: packaging containing residues of or contaminated by dangerous substances

• **Recommendation:** Disposal must be made according to official regulations.

14 Transport information · 14.1 UN number or ID number · ADR, IMDG, IATA UN1263 · 14.2 UN proper shipping name ·ADR 1263 PAINT RELATED MATERIAL · IMDG, IATA PAINT RELATED MATERIAL · 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 3 Flammable liquids. 3 · Label · 14.4 Packing group Ш · ADR, IMDG, IATA · 14.5 Environmental hazards: · Marine pollutant: No Warning: Flammable liquids. · 14.6 Special precautions for user · Hazard identification number (Kemler code): 30 F-E, S-E· EMS Number: (Contd. on page 8) FΠ

(Contd. of page 6)



Version number 3 (replaces version 2)

Revision: 15.02.2024

Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER

	(Contd. of page
· Stowage Category	Α
· 14.7 Maritime transport in bulk according	to IMO
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

• Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)



Version number 3 (replaces version 2)

Revision: 15.02.2024

Trade name: SWIN KUNSTSTOFF-HAFTVERMITTLER

(Contd. of page 8)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. · Department issuing SDS: -· Contact: -• Date of previous version: 15.02.2024 • Version number of previous version: 2 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1