

Safety data sheet according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4)

Revision: 15.02.2024

	ntifier CODE 3003
Trade name: <u>SV</u>	VIN 2K HÄRTER KURZ
Article number:	
UFI: E820-A0Q	
1.2 Relevant ide Sector of Use	ntified uses of the substance or mixture and uses advised against
	uses: Uses of substances as such or in preparations at industrial sites
	nal uses: Public domain (administration, education, entertainment, services, craftsmen)
	y PC9a Coatings and paints, thinners, paint removers
Process categor y PROC7 Industr	
	ndustrial spraying
Environmental i	release category ERC8c Widespread use leading to inclusion into/onto article (indoor)
Application of the second s	he substance / the mixture Hardening agent/ Curing agent
	e supplier of the safety data sheet
Manufacturer/S Swin Lacksyster	
Swin Lacksystem Boschweg 5	
D-48351 Eversw	
info@swin-lack.	de
Further informa	ition obtainable from:
Laboratory depa	
	3 / +49 2582-67677
	t elephone number: zentrum Göttingen (GIZ-Nord) Phone: +49 (0)551-19240
Hazards iden 2.1 Classificatio	
Hazards iden 2.1 Classificatio Classification ad	tification n of the substance or mixture
Hazards iden 2.1 Classificatio Classification ad	tification n of the substance or mixture ecording to Regulation (EC) No 1272/2008
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3	tification n of the substance or mixture ecording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3	tification n of the substance or mixture ccording to Regulation (EC) No 1272/2008 2 flame
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 GHS0	tification n of the substance or mixture ecording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 GHS0 STOT RE 2	tification n of the substance or mixture coording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard
Hazards iden 2.1 Classificatio Classification ac GHS0 Flam. Liq. 3 GHS0 STOT RE 2	tification n of the substance or mixture ecording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 GHS0 STOT RE 2	tification n of the substance or mixture eccording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 Flam. Liq. 3 GHS0 STOT RE 2 Asp. Tox. 1 GHS0	tification n of the substance or mixture coording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 7
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 GHS0 STOT RE 2 Asp. Tox. 1 GHS0 Acute Tox. 4	tification n of the substance or mixture coording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 GHS0 STOT RE 2 Asp. Tox. 1 GHS0 Acute Tox. 4 Skin Irrit. 2	tification n of the substance or mixture ccording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 7 H332 Harmful if inhaled. H315 Causes skin irritation.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 Flam. Liq. 3 GHS0 STOT RE 2 Asp. Tox. 1 GHS0 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2	tification n of the substance or mixture ccording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 7 H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 GHS0 STOT RE 2 Asp. Tox. 1 GHS0 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1	tification n of the substance or mixture excording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 7 H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 GHS0 STOT RE 2 Asp. Tox. 1 GHS0 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 STOT SE 3	tification n of the substance or mixture eccording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 7 H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.
Hazards iden 2.1 Classificatio Classification ad GHS0 Flam. Liq. 3 GHS0 STOT RE 2 Asp. Tox. 1 GHS0 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 STOT SE 3	tification n of the substance or mixture excording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 7 H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.
Hazards iden 2.1 Classificatio Classification ad Classification ad GHS0 Flam. Liq. 3 GHS0 STOT RE 2 Asp. Tox. 1 GHS0 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 STOT SE 3 Aquatic Chronic 2.2 Label eleme	<i>tification</i> n of the substance or mixture scording to Regulation (EC) No 1272/2008 2 flame H226 Flammable liquid and vapour. 8 health hazard H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. 7 H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes an allergic skin reaction. H317 May cause en allergic skin reaction. H335 May cause respiratory irritation. 3 H412 Harmful to aquatic life with long lasting effects.



Version number 5 (replaces version 4)

Revision: 15.02.2024

Trade name: SWIN 2K HÄRTER KURZ

Hazard pictogr	(Contd. of pag
JUL 1	
GHS02 GH	S07 GHS08
Signal word Da	anger
Hazard-determ	ining components of labelling:
	-2 Hexamethylen-1,6-diisocyanat Homopolymer
	rierungsnummer: 01-2119457571-37-0000
	(Gew%): < 0,1
xylene	
	a (petroleum), light arom.
4-isocyanatosu	
Hazard stateme	
H226 Flammab	ble liquid and vapour.
H332 Harmful	
H315 Causes st	
H319 Causes se	erious eye irritation.
H317 May caus	se an allergic skin reaction.
H335 May caus	se respiratory irritation.
H373 May caus	se damage to organs through prolonged or repeated exposure.
H304 May be fo	atal if swallowed and enters airways.
H412 Harmful	to aquatic life with long lasting effects.
Precautionary	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/heari protection.
P303+P361+P	2353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin w
	water [or shower].
P305+P351+P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses
	present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
2.3 Other haza	

• **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

$C_{4}C_{5}$, 29192 , 91.2 , Hongmothylon, 1.6, diagonangt 50,1000
CAS: 28182-81-2 Hexamethylen-1,6-diisocyanat 50-1009
Homopolymer
REACH Registrierungsnummer: 01-2119457571-37-0000
Konzentration (Gew%): $< 0,1$
() Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3,
H335

- EU



Version number 5 (replaces version 4)

Revision: 15.02.2024

Trade name: SWIN 2K HÄRTER KURZ

CAS: 123-86-4	n-butyl acetate	td. of page 2 10-25%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066	
EINECS: 215-535-7	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119486773-24-XXXX	Solvent naphtha (petroleum), light arom. Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; STOT SE 3, H335	2.5-10%
Reg.nr.: 01-2119980050-47-XXXX	4-isocyanatosulphonyltoluene	<i>≤</i> 2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- 4.1 Description of first aid measures
- · General information: Personal protection for the First Aider.
- After inhalation:
- Supply fresh air.
- Seek medical treatment in case of complaints.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- *After swallowing:* Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- *Protective equipment:* Mouth respiratory protective device.

6 Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

EU



Version number 5 (replaces version 4)

Revision: 15.02.2024

Trade name: SWIN 2K HÄRTER KURZ

5.5 1110.	(Contd. of p thods and material for containment and cleaning up:
Absorh	with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
	e contaminated material as waste according to section 13.
	ference to other sections
	tion 7 for information on safe handling.
See Sec	tion 8 for information on personal protection equipment.
Hand	ling and storage
	cautions for safe handling
	good ventilation/exhaustion at the workplace.
	t the quantity stored at the work place.
	130 Isocyanate - Exposition und Überwachung beachten.
	ation about fire - and explosion protection:
	can combine with air to form an explosive mixture.
	able gas-air mixtures may form in empty receptacles.
	nition sources away - Do not smoke.
	plosion-proof apparatus / fittings and spark-proof tools. against electrostatic charges.
	nditions for safe storage, including any incompatibilities
Storage	
	ements to be met by storerooms and receptacles:
Provide	e solvent resistant, sealed floor.
	e material for receptacles and pipes: steel or stainless steel.
	ation about storage in one common storage facility: Not required.
	r information about storage conditions: Keep container tightly sealed.
-	cific end use(s) No further relevant information available. Sure controls/personal protection
Expos	
Expos 8.1 Cor Ingredi	sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace:
Expos 8.1 Cor Ingredi 123-86	sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate
Expos 8.1 Cor Ingredi 123-86	Sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m ³ , 150 ppm
Expos 8.1 Cor Ingredi 123-86 IOELV	Sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm
Expos 8.1 Con Ingredi 123-86 IOELV 108-65	sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm -6 2-methoxy-1-methylethyl acetate
Expos 8.1 Con Ingredi 123-86 IOELV 108-65	<i>Sure controls/personal protection</i> <i>ntrol parameters</i> <i>ients with limit values that require monitoring at the workplace:</i> <i>-4 n-butyl acetate</i> <i>Short-term value: 723 mg/m³, 150 ppm</i> <i>Long-term value: 241 mg/m³, 50 ppm</i> <i>-6 2-methoxy-1-methylethyl acetate</i> <i>Short-term value: 550 mg/m³, 100 ppm</i>
Expos 8.1 Con Ingredi 123-86 IOELV 108-65	Sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm
Expos 8.1 Con Ingreda 123-86 IOELV 108-65 IOELV	<i>Sure controls/personal protection</i> <i>ntrol parameters</i> <i>ients with limit values that require monitoring at the workplace:</i> <i>-4 n-butyl acetate</i> <i>Short-term value: 723 mg/m³, 150 ppm</i> <i>Long-term value: 241 mg/m³, 50 ppm</i> <i>-6 2-methoxy-1-methylethyl acetate</i> <i>Short-term value: 550 mg/m³, 100 ppm</i>
Expos 8.1 Con Ingredu 123-86 IOELV 108-65 IOELV Additio 8.2 Exp	sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Short-term value: 750 mg/m³, 50 ppm Long-term value: 550 mg/m³, 50 ppm Short-term value: 755 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Short term value: 275 mg/m³, 50 ppm
Expos 8.1 Con Ingreda 123-86 IOELV 108-65 IOELV Additio 8.2 Exp Approp	Aure controls/personal protection atrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Skin onal information: The lists valid during the making were used as basis. posure controls priate engineering controls No further data; see section 7.
Expos 8.1 Con Ingreda 123-86 IOELV 108-65 IOELV Additio 8.2 Exp Approp Individ	Sure controls/personal protection atrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin mal information: The lists valid during the making were used as basis. posure controls priate engineering controls No further data; see section 7. ual protection measures, such as personal protective equipment
Expos 8.1 Con Ingredi 123-86 IOELV 108-65 IOELV Additio 8.2 Exp Approp Individ Genera	sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin mal information: The lists valid during the making were used as basis. posure controls priate engineering controls No further data; see section 7. Yual protection measures, such as personal protective equipment of protective and hygienic measures:
Expos 8.1 Con Ingredi 123-86 IOELV 108-65 IOELV Additio 8.2 Exp Approp Individ Genera Keep a	sure controls/personal protection atrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Skin nal information: The lists valid during the making were used as basis. posure controls riate engineering controls No further data; see section 7. ual protection measures, such as personal protective equipment di protective and hygienic measures: way from foodstuffs, beverages and feed.
Expos 8.1 Con Ingredi 123-86 10ELV 108-65 10ELV Additio 8.2 Exp Approp Individ Genera Keep a Immedi	state controls/personal protection atrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate short-term value: 723 mg/m³, 150 ppm Short-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Skin nal information: The lists valid during the making were used as basis. posure controls protection measures, such as personal protective equipment Iprotective and hygienic measures: way from foodstuffs, beverages and feed. iately remove all soiled and contaminated clothing Stately
Expos 8.1 Con Ingredi 123-86 10ELV 108-65 10ELV Additio 8.2 Exp Approp Individ Genera Keep a Immedi Wash h	Sure controls/personal protection atrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin nal information: The lists valid during the making were used as basis. posure controls wriate engineering controls No further data; see section 7. ual protection measures, such as personal protective equipment A protective and hygienic measures: way from foodstuffs, beverages and feed. ately remove all soiled and contaminated clothing ands before breaks and at the end of work.
Expos 8.1 Con Ingredi 123-86 10ELV 108-65 10ELV Additio 8.2 Exp Approp Individ Genera Keep a Immedi Wash h Do not	sure controls/personal protection ntrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin nal information: The lists valid during the making were used as basis. posure controls oriate engineering controls No further data; see section 7. wal protection measures, such as personal protective equipment ul protective and hygienic measures: way from foodstuffs, beverages and feed. iately remove all soiled and contaminated clothing ands before breaks and at the end of work. inhale gases / fumes / aerosols.
Expos 8.1 Con Ingredi 123-86 10ELV 108-65 10ELV Additio 8.2 Exp Approp Individ Genera Keep a Immedi Wash h Do not Avoid c	Sure controls/personal protection atrol parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin nal information: The lists valid during the making were used as basis. posure controls wriate engineering controls No further data; see section 7. ual protection measures, such as personal protective equipment A protective and hygienic measures: way from foodstuffs, beverages and feed. ately remove all soiled and contaminated clothing ands before breaks and at the end of work.
Expos 8.1 Con Ingredi 123-86 10ELV 108-65 10ELV Additio 8.2 Exp Approp Individ Genera Keep a Immedi Wash h Do not Avoid c Respire Use sui	Autro controls/personal protection Introl parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Skin mal information: The lists valid during the making were used as basis. posure controls writate engineering controls No further data; see section 7. ual protection measures, such as personal protective equipment In protective and hygienic measures: way from foodstuffs, beverages and feed. iately remove all soiled and contaminated clothing ands before breaks and at the end of work. inhale gases / fumes / aerosols. contact with the eyes and skin. tutory protection: table respiratory protective device in case of insufficient ventilation.
Expos 8.1 Con Ingreda 123-86 IOELV 108-65 IOELV Additio 8.2 Exp Approp Individ Genera Keep a Immedu Wash h Do not Avoid c Respira Use sui In case	Aure controls/personal protection Introl parameters ients with limit values that require monitoring at the workplace: -4 n-butyl acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm -6 2-methoxy-1-methylethyl acetate Short-term value: 250 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Skin mal information: The lists valid during the making were used as basis. posure controls wriate engineering controls No further data; see section 7. ual protection measures, such as personal protective equipment al protective and hygienic measures: way from foodstuffs, beverages and feed. iately remove all soiled and contaminated clothing ands before breaks and at the end of work. inhale gases / finmes / aerosols. contact with the eyes and skin. thory protection: table respiratory protective device in case of insufficient ventilation. of brief exposure or low pollution use respiratory filter device. In case of intensive or longer export
Expos 8.1 Con Ingredi 123-86 IOELV 108-65 IOELV Additio 8.2 Exp Approp Individ Genera Keep a Immedi Wash h Do not Avoid c Respire Use sui In case use selj	http://www.controls/personal protection http://acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 723 mg/m³, 150 ppm 6 2-methoxy-1-methylethyl acetate Short-term value: 255 mg/m³, 50 ppm 6 2-methoxy-1-methylethyl acetate Short-term value: 275 mg/m³, 50 ppm Long-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Skin mal information: The lists valid during the making were used as basis. posure controls wriate engineering controls No further data; see section 7. ual protection measures, such as personal protective equipment Il protective and hygienic measures: way from foodstuffs, beverages and feed. iately remove all soiled and contaminated clothing ands before breaks and at the end of work. inhale gases / fumes / aerosols. contact with the eyes and skin. turp protection: table respiratory protective device in case of insufficient ventilation. of brief exposure or low pollution use respiratory filter device. In case of intensive or longer export-contained respiratory protective device.
Expos 8.1 Con Ingreda 123-86 IOELV 108-65 IOELV Additio 8.2 Exp Approp Individ Genera Keep a Immedu Wash h Do not Avoid c Respira Use sui In case	http://www.controls/personal protection http://acetate Short-term value: 723 mg/m³, 150 ppm Long-term value: 723 mg/m³, 150 ppm 6 2-methoxy-1-methylethyl acetate Short-term value: 255 mg/m³, 50 ppm 6 2-methoxy-1-methylethyl acetate Short-term value: 275 mg/m³, 50 ppm Long-term value: 275 mg/m³, 50 ppm Short-term value: 275 mg/m³, 50 ppm Skin mal information: The lists valid during the making were used as basis. posure controls wriate engineering controls No further data; see section 7. ual protection measures, such as personal protective equipment Il protective and hygienic measures: way from foodstuffs, beverages and feed. iately remove all soiled and contaminated clothing ands before breaks and at the end of work. inhale gases / fumes / aerosols. contact with the eyes and skin. turp protection: table respiratory protective device in case of insufficient ventilation. of brief exposure or low pollution use respiratory filter device. In case of intensive or longer export-contained respiratory protective device.



Version number 5 (replaces version 4)

Revision: 15.02.2024

(Contd. of page 4)

Trade name: SWIN 2K HÄRTER KURZ

· Hand protection

Only use chemical-protective gloves with CE-labelling of category III.



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be checked prior to the application.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber (Ansell Sol-Vex®)

Recommended thickness of the material: ≥ 0.4 mm

- · Penetration time of glove material
- *Value for the permeation: Level* $\leq l$

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®)
- · Eye/face protection



Tightly sealed goggles

· Body protection:

Protective clothing, anti-static (TYVEK® CLASSIC PLUS) Safety shoes/boots, antstatic

9 Physical and chemical properties

9.1 Information on basic physical and chemical p	properties				
General Information					
· Physical state	Fluid				
· Colour:	Colourless				
· Odour:	Aromatic				
· Odour threshold:	Not determined.				
• Melting point/freezing point:	Undetermined.				
• Boiling point or initial boiling point and boiling					
range	124 °C				
· Flammability	Flammable.				
· Lower and upper explosion limit					
· Lower:	1.1 Vol %				
· Upper:	10.8 Vol %				
· Flash point:	23 - 60 °C				
· Auto-ignition temperature:	315 °C				
· Decomposition temperature:	Not determined.				
· pH-value	Not applicable.				
· Viscosity:	**				
· Kinematic viscosity at 20 °C	12 s (DIN 53211/4)				
· Dynamic:	Not determined.				
· Solubility					
· water:	Not miscible or difficult to mix.				
· Partition coefficient n-octanol/water (log value)	Not determined.				
· Vapour pressure at 20 °C:	10.7 hPa				



Version number 5 (replaces version 4)

Revision: 15.02.2024

Trade name: SWIN 2K HÄRTER KURZ

	(Contd. of page
Density and/or relative density	
Relative density	Not determined.
Density	
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of heal	th and
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Change in condition	· · ·
Evaporation rate	Not determined.
Information with regard to physical hazard of	classes
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

10 Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Harmful if inhaled.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation
- Persons already sensitised to may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact with this product.
- May cause an allergic skin reaction.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

[–] EU



Version number 5 (replaces version 4)

Revision: 15.02.2024

(Contd. of page 6)

Trade name: SWIN 2K HÄRTER KURZ

- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Harmful to aquatic organisms

13 Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

	Luropean wasie Calalogue				
		8 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF			
		COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS			
		AND PRINTING INKS			
	08 01 00	wastes from MFSU and removal of paint and varnish			
Ī	08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances			

· Uncleaned packaging:

15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00: packaging (including separately collected municipal packaging waste)

15 01 10*: packaging containing residues of or contaminated by dangerous substances

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

• 14.1 UN number or ID number

· ADR, IMDG, IATA

UN1263

(Contd. on page 8)



Version number 5 (replaces version 4)

Revision: 15.02.2024

Trade name: SWIN 2K HÄRTER KURZ

	(Contd. of pag
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	N7
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	30 F-E,S-E
Stowage Category	A
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El Marimum not quantity par innor packaging: 20 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	<i>3</i>
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 9)

EU –



Version number 5 (replaces version 4)

Revision: 15.02.2024

(Contd. of page 8)

Trade name: SWIN 2K HÄRTER KURZ

· REGULATION (EU) 2019/1148

• Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

- *Employment restrictions concerning pregnant and lactating women must be observed.*
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- *H411 Toxic to aquatic life with long lasting effects.*

EUH014 Reacts violently with water.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing SDS: -

- · Contact: -
- Date of previous version: 15.02.2024
- Version number of previous version: 4
- · Abbreviations and acronyms:
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods
- IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2
- *Eye Irrit. 2: Serious eye damage/eye irritation Category 2*
- Resp. Sens. 1: Respiratory sensitisation Category 1
- Skin Sens. 1: Skin sensitisation Category 1

(Contd. on page 10)

EU



Version number 5 (replaces version 4)

Revision: 15.02.2024

(Contd. of page 9)

EU

Trade name: SWIN 2K HÄRTER KURZ

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	