

## **Safety data sheet according to UK REACH**

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** Q 70-425 Thermo Coating black Aerosol
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
  - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
  - SU21 Consumer uses: Private households / general public / consumers
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture:** painting
- **Uses advised against** No further relevant information available.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
  - Q-Company Int. GmbH
  - Lentföhrdener Strasse 12-14
  - D-24576 Weddelbrook Germany
- Tel.: +49 (0) 4192 891420  
e-mail: msds@qrefinish.com
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** TEL.: +49(0)551-19240 (Giftinformationszentrum-Nord)
- **national:**
  - National Poisons Information Service, Birmingham
  - Tel.: 844 892 0111
- **K-Nr.** 0055

### **SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame


Aerosol 1 H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)



## **Safety data sheet** **according to UK REACH**

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

(Contd. of page 1)


**· 2.2 Label elements****· Labelling according to Regulation (EC) No 1272/2008***The product is classified and labelled according to the GB CLP regulation.***· Hazard pictograms**

GHS02 GHS07

**· Signal word Danger****· Hazard-determining components of labelling:***acetone**n-butyl acetate**propan-2-ol**2-methoxy-1-methylethyl acetate***· Hazard statements***H222 Extremely flammable aerosol.**H229 Pressurised container: May burst if heated.**H319 Causes serious eye irritation.**H336 May cause drowsiness or dizziness.***· Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P103 Read carefully and follow all instructions.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P211 Do not spray on an open flame or other ignition source.**P251 Do not pierce or burn, even after use.**P271 Use only outdoors or in a well-ventilated area.**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P312 Call a POISON CENTER/doctor if you feel unwell.**P337+P313 If eye irritation persists: Get medical advice/attention.**P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***· Additional information:***Without adequate ventilation, explosive atmosphere/gas mix may be created.**Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.***· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.

(Contd. on page 3)

GB



## Safety data sheet according to UK REACH

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**· **vPvB:** Not applicable.

(Contd. of page 2)

### SECTION 3: Composition/information on ingredients


#### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

#### · **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-<50%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1-<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	1-<2.5%
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23-xxxx	i-butanol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3, H336	<1%

(Contd. on page 4)



## **Safety data sheet** **according to UK REACH**

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 3)

### **SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
  - **After inhalation:** Supply fresh air; consult doctor in case of complaints.
  - **After skin contact:** Generally the product does not irritate the skin.
  - **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
  - **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media -**
- **Suitable extinguishing agents:** Cool container with water
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.


### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)



## Safety data sheet according to UK REACH

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**


(Contd. of page 4)

**· Information about fire - and explosion protection:***Do not spray onto a naked flame or any incandescent material.**Keep ignition sources away - Do not smoke.**Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.***· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:***Observe official regulations on storing packagings with pressurised containers.***· Information about storage in one common storage facility: Not required.****· Further information about storage conditions: None.****· 7.3 Specific end use(s) No further relevant information available.**

### SECTION 8: Exposure controls/personal protection

**· 8.1 Control parameters****· Ingredients with limit values that require monitoring at the workplace:****67-64-1 acetone***WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm**Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm***115-10-6 dimethyl ether***WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm**Long-term value: 766 mg/m<sup>3</sup>, 400 ppm***123-86-4 n-butyl acetate***WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm**Long-term value: 724 mg/m<sup>3</sup>, 150 ppm***106-97-8 butane (containing ≤ 0,1 % butadiene (203-450-8))***WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm**Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm**Carc (if more than 0.1% of buta-1.3-diene)***1330-20-7 xylene, mixture of isomers***WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm**Long-term value: 220 mg/m<sup>3</sup>, 50 ppm**Sk; BMGV***67-63-0 propan-2-ol***WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm**Long-term value: 999 mg/m<sup>3</sup>, 400 ppm***100-41-4 ethylbenzene***WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm**Long-term value: 441 mg/m<sup>3</sup>, 100 ppm**Sk*

(Contd. on page 6)



## Safety data sheet according to UK REACH

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

(Contd. of page 5)

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

**78-83-1 i-butanol**

WEL Short-term value: 231 mg/m<sup>3</sup>, 75 ppm  
Long-term value: 154 mg/m<sup>3</sup>, 50 ppm

· **Regulatory information** WEL: EH40/2020

· **Ingredients with biological limit values:**

**1330-20-7 xylene, mixture of isomers**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

· **Regulatory information** BMGV: EH40/2011

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· **Hand protection**

Protective gloves




The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Penetration time of glove material**

Gloves must be changed after every contamination.

(Contd. on page 7)



## Safety data sheet according to UK REACH

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

(Contd. of page 6)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

butyl rubber, 0,7mm

- **Eye/face protection**

Safety glasses



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Physical state

Aerosol

##### · Colour:

According to product specification

##### · Odour:

Characteristic

##### · Odour threshold:

Not determined.

##### · Melting point/freezing point:

Undetermined.

##### · Boiling point or initial boiling point and boiling range

-44 °C

##### · Flammability

Not applicable.

##### · Lower and upper explosion limit

##### · Lower:

1.2 Vol % (123-86-4 n-butyl acetate)

##### · Upper:

18.6 Vol % (115-10-6 dimethyl ether)

##### · Flash point:

-97 °C (74-98-6 propane)

##### · Auto-ignition temperature:

235 °C (115-10-6 dimethyl ether)

##### · Decomposition temperature:

Not determined.

##### · pH

Mixture is non-polar/aprotic.

##### · Viscosity:

##### · Kinematic viscosity

Not determined.

##### · Dynamic:

Not determined.

##### · Solubility

##### · water:

Not miscible or difficult to mix.

##### · Partition coefficient n-octanol/water (log value)

Not determined.

##### · Vapour pressure at 20 °C:

3,600 hPa (74-98-6 propane)

##### · Vapour pressure at 50 °C:

800 hPa

##### · Density and/or relative density

##### · Relative density


Not determined.

##### · Vapour density

Not determined.

(Contd. on page 8)

GB



## Safety data sheet according to UK REACH

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

(Contd. of page 7)

**· 9.2 Other information****· Appearance:****· Form:**

Aerosol

**· Important information on protection of health and environment, and on safety.****· Ignition temperature:**

Product is not selfigniting.

**· Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  
Not determined.

**· Solvent content:****· Organic solvents:**

90.5 %

With propellant gas. Content given by weight.

**· VOC (EU)**

(&lt;840g/l)

90.46 %

**· Solids content:**

9.5 %

**· Change in condition****· Evaporation rate**

Not applicable.

**· Information with regard to physical hazard classes****· Explosives**

Void

**· Flammable gases**

Void

**· Aerosols**

Extremely flammable aerosol. Pressurised container:  
May burst if heated.

**· Oxidising gases**

Void

**· Gases under pressure**

Void

**· Flammable liquids**

Void

**· Flammable solids**

Void

**· Self-reactive substances and mixtures**

Void

**· Pyrophoric liquids**

Void

**· Pyrophoric solids**

Void

**· Self-heating substances and mixtures**

Void

**· Substances and mixtures, which emit flammable gases in contact with water**

Void

**· Oxidising liquids**

Void

**· Oxidising solids**

Void

**· Organic peroxides**

Void

**· Corrosive to metals**

Void


**· Desensitised explosives**

Void

**SECTION 10: Stability and reactivity****· 10.1 Reactivity** No further relevant information available.

(Contd. on page 9)

GB



## Safety data sheet according to UK REACH

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

(Contd. of page 8)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Dermal	LD50	37,662 mg/kg (rabbit)
Inhalative	LC50/4 h	150 mg/l

- **Primary irritant effect:**
- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**


**Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 10)



**Safety data sheet**  
**according to UK REACH**

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol***Danger to drinking water if even small quantities leak into the ground.*

(Contd. of page 9)

**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation***Must not be disposed together with household garbage. Do not allow product to reach sewage system.*· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN number or ID number**· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· **ADR**· **Class**

2 5F Gases.

· **Label**

2.1

· **IMDG, IATA**· **Class**

2.1 Gases.

· **Label**


2.1

· **14.4 Packing group**· **ADR, IMDG, IATA**

Void

not classified

(Contd. on page 11)



## Safety data sheet according to UK REACH

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

(Contd. of page 10)


· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	- not classified
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
VOC 2004/42/EG: <840g/l

(Contd. on page 12)

GB

**Safety data sheet**  
**according to UK REACH**

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

(Contd. of page 11)

**· Poisons Act****· Regulated explosives precursors**

None of the ingredients is listed.

**· Regulated poisons**

None of the ingredients is listed.

**· Reportable explosives precursors**

67-64-1 acetone

Listed

**· Reportable poisons**

None of the ingredients is listed.

**· Directive 2012/18/EU****· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category P3a FLAMMABLE AEROSOLS****· Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**· National regulations:****· Technical instructions (air):**

Class	Share in %
NK	50-100


**· Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

- H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 13)



**Safety data sheet**  
**according to UK REACH**

Printing date 05.12.2024

Version number 1

Revision: 05.12.2024

**Trade name: Q 70-425 Thermo Coating black Aerosol**

(Contd. of page 12)

*H412 Harmful to aquatic life with long lasting effects.*  
*EUH018 In use may form flammable/explosive vapour-air mixture.*  
*EUH066 Repeated exposure may cause skin dryness or cracking.*

· **Department issuing SDS:** Product safety department

· **Abbreviations and acronyms:**

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*ATE: Acute toxicity estimate values*

*Flam. Gas 1A: Flammable gases – Category 1A*

*Aerosol 1: Aerosols – Category 1*

*: Aerosols – Category 3*

*Press. Gas (Comp.): Gases under pressure – Compressed gas*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· **\* Data compared to the previous version altered.**